



IMDG - UN card

UN 3170

UN number 3170		Shipping name ALUMINIUM SMELTING BY-PRODUCTS / ALUMINIUM RE-MELTING BY-PRODUCTS BIPRODUKTER FRA ALUMINIUMSMELTNING / BIPRODUKTER FRA ALUMINIUMOMSMELTNING				
Class 4.3	Packing group III	Hazard labels 4.3	Marine pollutant Maybe	EmS F-G, S-P	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels 		Marking UN 3170 ALUMINIUM SMELTING BY-PRODUCTS / ALUMINIUM RE-MELTING BY-PRODUCTS				
Packaging Can be packed in approved packaging according to packing instruction P002. Note: Packagings shall be hermetically sealed (PP31).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223). This entry includes materials and substances such as aluminium dross, aluminium skimmings, spent cathodes, spent potliner and aluminium salt slags. Before loading, these by-products shall be cooled to ambient temperature, unless they have been calcined to remove moisture. Cargo transport units containing bulk loads shall be adequately ventilated and protected against ingress of water throughout the journey (SP 244).						
Properties and observations Grey powder or lumps with some metallic inclusions. Contact with water may cause heating with possible evolution of flammable and toxic gases such as hydrogen and ammonia. This entry includes e.g. aluminium dross, aluminium skimmings, spent cathodes, spent potliner and aluminium salt slags.						
Tank type: T1		Transport in bulk			Orange panel	
Tank provisions: TP33		BK2			3170	
Stowage and segregation						
Stowage		If under deck, stow in a mechanically ventilated space (SW5). Keep as dry as reasonably practicable (H1).				
Segregation		Check the segregation table for sea transport. The substance belongs to group: powdered metals (SGG15). In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26).				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 1 kg Outer: 30 kg <i>Trays</i> Inner: 1 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. Parcel label: 		