



IMDG - UN card

UN 3486

UN number 3486		Shipping name CALCIUM HYPOCHLORITE MIXTURE, DRY, CORROSIVE CALCIUMHYPOCHLORIT, BLANDING, TØR, ÆTSENDE				
Class 5.1	Packing group III	Hazard labels 5.1+8	Marine pollutant Yes	EmS F-H, S-Q	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels   		Marking UN 3486 CALCIUM HYPOCHLORITE MIXTURE, DRY, CORROSIVE				
Packaging		Can be packed in approved packaging according to packing instruction P002. Note: Packagings shall be so constructed that explosion is not possible by reason of increased internal pressure. Cylinders, tubes and pressure drums shall not be used for these substances (PP8).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		These substances are liable to exothermic decomposition at elevated temperatures. Decomposition can be initiated by heat or by impurities (e.g. powdered metals (iron, manganese, cobalt, magnesium) and their compounds). During the course of transport, these substances shall be shaded from direct sunlight and all sources of heat and be placed in adequately ventilated areas (SP 314).				
Properties and observations		White or yellowish corrosive solid (powder, granules or tablets) with chlorine-like odour. Soluble in water. May cause fire in contact with organic material or ammonium compounds. Substances are liable to exothermic decomposition at elevated temperatures. This condition may lead to fire or explosion. Decomposition can be initiated by heat or by impurities (e.g. powdered metals (iron, manganese, cobalt, magnesium) and their compounds). Liable to heat slowly. Reacts with acids, evolving chlorine, an irritating, corrosive and toxic gas. In the presence of moisture, corrosive to most metals. Causes burns to skin, eyes and mucous membranes.				
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	–	Not allowed		3486		
Stowage and segregation						
Stowage		Must be protected from sources of heat (SW1). Cargo transport units shall be shaded from direct sunlight. Packages in cargo transport units shall be stowed so as to allow for adequate air circulation throughout the cargo (SW11).				
Segregation		Check the segregation table for sea transport. The substance belongs to group: hypochlorites (SGG8). Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG2 – ammonium compounds (SG38). Stow "separated from" SGG6 – cyanides (SG49). Stow "separated from" liquid organic substances (SG53). "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ)		Parcel label: 		Excepted quantities (EQ)		
Combination packaging Inner: 5 kg Outer: 30 kg				Combination packaging Inner: 30 mg Outer: 1000 mg		
Trays Inner: 5 kg Outer: 20 kg				Parcel label:  Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		