



IMDG - UN card

UN 0143

UN number 0143	Shipping name NITROGLYCERIN, DESENSITIZED NITROGLYCERIN, DESENSIBILISERET					
	Class 1.1D	Packing group —	Hazard labels 1.1D (See SP271)	Marine pollutant No	EmS F-B, S-Z	<i>ADR transport category: 1 ADR tunnel: (B1000C)</i>
Hazard labels  		Marking UN 0143 NITROGLYCERIN, DESENSITIZED				
Packaging Can be packed in approved, tested packaging according to packing instruction P115. Note: When boxes are used as outer packagings, inner packagings shall have taped screw cap closures and be not more than 5 litres capacity each. Inner packagings shall be surrounded with non-combustible absorbent cushioning materials. The amount of absorbent cushioning material shall be sufficient to absorb the liquid contents. Metal receptacles shall be cushioned from each other. Net mass of propellant is limited to 30 kg for each package when outer packagings are boxes (PP53). When drums are used as outer packagings and when intermediate packagings are drums, they shall be surrounded with non-combustible cushioning material in a quantity sufficient to absorb the liquid contents. A composite packaging consisting of a plastics receptacle in a metal drum may be used instead of the inner and intermediate packagings. The net volume of propellant in each package shall not exceed 120 litres (PP54). Bags shall be used as intermediate packagings when boxes are used as outer packagings (PP57). Drums shall be used as intermediate packagings when drums are used as outer packagings (PP58).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks This substance, when containing less alcohol, water or phlegmatizer than specified, shall not be transported, unless specifically authorized by the competent authority (SP 266). Lactose or glucose or similar materials may be used as a phlegmatizer provided that the substance contains not less than 90%, by mass, of phlegmatizer. The competent authority may authorize these mixtures to be classified under class 4.1 on the basis of series 6(c) tests of part I of the Manual of Tests and Criteria on at least three packages as prepared for transport. Mixtures containing at least 98%, by mass, of phlegmatizer are not subject to the provisions of the IMDG Code. Packages containing mixtures with not less than 90%, by mass, of phlegmatizer need not bear a "TOXIC" subsidiary hazard label (SP 271). This substance shall not be transported under the provisions of class 4.1 unless specifically authorized by the competent authority (see UN 0143 or UN 0150 as appropriate) (SP 272).						
Properties and Substance. This substance, when containing less alcohol, water or phlegmatizer than specified, shall not be						
Tank type:	Not allowed	Transport in bulk			Orange panel	
Tank provisions:	—	Not allowed			0143	
Stowage and segregation						
Stowage Must be protected from sources of heat (SW1).						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance must be kept separate from food and feedstuffs.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:				Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:		