



IMDG - UN card

UN 0495

UN number 0495		Shipping name 🇬🇧 PROPELLANT, LIQUID 🇩🇰 DRIVMIDDEL, FLYDENDE				
Class 1.3C	Packing group —	Hazard labels 1.3C	Marine pollutant Maybe	EmS F-B, S-Y	<i>ADR transport category: 1 ADR tunnel: (C5000D)</i>	
Hazard labels 		Marking UN 0495 PROPELLANT, LIQUID				
Packaging Can be packed in approved, tested packaging according to packing instruction P115. Note: When boxes are used as outer packagings, inner packagings shall have taped screw cap closures and be not more than 5 litres capacity each. Inner packagings shall be surrounded with non-combustible absorbent cushioning materials. The amount of absorbent cushioning material shall be sufficient to absorb the liquid contents. Metal receptacles shall be cushioned from each other. Net mass of propellant is limited to 30 kg for each package when outer packagings are boxes (PP53). When drums are used as outer packagings and when intermediate packagings are drums, they shall be surrounded with non-combustible cushioning material in a quantity sufficient to absorb the liquid contents. A composite packaging consisting of a plastics receptacle in a metal drum may be used instead of the inner and intermediate packagings. The net volume of propellant in each package shall not exceed 120 litres (PP54). Bags shall be used as intermediate packagings when boxes are used as outer packagings (PP57). Drums shall be used as intermediate packagings when drums are used as outer packagings (PP58).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks Unless it can be demonstrated by testing that the sensitivity of the substance in its frozen state is no greater than in its liquid state, the substance shall remain liquid during normal transport conditions. It shall not freeze at temperatures above -15°C (SP 224).						
Properties and observations See glossary of terms in appendix B of the IMDG Code.						
Tank type: Not allowed		Transport in bulk Not allowed			Orange panel 0495	
Stowage and segregation						
Stowage		Must be protected from sources of heat (SW1).				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:			