



IMDG - UN card

UN 1040

UN number 1040		Shipping name ETHYLENE OXIDE / ETHYLENE OXIDE WITH NITROGEN ETHYLENOXID MED NITROGEN				
Class 2.3	Packing group —	Hazard labels 2.3+2.1	Marine pollutant Maybe	EmS F-D, S-U	ADR transport category: 1 ADR tunnel: (B/D)	
Hazard labels  		Marking UN 1040 ETHYLENE OXIDE / ETHYLENE OXIDE WITH NITROGEN				
Packaging	Can be packed in approved packaging according to packing instruction P200.					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	Glass inner receptacles (such as ampoules or capsules) intended only for use in sterilization devices, when containing less than 30 mL of ethylene oxide per inner packaging with not more than 300 mL per outer packaging, may be transported in accordance with the provisions in chapter 3.5, irrespective of the indication of "EO" in column 7b of the Dangerous Goods List provided that: 1. After filling, each glass inner receptacle has been determined to be leak tight by placing the glass inner receptacle in a hot water bath at a temperature, and for a period of time, sufficient to ensure that an internal pressure equal to the vapour pressure of ethylene oxide at 55°C is achieved. Any glass inner receptacle showing evidence of leakage, distortion or other defect under this test shall not be transported under the terms of this special provision; 2. In addition to the packaging required by 3.5.2, each glass inner receptacle is placed in a sealed plastics bag compatible with ethylene oxide and capable of containing the contents in the event of breakage or leakage of the glass inner receptacle; and 3. Each glass inner receptacle is protected by a means of preventing puncture of the plastics bag (e.g. sleeves or cushioning) in the event of damage to the packaging (e.g. by crushing) (SP 342).					
Properties and observations	Liquefied, flammable, toxic gases with an ether-like odour. Heavier than air (1.5). Boiling point: 11 °C.					
Tank type:	T50	Transport in bulk		Orange panel		
Tank provisions:	TP20 TP90	Not allowed		1040		
Stowage and segregation						
Stowage	Stay clear of living quarters (SW2).					
Segregation	Check the segregation table for sea transport. There are no special requirements for segregation.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance must be kept separate from food and feedstuffs.					
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:			