




IMDG - UN card

UN 1046

UN number 1046		Shipping name HELIUM, COMPRESSED HELIUM, KOMPRIMERET				
Class 2.2	Packing group —	Hazard labels 2.2	Marine pollutant Maybe	EmS F-C, S-V	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels 		Marking UN 1046 HELIUM, COMPRESSED				
Packaging		Can be packed in approved packaging according to packing instruction P200.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		Radiation detectors containing this gas in non-refillable pressure receptacles not meeting the requirements of chapter 6.2 and packing instruction P200 of 4.1.4.1 may be transported under this entry provided: 1. The working pressure in each receptacle does not exceed 50 bar; 2. The receptacle capacity does not exceed 12 litres; 3. Each receptacle has a minimum burst pressure of at least 3 times the working pressure when a relief device is fitted and at least 4 times the working pressure when no relief device is fitted; 4. Each receptacle is manufactured from material which will not fragment upon rupture; 5. Each detector is manufactured under a registered quality assurance programme; Note: ISO 9001:2008 may be used for this purpose. 6. Detectors are transported in strong outer packagings. The complete package shall be capable of withstanding a 1.2 metre drop test without breakage of the detector or rupture of the outer packaging. Equipment that includes a detector shall be packed in a strong outer packaging unless the detector is afforded equivalent protection by the equipment in which it is contained; and 7. The transport document includes the following statement "Transport in accordance with special provision 378". Radiation detectors, including detectors in radiation detection systems, are not subject to any other requirements of the IMDG Code if the detectors meet the requirements in 1. to 6. above and the capacity of detector receptacles does not exceed 50 ml (SP 378). See special provision 392 in the IMDG Code. These substances may be transported in IMO type 9 tanks (SP 974).				
Properties and observations		Inert gas. Much lighter than air (0.14).				
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	—	Not allowed		1046		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 120 mL Outer: 30 kg <i>Trays</i> Inner: 120 mL Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mL Outer: 1000 mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. Parcel label: 		