



IMDG - UN card

UN 1262

UN number 1262		Shipping name OCTANES OCTANER				
Class 3	Packing group II	Hazard labels 3	Marine pollutant Yes	EmS F-E, S-E	<i>ADR transport category: 2</i> <i>ADR tunnel: (D/E)</i>	
Hazard labels 		Marking UN 1262 OCTANES				
Packaging		Can be packed in approved packaging according to packing instruction P001.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		Colourless liquids. Explosive limits: 1% to 6.5%. ISOCTANE: flashpoint -12 °C c.c. n-OCTANE: flashpoint 13 °C c.c. Immiscible with water.				
Tank type: T4		Transport in bulk		Orange panel		
Tank provisions: TP2		Not allowed		1262		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ)		Parcel label:		Excepted quantities (EQ)		
Combination packaging				Combination packaging		
Inner: 1 L				Inner: 30 mL		
Outer: 30 kg				Outer: 500 mL		
Trays				Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
Inner: 1 L						
Outer: 20 kg						