



IMDG - UN card

UN 1263

UN number 1263		Shipping name PAINT / PAINT RELATED MATERIAL MALING / MALINGRELATEREDE PRODUKTER				
Class 3	Packing group III	Hazard labels 3	Marine pollutant Maybe	EmS F-E, S-E	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels 		Marking UN 1263 PAINT / PAINT RELATED MATERIAL				
Packaging Can be packed in approved packaging according to packing instruction P001. Note: Metal or plastics packagings for substances in quantities of 5 litres or less per packaging are not required to be UN specification packaging when carried (a) in palletized loads, a pallet box or unit load device, e.g. individual packagings placed or stacked and secured by strapping, shrink or stretch-wrapping or other suitable means to a pallet; or (b) as inner packagings of combination packagings with a maximum net mass of 40 kg (PP1). Can also be packaged in large packagings (LP01).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks A substance specifically listed by name in the Dangerous Goods List shall not be transported under this entry. Materials transported under this entry may contain 20% or less nitrocellulose provided the nitrocellulose contains not more than 12.6% nitrogen (by dry mass) (SP 163). If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223). For the purposes of documentation and package marking: The proper shipping name "PAINT RELATED MATERIAL" may be used for consignments of packages containing "PAINT" and "PAINT RELATED MATERIAL" in the same package; The proper shipping name "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for consignments of packages containing "PAINT, CORROSIVE, FLAMMABLE" and "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" in the same package; The proper shipping name "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for consignments of packages containing "PAINT, FLAMMABLE, CORROSIVE" and "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" in the same package; and The proper shipping name "PRINTING INK RELATED MATERIAL" may be used for consignments of packages containing "PRINTING INK" and "PRINTING INK RELATED MATERIAL" in the same package (SP 367). If a viscous substance and its packaging fulfils the provisions of 2.3.2.5, the packing provisions of chapter 4.1, the marking and labelling provisions of chapter 5.2 and the package testing provisions of chapter 6.1 are not applicable (SP 955).						
Tank type: T2		Transport in bulk Not allowed			Orange panel 1263	
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 L Outer: 30 kg <i>Trays</i> Inner: 5 L Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mL Outer: 1000 mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		