



IMDG - UN card

UN 1309

UN number 1309		Shipping name ALUMINIUM POWDER, COATED ALUMINIUMPULVER, OVERTRUKKET				
Class 4.1	Packing group III	Hazard labels 4.1	Marine pollutant Maybe	EmS F-G, S-G	<i>ADR transport category: 3 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 1309 ALUMINIUM POWDER, COATED				
Packaging	Can be packed in approved packaging according to packing instruction P002. Note: 5H1, 5L1 and 5M1 bags are allowed if they are overpacked in plastic bags and are wrapped in shrink or stretch wrap on pallets (PP11). Bags are permitted only in closed vehicles or containers (PP38). The packaging shall be vented (PP10). Can also be packaged in large packagings (LP02).					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223).					
Properties and observations	See entry above.					
Tank type:	T1	Transport in bulk		Orange panel		
Tank provisions:	TP33	Not allowed		1309		
Stowage and segregation						
Stowage	Keep as dry as reasonably practicable (H1).					
Segregation	Check the segregation table for sea transport. The substance belongs to group: powdered metals (SGG15). Stow "separated from" class 5.1 (SG17). Stow "separated from" goods of classes 2.1 and 3 (SG25). In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "away from" SGG10 – liquid halogenated hydrocarbons (SG32). "Away/separated from": May not be loaded into the same transport unit.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance is not required to be kept separate from food and feed.					
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 kg Outer: 30 kg <i>Trays</i> Inner: 5 kg Outer: 20 kg		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.				
Parcel label: 		Parcel label: 				