



IMDG - UN card

UN 1309

UN number 1309		Shipping name ALUMINIUM POWDER, COATED ALUMINIUMPULVER, OVERTRUKKET				
Class 4.1	Packing group II	Hazard labels 4.1	Marine pollutant Maybe	EmS F-G, S-G	<i>ADR transport category: 2 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 1309 ALUMINIUM POWDER, COATED				
Packaging		Can be packed in approved packaging according to packing instruction P002. Note: Bags are permitted only in closed vehicles or containers (PP38). The packaging shall be vented (PP10).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		If uncoated, it possesses the property of evolving hydrogen gas when in contact with water, especially seawater; if treated with oil or wax, it does not at ordinary temperatures. Reacts readily with acids and caustic alkalis, evolving hydrogen, a flammable gas. Reacts readily with iron oxide, producing a thermite effect. May form explosive mixtures with oxidizing substances. In the event of breakage of receptacles, the scattered powder is readily ignited by sparks or open flame and may give rise to an explosive atmosphere.				
Tank type:	T3	Transport in bulk		Orange panel		
Tank provisions:	TP33	Not allowed		1309		
Stowage and segregation						
Stowage		Keep as dry as reasonably practicable (H1).				
Segregation		Check the segregation table for sea transport. The substance belongs to group: powdered metals (SGG15). Stow "separated from" class 5.1 (SG17). Stow "separated from" goods of classes 2.1 and 3 (SG25). In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "away from" SGG10 – liquid halogenated hydrocarbons (SG32). "Away/separated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 1 kg Outer: 30 kg <i>Trays</i> Inner: 1 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 500 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		