




IMDG - UN card

UN 1405

UN number 1405		Shipping name CALCIUM SILICIDE CALCIUMSILICID				
Class 4.3	Packing group III	Hazard labels 4.3	Marine pollutant Maybe	EmS F-G, S-N	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels 		Marking UN 1405 CALCIUM SILICIDE				
Packaging Can be packed in approved packaging according to packing instruction P410. Note: Packagings shall be hermetically sealed (PP31).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223). Requires a certificate from the maker or shipper, stating that the shipment was stored under cover, but in the open air, in the size in which it was packaged, for not less than 3 days prior to shipment (SP 932).						
Properties and observations In contact with water, evolves hydrogen, a flammable gas. If calcium carbide is present as an impurity, acetylene will also be evolved. In contact with acids, evolves silane, a spontaneously flammable gas.						
Tank type: T1		Transport in bulk		Orange panel		
Tank provisions: TP33		Not allowed		1405		
Stowage and segregation						
Stowage		If under deck, stow in a mechanically ventilated space (SW5). Keep as dry as reasonably practicable (H1).				
Segregation		Check the segregation table for sea transport. In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "separated from" SGG1 – acids (SG35). "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 1 kg Outer: 30 kg <i>Trays</i> Inner: 1 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. Parcel label: 		