



IMDG - UN card

UN 1486

UN number 1486		Shipping name POTASSIUM NITRATE KALIUMNITRAT				
Class 5.1	Packing group III	Hazard labels 5.1	Marine pollutant Maybe	EmS F-A, S-Q	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels 		Marking UN 1486 POTASSIUM NITRATE				
Packaging	Can be packed in approved packaging according to packing instruction P002. Can also be packaged in large packagings (LP02).					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	This substance is not subject to the provisions of the IMDG Code when transported in non-friable prills or granules form and if it passes the test for oxidizing solid substances as reflected in the Manual of Tests and Criteria (see 34.4.1) and is accompanied by a certificate from a laboratory accredited by a competent authority, stating that the product has been correctly sampled by trained staff from the laboratory and that the sample was correctly tested and has passed the test. 1. When transported in cargo transport units, the cargo transport units shall provide an adequate exchange of air in the unit (e.g. by using a ventilated container, open-top container or container in one door off operation) to prevent the build-up of an explosive atmosphere. Alternatively, these entries shall be transported under temperature control in refrigerated cargo transport units that comply with the provisions of 7.3.7.6. When cargo transport units with venting devices are used, these devices shall be kept clear and operable. When mechanical devices are used for ventilation, they shall be explosion-proof to prevent ignition of flammable vapours from the substances. 2. The provisions of .1 do not apply if: 1. the substance is packed in hermetically sealed packagings or IBCs, which conform to packing group II performance level for liquid dangerous goods according to the provisions of 6.1 or 6.5, respectively; and 2. the marked hydraulic test pressure exceeds 1.5 times the total gauge pressure in the packagings or IBCs determined at 55°C for the respective filling goods according to 4.1.1.10.1. 3. Where the substance is loaded in closed cargo transport units, the provisions of 7.3.6.1 shall be met. 4. Cargo transport units shall be marked with a warning mark including the words "CAUTION – MAY CONTAIN FLAMMABLE VAPOUR" with lettering not less than 25 mm high. This mark shall be affixed at each access point in a location where it will be easily seen by persons prior to opening or entering the cargo transport unit and shall remain on the cargo transport unit until the following provisions are met: 1. the cargo transport unit has been completely ventilated to remove any hazardous concentration of vapour or gas; 2. the immediate vicinity of the cargo transport unit is clear of any source of ignition; and 3. the goods have been unloaded (SP 964). Flexible					
Tank type:	T1	Transport in bulk		Orange panel		
Tank provisions:	TP33	BK2 / BK3		1486		
Stowage and segregation						
Stowage	When transported in BK3 bulk container, see 7.6.2.12 and 7.7.3.9 of the IMDG Code (SW23).					
Segregation	Check the segregation table for sea transport. There are no special requirements for segregation.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance is not required to be kept separate from food and feed.					
Limited quantities (LQ)		Excepted quantities (EQ)				
Combination packaging		Combination packaging				
Inner: 5 kg		Inner: 30 mg				
Outer: 30 kg		Outer: 1000 mg				
Trays		Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.				
Inner: 5 kg						
Outer: 20 kg						
Parcel label:		Parcel label:				
						