



IMDG - UN card

UN 1555

UN number 1555		Shipping name ARSENIC BROMIDE ARSENBROMID				
Class 6.1	Packing group II	Hazard labels 6.1	Marine pollutant Maybe	EmS F-A, S-A	<i>ADR transport category: 2</i> <i>ADR tunnel: (D/E)</i>	
Hazard labels 		Marking UN 1555 ARSENIC BROMIDE				
Packaging		Can be packed in approved packaging according to packing instruction P002.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		White, deliquescent crystals. Melting point: approximately 33 °C. Decomposed by water, evolving hydrogen bromide, an irritating and corrosive gas, apparent as white fumes. Toxic if swallowed, by skin contact or by dust inhalation.				
Tank type:	T3	Transport in bulk		Orange panel		
Tank provisions:	TP33	Not allowed		1555		
Stowage and segregation						
Stowage		Must be protected from sources of heat (SW1). Stay clear of living quarters (SW2). Keep as cool as reasonably practicable (H2).				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ)		Parcel label:		Excepted quantities (EQ)		
Combination packaging				Combination packaging		
Inner: 500 g				Inner: 1 mg el. mL		
Outer: 30 kg				Outer: 500 mg el. mL		
Trays				Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
Inner: 500 g						
Outer: 20 kg						