



IMDG - UN card

UN 1759

UN number 1759		Shipping name CORROSIVE SOLID, N.O.S. ÆTSENDE FAST STOF, N.O.S.				
Class 8	Packing group II	Hazard labels 8	Marine pollutant Maybe	EmS F-A, S-B	<i>ADR transport category: 2</i> <i>ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 1759 CORROSIVE SOLID, N.O.S. (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging Can be packed in approved packaging according to packing instruction P002.						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks There are no special provisions for this substance.						
Properties and observations Causes burns to skin, eyes and mucous membranes.						
Tank type: T3		Transport in bulk		Orange panel		
Tank provisions: TP33		Not allowed		1759		
Stowage and segregation						
Stowage There are no special requirements for stowage.						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation. Note that for this substance, the consignor must assign the substance to a segregation group based on the substance's physical and chemical properties, if applicable.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance must be kept separate from food and feedstuffs.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: 1 kg Outer: 30 kg <i>Trays</i> Inner: 1 kg Outer: 20 kg		Parcel label: 				
		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 500 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		Parcel label: 		