



IMDG - UN card

UN 1824

UN number 1824		Shipping name SODIUM HYDROXIDE SOLUTION NATRIUMHYDROXIDOPLØSNING				
Class 8	Packing group II	Hazard labels 8	Marine pollutant Maybe	EmS F-A, S-B	<i>ADR transport category: 2 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 1824 SODIUM HYDROXIDE SOLUTION				
Packaging		Can be packed in approved packaging according to packing instruction P001.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		Colourless liquid. Corrosive to aluminium, zinc and tin. Reacts with ammonium salts, evolving ammonia gas. Causes burns to skin, eyes and mucous membranes. Reacts violently with acids.				
Tank type: T7		Transport in bulk		Orange panel		
Tank provisions: TP2		Not allowed		1824		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. The substance belongs to group: alkalis (SGG18). Stow "separated from" SGG1 – acids (SG35). "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ)		Parcel label:		Excepted quantities (EQ)		
Combination packaging				Combination packaging		
Inner: 1 L				Inner: 30 mL		
Outer: 30 kg				Outer: 500 mL		
Trays				Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
Inner: 1 L						
Outer: 20 kg						