



IMDG - UN card

UN 2037

UN number 2037	Shipping name RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES) BEHOLDERE, SMÅ, INDEHOLDENDE GAS					
	Class 2	Packing group —	Hazard labels See SP303	Marine pollutant Maybe	EmS F-D, S-U	ADR transport category: 1,2,3 ADR tunnel: (D)/(E)
Hazard labels Beholdere skal henføres til gassens klasse og evt. sekundære fare iht. IMDG-koden.		Marking UN 2037 RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)				
Packaging Can be packed in suitable packaging according to packing instruction P003. Note: Packages shall not exceed 55 kg net mass for fibreboard packagings or 125 kg net mass for other packagings (PP17). For UN 2037 waste gas cartridges carried in accordance with special provision 327 of Chapter 3.3, the packagings shall be adequately ventilated to prevent the creation of dangerous atmospheres and the build-up of pressure (PP96). Can also be packaged in large packagings (LP200).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks Receptacles with a capacity not exceeding 50 mL containing only non-toxic constituents are not subject to the provisions of the IMDG Code (SP 191). For aerosols or receptacles containing toxic substances, the limited quantity value is 120 mL. For all other aerosols or receptacles, the limited quantity value is 1,000 mL (SP 277). Receptacles shall be assigned to the class and, if any, subsidiary hazard of the gas or mixture of gases contained therein determined in accordance with the provisions of chapter 2.2 (SP 303). Waste aerosol containers and gas cartridges can be transported under UN 1950 or 2037, for reprocessing/disposal purposes. Protection against movement and accidental discharge is not necessary if measures are taken to avoid dangerous pressure build-up. Waste gas cartridges which were filled with non-flammable, non-toxic Class 2 gases and which have been perforated are not subject to the IMDG Code (SP 327). The provisions of 6.2.4 shall be met (SP 344). Waste aerosols or waste gas cartridges authorized for transport under special provision 327 shall only be transported on short international voyages. Long international voyages are authorized only with the approval of the competent authority. Packagings shall be marked and labelled and cargo transport units shall be marked and placarded for appropriate sub-division of class 2 and, if applicable, the subsidiary hazard(s) (SP 959).						
Properties and observations Normally contain mixtures of liquefied butane and propane in various proportions for use in camping stoves, etc.						
Tank type: Not allowed		Transport in bulk Not allowed			Orange panel 2037	
Stowage and segregation						
Stowage		Stay clear of living quarters (SW2). For AEROSOLS with a maximum capacity of 1 L: category A. For AEROSOLS with a capacity above 1 L: category B. For WASTE AEROSOLS: category C, clear of living quarters (SW22).				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 1 L (120 mL, hvis giftig) Outer: 30 kg <i>Trays</i> Inner: 1 L (120 mL, hvis giftig)		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:		