



IMDG - UN card

UN 2211

UN number 2211		Shipping name POLYMERIC BEADS, EXPANDABLE EKSPANDERBARE POLYMERKUGLER				
Class 9	Packing group III	Hazard labels 9	Marine pollutant Maybe	EmS F-A, S-I	<i>ADR transport category: 3</i> <i>ADR tunnel: (D/E)</i>	
Hazard labels 		Marking UN 2211 POLYMERIC BEADS, EXPANDABLE				
Packaging Can be packed in approved packaging according to packing instruction P002. Note: Packagings are not required to meet the performance tests in Chapter 6.1 (PP14).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks Polymeric beads may be made from polystyrene, poly(methyl methacrylate) or other polymeric material. When it can be demonstrated that no flammable vapour, resulting in a flammable atmosphere, is evolved according to test U1 (Test method for substances liable to evolve flammable vapours) of part III, subsection 38.4.4 of the Manual of Tests and Criteria, polymeric beads, expandable, need not be classified under this UN number. This test should only be performed when declassification of a substance is considered (SP 382). Hydrogen peroxide aqueous solutions with less than 8% hydrogen peroxide are not subject to the provisions of the IMDG Code (SP 65).						
Properties and observations A moulding material in bead or granular form consisting predominantly of polystyrene, poly(methyl methacrylate) or other polymeric material and containing 5% to 8% of a volatile hydrocarbon which is predominantly pentane. During storage, a small proportion of this pentane is released to the atmosphere; this proportion increases at elevated temperatures.						
Tank type: T1		Transport in bulk			Orange panel	
Tank provisions: TP33		Not allowed			2211	
Stowage and segregation						
Stowage		Must be protected from sources of heat (SW1). When stowed under deck, mechanical ventilation shall be in accordance with SOLAS regulation II-2/19 (II-2/54) for flammable liquids with flashpoint below 23°C c.c (SW6).				
Segregation		Check the segregation table for sea transport. Segregation as for class 3 (SG5). Stow "separated from" class 1 except for division 1.4S (SG14). "Separated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 kg Outer: 30 kg <i>Trays</i> Inner: 5 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		