



IMDG - UN card

UN 2322

UN number 2322		Shipping name TRICHLOROBUTENE TRICHLORBUTEN				
Class 6.1	Packing group II	Hazard labels 6.1	Marine pollutant Yes	EmS F-A, S-A	<i>ADR transport category: 2</i> <i>ADR tunnel: (D/E)</i>	
Hazard labels  		Marking UN 2322 TRICHLOROBUTENE				
Packaging		Can be packed in approved packaging according to packing instruction P001.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		Colourless liquid. Immiscible with water. When heated, develops toxic and irritant gases such as phosgene and hydrogen chloride and may also explode. Toxic if swallowed, by skin contact or by inhalation.				
Tank type: T7		Transport in bulk		Orange panel		
Tank provisions: TP2		Not allowed		2322		
Stowage and segregation						
Stowage		Must be protected from sources of heat (SW1). Stay clear of living quarters (SW2).				
Segregation		Check the segregation table for sea transport. The substance belongs to group: liquid halogenated hydrocarbons (SGG10).				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 100 mL Outer: 30 kg <i>Trays</i> Inner: 100 mL Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 1 mL Outer: 500 mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		