



IMDG - UN card

UN 2793

UN number 2793		Shipping name FERROUS METAL BORINGS / SHAVINGS / TURNINGS / CUTTINGS METALLISK JERN, SOM SPÅNER				
Class 4.2	Packing group III	Hazard labels 4.2	Marine pollutant Maybe	EmS F-G, S-J	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels 		Marking UN 2793 FERROUS METAL BORINGS / SHAVINGS / TURNINGS / CUTTINGS				
Packaging Can be packed in suitable packaging according to packing instruction P003. Note: Any sift-proof, tearproof receptacle may be used (PP20). The packaging shall be vented (PP10). Can also be packaged in large packagings (LP02).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223). A consignment of this substance which is accompanied by a declaration from the shipper stating that it has no self-heating properties is not subject to the provisions of the IMDG Code (SP 931).						
Properties and observations These cargoes are liable to self-heating and to ignite spontaneously, particularly when in a finely divided form, wet or contaminated with such materials as unsaturated cutting oil, oily rags and other combustible matter. Self-heating or inadequate ventilation may cause dangerous depletion of oxygen in the stowage spaces. Excessive amounts of cast iron borings or organic materials may encourage heating. The swarf should be protected from moisture prior to and after loading. If, during loading, the weather is inclement, hatches should be closed or otherwise protected to keep the material dry.						
Tank type: Not allowed		Transport in bulk			Orange panel	
Tank provisions: –		Not allowed			2793	
Stowage and segregation						
Stowage Keep as dry as reasonably practicable (H1).						
Segregation Check the segregation table for sea transport. In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26).						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance is not required to be kept separate from food and feed.						
Limited quantities (LQ) Combination packaging Inner: Not allowed Outer: Trays Inner: Not allowed Outer:			Excepted quantities (EQ) Combination packaging Inner: 30 mg el. mL Outer: 1000 mg el. mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.			
			Parcel label: 			