



IMDG - UN card

UN 2803

UN number 2803		Shipping name GALLIUM GALLIUM				
Class 8	Packing group III	Hazard labels 8	Marine pollutant Maybe	EmS F-A, S-B	<i>ADR transport category: 3 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 2803 GALLIUM				
Packaging		Can be packed in approved packaging according to packing instruction P800. Note: Packagings shall meet the packing group II performance level (PP4).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		Silvery-white metallic element that melts at 29 °C, becoming a bright, shiny liquid. Insoluble in water. Highly corrosive to aluminium. Harmful if swallowed, by skin contact or by inhalation. Special care should be taken if a leakage occurs when carried in aluminium freight containers. Carriage should be prohibited in hovercraft and other ships constructed from aluminium.				
Tank type:	T1	Transport in bulk		Orange panel		
Tank provisions:	TP33	Not allowed		2803		
Stowage and segregation						
Stowage		Must be protected from sources of heat (SW1).				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ)		Parcel label:		Excepted quantities (EQ)		
Combination packaging				Combination packaging		
Inner: 5 kg				Inner: Not allowed		
Outer: 30 kg				Outer:		
Trays						
Inner: 5 kg						
Outer: 20 kg						