



IMDG - UN card

UN 3090

UN number 3090		Shipping name LITHIUM METAL BATTERIES LITHIUMMETALBATTERIER				
Class 9	Packing group —	Hazard labels 9A	Marine pollutant Maybe	EmS F-A, S-I	ADR transport category: 2 ADR tunnel: (E)	
Hazard labels 		Marking UN 3090 LITHIUM METAL BATTERIES				
Packaging		Can be packed in approved packaging according to packing instruction P903. Can also be packaged in large packagings (LP903).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		Lithium cells and batteries may be transported under this entry if they meet the provisions of 2.9.4 (SP 230). The testing requirements in the Manual of Tests and Criteria, part III, subsection 38.3 do not apply to production runs, consisting of not more than 100 cells or batteries, or to pre-production prototypes of cells or batteries when these prototypes are transported for testing when packaged in accordance with packing instruction P910 of 4.1.4.1 or LP905 of 4.1.4.3, as applicable. The transport document shall include the following statement: "Transport in accordance with special provision 310". Damaged or defective cells, batteries, or cells and batteries contained in equipment shall be transported in accordance with special provision 376. Cells, batteries or cells and batteries contained in equipment transported for disposal or recycling may be packaged in accordance with special provision 377 and packing instruction P909 of 4.1.4.1 (SP 310). Lithium ion cells or batteries and lithium metal cells or batteries identified as being damaged or defective such that they do not conform to the type tested according to the applicable provisions of the Manual of Tests and Criteria shall comply with the requirements of this special provision (SP 376).				
Properties and observations		Electrical batteries containing lithium encased in a rigid metallic body. Lithium batteries may also be shipped in, or packed with, equipment. Electrical lithium batteries may cause fire due to an explosive rupture of the body caused by improper construction or reaction with contaminants.				
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	—	Not allowed		3090		
Stowage and segregation						
Stowage	For batteries transported in accordance with special provisions 376 or 377, category C, unless transported on a short international voyage (SW19).					
Segregation	Check the segregation table for sea transport. There are no special requirements for segregation.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance is not required to be kept separate from food and feed.					
Special for lithium batteries	Note: Lithium metal batteries are in certain cases exempt from following the provisions of the IMDG Code, if certain conditions are met: Batteries must have a maximum lithium quantity of 2 g and cells a maximum of 1 g. The batteries must meet the requirements of the Manual of Tests and Criteria, Part III, Subsection 38.3, and be produced under a quality management program. Each battery must be protected against short-circuiting (e.g. tape over terminals or enclosed in blister pack), and placed in inner packaging so that they are completely enclosed. The inner packaging must be placed in a strong outer packaging that can withstand a drop test of 1.2 m in any direction and without damaging the cells or batteries in the package, without displacing the contents. The maximum weight of a parcel must be 30 kg. Each package must be marked with the lithium battery label (with the text "UN 3090"). Lithium ion and lithium metal cells and batteries, as well as equipment containing such cells and batteries, which are transported for disposal or recycling, and which may be packed with batteries without lithium, can be packed according to P909 (SP377). Lithium batteries according to 2.2.9.1.7 (f) containing both primary lithium metal cells and rechargeable lithium ion cells must be assigned to either UN 3090 or 3091. When such batteries are transported according to SP 188, the total amount of lithium in all lithium metal cells in the battery must not exceed 1.5 g and the total capacity of all lithium ion cells in the battery not exceed 10 Wh (SP387).					
Limited quantities (LQ)			Excepted quantities (EQ)			
Combination packaging			Combination packaging			
Inner: Not allowed			Inner: Not allowed			
Outer:			Outer:			
Trays						
Inner: Not allowed						
Outer:						