



IMDG - UN card

UN 3102

UN number 3102	Shipping name ORGANIC PEROXIDE TYPE B, SOLID ORGANISK PEROXID, TYPE B, FAST					
Class 5.2	Packing group —	Hazard labels 5.2 (See SP181)	Marine pollutant No	EmS F-J, S-R	ADR transport category: 1 ADR tunnel: (B)	
Hazard labels  		Marking UN 3102 ORGANIC PEROXIDE TYPE B, SOLID (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging	Can be packed in approved packaging according to packing instruction P520.					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	The subsidiary hazard(s), the control and emergency temperatures, if any, and the generic entry number for each of the currently assigned organic peroxide formulations are given in 2.5.3.2.4, 4.1.4.2 packing instruction IBC520 and 4.2.5.2.6 portable tank instruction T23 (SP 122). Packages containing this type of substance shall bear the "EXPLOSIVE" subsidiary hazard label (Model No. 1, see 5.2.2.2.2) unless the competent authority of the country of origin has permitted this label to be dispensed with for the specific packaging employed because test data have proved that the substance in this packaging does not exhibit explosive behaviour (see 5.4.1.5.5.1). The provisions of 7.2.3.3 shall also be considered (SP 181). For certain organic peroxides types B or C, a smaller packaging than that allowed by packing methods OP5 or OP6 respectively has to be used (see 4.1.7 and 2.5.3.2.4) (SP 195).					
Properties and observations	May explode at elevated temperatures or in a fire. Burns vigorously. Insoluble in water. Contact with the eyes and skin should be avoided. Addition of water to disuccinic acid peroxide will decrease its thermal stability. May evolve irritant or toxic fumes.					
Tank type:	Not allowed	Transport in bulk			Orange panel	
Tank provisions:	—	Not allowed			3102	
Stowage and segregation						
Stowage	Must be protected from sources of heat (SW1).					
Segregation	Check the segregation table for sea transport. For packages carrying a subsidiary hazard label of class 1, segregation as for class 1, division 1.3. However, in relation to goods of class 1, segregation as for the primary hazard (SG1). Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG18 – alkalis (SG36). See tables in 7.2.6.3 (SG72). "Seperated from": May not be loaded into the same transport unit.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance must be kept separate from food and feedstuffs.					
Limited quantities (LQ) <i>Combination packaging</i> Inner: 100 g Outer: 30 kg <i>Trays</i> Inner: 100 g Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:		