



IMDG - UN card

UN 3111

UN number 3111		Shipping name ORGANIC PEROXIDE TYPE B, LIQUID, TEMPERATURE CONTROLLED ORGANISK PEROXID TYPE B, FLYDENDE, MED TEMPERATURKONTROL				
Class 5.2	Packing group —	Hazard labels 5.2 (See SP181)	Marine pollutant No	EmS F-F, S-R	ADR transport category: 1 ADR tunnel: (B)	
Hazard labels 		Marking UN 3111 ORGANIC PEROXIDE TYPE B, LIQUID, TEMPERATURE CONTROLLED (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging	Can be packed in approved packaging according to packing instruction P520.					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	The subsidiary hazard(s), the control and emergency temperatures, if any, and the generic entry number for each of the currently assigned organic peroxide formulations are given in 2.5.3.2.4, 4.1.4.2 packing instruction IBC520 and 4.2.5.2.6 portable tank instruction T23 (SP 122). Packages containing this type of substance shall bear the "EXPLOSIVE" subsidiary hazard label (Model No. 1, see 5.2.2.2.2) unless the competent authority of the country of origin has permitted this label to be dispensed with for the specific packaging employed because test data have proved that the substance in this packaging does not exhibit explosive behaviour (see 5.4.1.5.5.1). The provisions of 7.2.3.3 shall also be considered (SP 181). For certain organic peroxides types B or C, a smaller packaging than that allowed by packing methods OP5 or OP6 respectively has to be used (see 4.1.7 and 2.5.3.2.4) (SP 195). The temperature shall be checked regularly (SP 923).					
Properties and observations	May explode at temperatures higher than the emergency temperature or in a fire. Burns vigorously. Immiscible with water. Contact with the eyes and skin should be avoided. Control and emergency temperatures for each formulation are given in table 2.5.3.2.4. The temperature should be checked regularly. May evolve irritant or toxic fumes.					
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	—	Not allowed		3111		
Stowage and segregation						
Stowage	Must be protected from sources of heat (SW1). Shall be transported under temperature control (SW3).					
Segregation	Check the segregation table for sea transport. For packages carrying a subsidiary hazard label of class 1, segregation as for class 1, division 1.3. However, in relation to goods of class 1, segregation as for the primary hazard (SG1). Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG18 – alkalis (SG36). See tables in 7.2.6.3 (SG72). "Separated from": May not be loaded into the same transport unit.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance must be kept separate from food and feedstuffs.					
Limited quantities (LQ)			Excepted quantities (EQ)			
Combination packaging			Combination packaging			
Inner: Not allowed			Inner: Not allowed			
Outer:			Outer:			
Trays						
Inner: Not allowed						
Outer:						