



IMDG - UN card

UN 3115

UN number 3115		Shipping name ORGANIC PEROXIDE TYPE D, LIQUID, TEMPERATURE CONTROLLED ORGANISK PEROXID TYPE D, FLYDENDE, MED TEMPERATURKONTROL				
Class 5.2	Packing group —	Hazard labels 5.2	Marine pollutant Maybe	EmS F-F, S-R	ADR transport category: 1 ADR tunnel: (D)	
Hazard labels 		Marking UN 3115 ORGANIC PEROXIDE TYPE D, LIQUID, TEMPERATURE CONTROLLED (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging	Can be packed in approved packaging according to packing instruction P520.					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	The subsidiary hazard(s), the control and emergency temperatures, if any, and the generic entry number for each of the currently assigned organic peroxide formulations are given in 2.5.3.2.4, 4.1.4.2 packing instruction IBC520 and 4.2.5.2.6 portable tank instruction T23 (SP 122). The temperature shall be checked regularly (SP 923).					
Properties and observations	Decomposes at temperatures higher than the emergency temperature or in a fire. Burns vigorously. Immiscible with water. Contact with the eyes and skin should be avoided. Control and emergency temperatures for each formulation are given in table 2.5.3.2.4. The temperature should be checked regularly. May evolve irritant or toxic fumes.					
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	—	Not allowed		3115		
Stowage and segregation						
Stowage	Must be protected from sources of heat (SW1). Shall be transported under temperature control (SW3).					
Segregation	Check the segregation table for sea transport. Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG18 – alkalis (SG36). See tables in 7.2.6.3 (SG72). "Seperated from": May not be loaded into the same transport unit.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance is not required to be kept separate from food and feed.					
Limited quantities (LQ)			Excepted quantities (EQ)			
Combination packaging			Combination packaging			
Inner: Not allowed			Inner: Not allowed			
Outer:			Outer:			
Trays						
Inner: Not allowed						
Outer:						