



IMDG - UN card

UN 3171

UN number 3171	Shipping name BATTERY-POWERED VEHICLE / BATTERY-POWERED EQUIPMENT BATTERIDREVET KØRETØJ / BATTERIDREVET UDSKY				
Class 9	Packing group —	Hazard labels 9	Marine pollutant Maybe	EmS F-A, S-I	ADR transport category: - ADR tunnel: (-)
Hazard labels 		Marking UN 3171 BATTERY-POWERED VEHICLE / BATTERY-POWERED EQUIPMENT			
Packaging	Cannot be packed in packaging.				
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks	See special provision 388 in the IMDG Code. Vehicles are not subject to the provisions of the IMDG Code if any of the following conditions are met: 1. vehicles are stowed on the vehicle, special category and ro-ro spaces or on the weather deck of a ro-ro ship or a cargo space designated by the Administration (flag State) in accordance with SOLAS 74, chapter II-2, regulation 20 as specifically designed and approved for the carriage of vehicles, and there are no signs of leakage from the battery, engine, fuel cell, compressed gas cylinder or accumulator, or fuel tank when applicable. When packed in a cargo transport unit the exception does not apply to container cargo spaces of a ro-ro ship. In addition, for vehicles powered solely by lithium batteries and hybrid electric vehicles powered by both an internal combustion engine and lithium metal or ion batteries, the lithium batteries shall meet the provisions of 2.9.4, except that 2.9.4.1 and 2.9.4.7 do not apply when pre-production prototype batteries or batteries of a small production run, consisting of not more than 100 batteries, are installed in the vehicle and the vehicle is manufactured and approved according to the provisions applied in the country of manufacture or country of use. Where a lithium battery installed in a vehicle is damaged or defective, the battery shall be removed. 2. vehicles powered by a flammable liquid fuel with a flashpoint of 38°C or above, there are no 3 leaks in any portion of the fuel system, the fuel tank(s) contains 450 L of fuel or less and installed batteries are protected from short-circuit; 3. vehicles powered by a flammable liquid fuel with a flashpoint less than 38°C, the fuel tank(s) are empty and installed batteries are protected from short circuit. Vehicles are considered to be empty of flammable liquid fuel when the fuel tank has been drained and the vehicles cannot be operated due to a lack of fuel. Engine components such as fuel lines, fuel filters and injectors do not need to be cleaned, drained or purged to be considered empty. The fuel tank does not need to be cleaned or purged; 4. vehicles powered by a flammable gas (liquefied or compressed), the fuel tank(s) are empty and the positive pressure in the tank does not exceed 2 bar, the fuel shut-off or isolation valve is closed and secured, and installed batteries are protected from short circuit; 5. vehicles solely powered by a wet or dry electric storage battery or a sodium battery, and the				
Tank type:	Not allowed	Transport in bulk		Orange panel	
Tank provisions:	—	Not allowed		3171	
Stowage and segregation					
Stowage	There are no special requirements for stowage.				
Segregation	Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff	The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) Combination packaging Inner: — Outer: 30 kg Trays Inner: — Outer: 20 kg		Excepted quantities (EQ) Combination packaging Inner: FALSE Outer: Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.			
Parcel label: 		Parcel label: 			