



IMDG - UN card

UN 3231

UN number 3231		Shipping name SELF-REACTIVE LIQUID TYPE B, TEMPERATURE CONTROLLED SELVNEDBRYDENDE VÆSKE, TYPE B, MED TEMPERATURKONTROL				
Class 4.1	Packing group —	Hazard labels 4.1 (See SP181)	Marine pollutant No	EmS F-F, S-K	<i>ADR transport category: 1 ADR tunnel: (B)</i>	
Hazard labels  		Marking UN 3231 SELF-REACTIVE LIQUID TYPE B, TEMPERATURE CONTROLLED (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging	Can be packed in approved packaging according to packing instruction P520. Note: For certain self-reactive substances of types B or C, UN 3221, 3222, 3223, 3224, 3231, 3232, 3233 and 3234, a smaller packaging than that allowed by packing methods OP5 or OP6 respectively shall be used (see 4.1.7 and 2.2.41.4 in ADR) (PP21).					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	Packages containing this type of substance shall bear the "EXPLOSIVE" subsidiary hazard label (Model No. 1, see 5.2.2.2) unless the competent authority of the country of origin has permitted this label to be dispensed with for the specific packaging employed because test data have proved that the substance in this packaging does not exhibit explosive behaviour (see 5.4.1.5.5.1). The provisions of 7.2.3.3 shall also be considered (SP 181). The control and emergency temperatures, if any, and the generic entry number for each of the currently assigned self-reactive substances are given in 2.4.2.3.2.3 (SP 194). The temperature shall be checked regularly (SP 923).					
Properties and observations	May explode at temperatures higher than the emergency temperature or in a fire. Burns vigorously. Immiscible with water. Contact with alkalis or acids may cause dangerous decomposition. The products of combustion or self-accelerating decomposition may be toxic by inhalation. Control and emergency temperatures for each formulation can be found in 2.4.2.3.2.3. The temperature should be checked regularly.					
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	—	Not allowed		3231		
Stowage and segregation						
Stowage	Must be protected from sources of heat (SW1). Shall be transported under temperature control (SW3).					
Segregation	Check the segregation table for sea transport. For packages carrying a subsidiary hazard label of class 1, segregation as for class 1, division 1.3. However, in relation to goods of class 1, segregation as for the primary hazard (SG1). Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG18 – alkalis (SG36). "Seperated from": May not be loaded into the same transport unit.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance must be kept separate from food and feedstuffs.					
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:			