



IMDG - UN card

UN 3270

UN number 3270		Shipping name NITROCELLULOSE MEMBRANE FILTERS MEMBRANFILTRE AF NITROCELLULOSE				
Class 4.1	Packing group II	Hazard labels 4.1	Marine pollutant Maybe	EmS F-A, S-I	ADR transport category: 2 ADR tunnel: (E)	
Hazard labels 		Marking UN 3270 NITROCELLULOSE MEMBRANE FILTERS				
Packaging		Can be packed in approved packaging according to packing instruction P411.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		The membrane filters, including paper separators, coating or backing materials, etc., that are present in transport, shall not be liable to propagate a detonation as tested by one of the tests described in the Manual of Tests and Criteria, part I, test series 1(a). In addition, the competent authority may determine, on the basis of the results of suitable burning rate tests taking account of the standard tests in the Manual of Tests and Criteria, part III, 33.2.1, that nitrocellulose membrane filters in the form in which they are to be transported are not subject to the provisions of the IMDG Code applicable to flammable solids in class 4.1. 1. Batteries can be considered as non-spillable provided that they are capable of withstanding the vibration and pressure differential tests given below, without leakage of battery fluid: Vibration, test: The battery is rigidly clamped to the platform of a vibration machine and a simple harmonic motion having an amplitude of 0.8 mm (1.6 mm maximum total excursion) is applied. The frequency is varied at the rate of 1 Hz/min between the limits of 10 Hz and 55 Hz. The entire range of frequencies and return is traversed in 95 ± 5 minutes for each mounting position (direction of vibration) of the battery. The battery is tested in three mutually perpendicular positions (to include testing with fill openings and vents, if any, in an inverted position) for equal time periods. Pressure, differential, test: Following the vibration test, the battery is stored for six hours at 24°C ± 4°C while subjected to a pressure differential of at least 88 kPa. The battery is tested in three mutually perpendicular positions (to include testing with fill openings and vents, if any, in an inverted position) for at least six hours in each position. Non-spillable type batteries which are an integral part of and necessary for the operation of mechanical or electronic equipment shall be securely fastened in the battery holder on the equipment and protected in such a manner as to prevent damage and short circuits. 2. Non-spillable batteries are not subject to the provisions of the IMDG Code if, at a temperature of 55°C, the electrolyte will not flow from a ruptured or cracked case and there is no free liquid to flow and if, when packaged for transport, the terminals are protected from short circuit (SP 237). Nitrocellulose membrane filters covered by this entry, each with a mass not exceeding 0.5 g, are not subject to the provisions of the IMDG Code				
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	–	Not allowed		3270		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ)		Parcel label:		Excepted quantities (EQ)		
Combination packaging				Combination packaging		
Inner: 1 kg Outer: 30 kg				Inner: 30 mg Outer: 500 mg		
Trays				Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
Inner: 1 kg Outer: 20 kg						