



IMDG - UN card

UN 3397

UN number 3397		Shipping name ORGANOMETALLIC SUBSTANCE, SOLID, WATER-REACTIVE, SELF-HEATING ORGANOMETALLISK STOF, FAST, DER REAGERER MED VAND, SELVOPVARMENDE				
Class 4.3	Packing group III	Hazard labels 4.3+4.2	Marine pollutant Maybe	EmS F-G, S-N	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels 		Marking UN 3397 ORGANOMETALLIC SUBSTANCE, SOLID, WATER-REACTIVE, SELF-HEATING (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging		Can be packed in approved packaging according to packing instruction P410. Note: Packagings shall be hermetically sealed (PP31).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223).				
Properties and observations		Liable to self-heating or spontaneous combustion. Reacts violently with moisture, water and acids, evolving flammable gas.				
Tank type: T1		Transport in bulk		Orange panel		
Tank provisions: TP33 TP36 TP41		Not allowed		3397		
Stowage and segregation						
Stowage		Stay clear of living quarters (SW2). Keep as dry as reasonably practicable (H1).				
Segregation		Check the segregation table for sea transport. In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "separated from" SGG1 – acids (SG35). See tables in 7.2.6.3 (SG72). "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) Combination packaging Inner: 1 kg Outer: 30 kg Trays Inner: 1 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) Combination packaging Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. Parcel label: 		