



IMDG - UN card

UN 3406

UN number 3406		Shipping name BARIUM PERCHLORATE SOLUTION BARIUMPERCHLORATOPLSNING				
Class 5.1	Packing group III	Hazard labels 5.1+6.1	Marine pollutant Maybe	EmS F-H, S-Q	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels  		Marking UN 3406 BARIUM PERCHLORATE SOLUTION				
Packaging		Can be packed in approved packaging according to packing instruction P001.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223).				
Properties and observations		Reacts vigorously with sulphuric acid. Reacts fiercely with cyanides when heated. May form explosive mixtures with combustible material, powdered metals or ammonium compounds. These mixtures are liable to ignite. When involved in a fire, may cause an explosion. Toxic if swallowed, by skin contact or by inhalation. Leakage and subsequent evaporation of the water from the solutions may present increased dangers as follows: .1 in contact with combustible material (particularly fibrous material such as jute, cotton or sisal) or sulphur, danger of spontaneous combustion, .2 in contact with ammonium compounds, powdered metals or oils, danger of explosion.				
Tank type:	T4	Transport in bulk		Orange panel		
Tank provisions:	TP1	Not allowed		3406		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. The substance belongs to group: perchlorates (SGG13). Stow "separated from" SGG2 – ammonium compounds (SG38). Stow "separated from" SGG6 – cyanides (SG49). Stow "separated from" sulphur (SG62). "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 L Outer: 30 kg <i>Trays</i> Inner: 5 L Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mL Outer: 1000 mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		