



IMDG - UN card

UN 3505

UN number 3505	Shipping name CHEMICAL UNDER PRESSURE, FLAMMABLE, CORROSIVE, N.O.S. KEMIKALIE UNDER TRYK, BRANDFARLIGT, ÆTSENDE, N.O.S.					
	Class 2.1	Packing group —	Hazard labels 2.1+8	Marine pollutant Maybe	EmS F-D, S-U	ADR transport category: 1 ADR tunnel: (B/D)
Hazard labels 		Marking UN 3505 CHEMICAL UNDER PRESSURE, FLAMMABLE, CORROSIVE, N.O.S. (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging Can be packed in suitable packaging according to packing instruction P206. Note: Notwithstanding 4.1.6.9 (b), non-refillable cylinders used may have a water capacity in litres not exceeding 1 000 litres divided by the test pressure expressed in bars provided capacity and pressure restrictions of the construction standard comply with ISO 11118:1999, which limits the maximum capacity to 50 litres (PP89).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks This entry applies to liquids, pastes or powders, pressurized with a propellant which meets the definition of a gas in 2.2.1.1 and 2.2.1.2.1 or 2.2.1.2.2. Note: A chemical under pressure in an aerosol dispenser shall be transported under UN 1950. The following provisions shall apply: 1. the chemical under pressure shall be classified based on the hazard characteristics of the components in the different states: the propellant; the liquid; or the solid. If one of these components, which can be a pure substance or a mixture, needs to be classified as flammable, the chemical under pressure shall be classified as flammable in class 2.1. Flammable components are flammable liquids and liquid mixtures, flammable solids and solid mixtures or flammable gases and gas mixtures meeting the following criteria: 1a. flammable liquid is a liquid having a flashpoint of not more than 93°C; 2a. flammable solid is a solid which meets the criteria in 2.4.2.2 of the IMDG Code; 3a. flammable gas is a gas which meets the criteria in 2.2.2.1 of the IMDG Code; 2. gases of class 2.3 and gases with a subsidiary hazard of 5.1 shall not be used as a propellant in a chemical under pressure; 3. where the liquid or solid components are classified as dangerous goods of class 6.1, packing groups II or III, or class 8, packing groups II or III, the chemical under pressure shall be assigned a subsidiary hazard of class 6.1 or class 8 and the appropriate UN number shall be assigned. Components classified in class 6.1, packing group I, or class 8, packing group I, shall not be used for transport under this proper shipping name; 4. in addition, chemicals under pressure with components meeting the properties of: class 1, explosives; class 3, liquid desensitized explosives; class 4.1, self-reactive substances and solid desensitized explosives; class 4.2, substances liable to spontaneous combustion; class 4.3, substances which, in contact with water, emit flammable gases; class 5.1, oxidizing substances; class 5.2, organic peroxides; class 6.2, infectious substances or class 7, radioactive material, shall not be used for transport under this						
Tank type: T50		Transport in bulk			Orange panel	
Tank provisions: TP4 TP40		Not allowed			3505	
Stowage and segregation						
Stowage		Stay clear of living quarters (SW2).				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation. Note that for this substance, the consignor must assign the substance to a segregation group based on the substance's physical and chemical properties, if applicable.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:				Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:		