



IMDG - UN card

UN 3533

UN number 3533		Shipping name POLYMERIZING SUBSTANCE, SOLID, TEMPERATURE CONTROLLED, N.O.S. POLYMERISERENDE STOF, FAST, MED TEMPERATURKONTROL, N.O.S.				
Class 4.1	Packing group III	Hazard labels 4.1	Marine pollutant Maybe	EmS F-F, S-K	<i>ADR transport category: 1 ADR tunnel: (D)</i>	
Hazard labels 		Marking UN 3533 POLYMERIZING SUBSTANCE, SOLID, TEMPERATURE CONTROLLED, N.O.S. (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging Can be packed in approved packaging according to packing instruction P002. Note: Packagings shall be designed and constructed to permit the release of gas or vapour to prevent a build-up of pressure that could rupture the packagings in the event of loss of stabilization (PP92).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks When substances are stabilized by temperature control, the provisions of 7.3.7 apply. When chemical stabilization is employed, the person offering the packaging, IBC or tank for transport shall ensure that the level of stabilization is sufficient to prevent the substance in the packaging, IBC or tank from dangerous polymerization at a bulk mean temperature of 50°C, or, in the case of a portable tank, 45°C. Where chemical stabilization becomes ineffective at lower temperatures within the anticipated duration of transport, temperature control is required. In making this determination factors to be taken into consideration include, but are not limited to, the capacity and geometry of the packaging, IBC or tank and the effect of any insulation present, the temperature of the substance when offered for transport, the duration of the journey and the ambient temperature conditions typically encountered in the journey (considering also the season of year), the effectiveness and other properties of the stabilizer employed, applicable operational controls imposed by regulation (e.g. requirements to protect from sources of heat, including other cargo transported at a temperature above ambient) and any other relevant factors." (SP 386).						
Properties and observations Polymerizes at temperatures higher than the self-accelerating polymerization temperature or in a fire. Burns vigorously. Insoluble in water. Contact with alkalis or acids may cause dangerous polymerization. The products of combustion or self-accelerating polymerization may be toxic by inhalation. Control and emergency temperatures can be found in the transport document as required in 5.4.1.5.5. The temperature must be checked regularly.						
Tank type: T7		Transport in bulk		Orange panel		
Tank provisions: TP4 TP6 TP33		Not allowed		3533		
Stowage and segregation						
Stowage		Must be protected from sources of heat (SW1). Shall be transported under temperature control (SW3).				
Segregation		Check the segregation table for sea transport. Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG18 – alkalis (SG36). Note that for this substance, the consignor must assign the substance to a segregation group based on the substance's physical and chemical properties, if applicable. "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:			