

A novel metaheuristic approach to obtain near optimal solutions in high dimensional biochemical networks with a few function evaluations

Adithya Sagar, Christine Shoemaker and Jeffrey D. Varner*

School of Chemical and Biomolecular Engineering

Cornell University, Ithaca NY 14853

Running Title: Parameter estimation in large scale biological systems

To be submitted: *Biotechnology Journal*

*Corresponding author:

Jeffrey D. Varner,

Associate Professor, School of Chemical and Biomolecular Engineering,

244 Olin Hall, Cornell University, Ithaca NY, 14853

Email: jdv27@cornell.edu

Phone: (607) 255 - 4258

Fax: (607) 255 - 9166

Abstract

The problem of parameter estimation presents a significant challenge in the modeling of large complex systems. Mathematical modeling of biological systems with multiple feedback loops is one such area where parameter estimation is a difficult non-linear optimization problem. This difficulty is further compounded when dealing with parameter vectors of high dimensions. Such problems generally involve expensive function evaluations and it is hard to obtain optimal solutions within finite computational time. In this study we present a novel meta-heuristic approach that combines a variant of particle swarm optimization (PSO) along with dynamically dimensioned search (DDS) to obtain near optimal solutions of high dimensional biochemical networks within a relatively few function evaluations. We use a particle swarm optimization technique that uses multi-swarms to generate candidate vectors which are then greedily updated using DDS by dynamically varying the perturbed parameter dimensions. We tested this algorithm (25 trials with 4000 function evaluations in each trial) on a biochemical network of coagulation (148 parameters and 92 species) and compared its performance against other metaheuristics like Differential Evolution (DE), Particle Swarm Optimization (PSO), Simulated Annealing (SA) and also against DDS alone. The new algorithm outperforms all the other metaheuristics on the coagulation model. The parameter vectors obtained using this approach fit the experimental data well and also make accurate enough predictions on unseen experimental data. We also performed this comparison on commonly used test functions (Ackley and Rosenbrock) for global optimization and found the same behavior. Further we used two recently published benchmark problems, a genome wide kinetic model with 1759 parameters and a metabolic model of Chinese Hamster Ovary cells with 117 parameters to evaluate the performance of our approach. We surprisingly performed well on these benchmarks and obtained the nominal parameter vector with just 4000 function evaluations in both cases.

Keywords: Parameter identification, Mathematical modeling

1 Introduction

2 Biological systems interact with one another and with the external world through highly
3 complex biochemical networks. The advent of high throughput technologies has provided
4 researchers with a deluge of data about these networks. Over the last decade, with an
5 increase in computational power, large scale mathematical modeling has evolved as a
6 powerful paradigm to characterize these complex biochemical interactions (2, 3, 4, 5, 6,
7). Mathematical modeling of these networks is an iterative process that primarily consists
8 of two tasks a) Model construction b) Model calibration or Parameter Estimation (7,)(8,)
9 (9,). Model construction involves translating existing knowledge about the network (i.e.
10 entities in the network, interactions amongst the entities, types of interactions) along with
11 reasonable assumptions into an appropriate mathematical framework. Model calibration
12 or parameter estimation follows the model construction step. In this step the model is
13 trained against experimental data to determine the model parameters that give a good 'fit'
14 against experimental data. Model training is generally framed as a non-linear optimiza-
15 tion problem wherein the residual (or objective function) between experimental data and
16 simulation data is minimized using various optimization techniques (10,). The optimal pa-
17 rameters obtained from the previous step are then used to validate the model on hitherto
18 unseen experimental data. If validation leads to unsatisfactory results, model construction
19 and calibration are repeated iteratively till satisfactory results are obtained.

20 With the capacity to construct very large models using various mathematical for-
21 malisms (11,) (12,)(13,) (14,) (15,) (16,)(17,) (18,), more often than not, parameter
22 estimation is becoming a major challenge if not a bottleneck in large scale mathematical
23 modeling. Though parameter estimation has been a well studied problem in engineering
24 (19,)(20,)(21,) (22,), the complex dynamics of large biological systems and noisy, often
25 incomplete experimental data pose a more difficult and rather unique challenge. Most of
26 the optimization problems pertaining to biological systems are non-linear and multi-modal

i.e. most of them have multiple local minima or maxima (10,)(8,). The non-linearity of the problem coupled with multi-modality generally renders the local optimization techniques like pattern search method (23,), Nelder-Mead simplex method (24,) or Levenberg-Marquardt method(25,) incapable of obtaining an optimal solution. Though deterministic global optimization techniques can handle non-linearity and multi-modality (26,) (27,), the absence of derivative information, discontinuity of the objective functions, non-smooth regions or the lack of any knowledge about the objective function severely hamper the use of these techniques.

Metaheuristic approaches like Genetic Algorithms, Simulated Annealing (28,), Evolutionary Programming and population based searches like Differential Evolution(29,) have shown promise in this regard (30,). They do not make any assumptions about the structure of objective function or require any *a priori* information about the objective function. Though they do not guarantee strong convergence, these approaches are effective in finding near optimal solutions. Mendes et al. (31,) used Simulated Annealing to estimate rate constants for the irreversible inhibition of HIV proteinase, Modchang et al. (32,) used Genetic Algorithms to estimate parameters for a mathematical model of signal transduction, Differential Evolution based approaches have been an effective approach on various systems (33,), (34,),(35,). Tashkova et al. (36,) compared different metaheuristics for parameter estimation on a dynamic model of endocytosis and showed that DE was the most effective. Banga and co-workers have applied scatter-search based methods (37,) (38,) (39,) to estimate parameters on non-linear biological processes. Hybrid approaches that combine a metaheuristic with a local optimization search, wherein a near optimal solution that is obtained with a metaheuristic is further refined using a local search have also become popular. Villaverde et al. (40,) combined scatter search with local search methods for parameter estimation in large scale systems biology models. Fan et al. recently showed that population based metaheuristics along with decomposition

based methods can be used to model gene circuits from mRNA data (41,).

Despite these successes, a major drawback with most of these approaches is the vast number of objective function evaluations they take in arriving at good search regions. As the models grow in size and complexity and the number of dimensions of parameter vector increases, parameter estimation becomes a computationally expensive task. In many of these high dimensional problems approaching an exact solution may not be necessary. Gutenkunst et al. (42,) showed that a number of systems biology models are 'sloppy'. Sloppy systems have specific parameter combinations that largely define the dynamics of the system. Large perturbations to the rest of the parameters does not greatly impact the system dynamics. Ensemble approaches (43, 44,) have exploited this aspect to describe the dynamics of biological systems including coagulation which can be described using only a set of key species or parameters (45,). Tolson and Shoemaker (46,) showed through Dynamically Dimensioned Search (DDS) that high-dimensional watershed models can be calibrated quickly by perturbing only a subset of dimensions. Thus in our current study we took into cognizance the fact that it may not be necessary to obtain the exact solution for high dimensional biological systems and that good enough solutions can be quickly obtained without expending a lot of objective function evaluations. Hence our current approach uses the power of population based heuristics along with DDS to obtain near optimal or good solutions. Though in theory we can combine any metaheuristic with DDS, for the current purpose we used Particle Swarm Optimization (PSO). PSO unlike Genetic Algorithm (GA) or Differential Evolution (DE) does not have complex operations like cross over, mutation or recombination. It is simple to use and does not have a lot of parameters associated with other heuristics. However PSO is known to rapidly converge to a local optimum and thus several variants (47, 48, 49,) have been developed of which Multi swarm particle swarm optimization approaches (MLSPSO) (50, 51,) are one of the effective ones. We used MLSPSO to preclude bad regions of search and thereafter

79 search within these regions using DDS.

Results

Performance on Coagulation model Coagulation is an archetype biochemical network that is highly interconnected and tightly regulated with multiple positive and negative feedback loops (Figure 1). The biochemistry underlying coagulation, though quite complex has been well studied (52, 53, 54, 55, 56, 57, 58,), and reliable experimental coagulation models have been developed (13, 59, 60, 61,). This makes it an ideal system for mathematical modeling and parameter estimation. Coagulation is regulated by a set of serine proteases also known as coagulation factors and blood platelets. The coagulation factors are generally in an inactive state and are known as zymogens. These zymogens are activated through certain triggers. Trigger events like injury or trauma or sepsis expose factors like collagen, tissue factor and von Willebrand factor (vWF) to blood. The exposure of these factors to blood kick-starts a series of convergent cascades that lead to conversion of zymogen prothrombinase to thrombin. Luan et al. modeled coagulation using coupled non-linear ordinary differential equations with 148 reactions and 92 species (13,) and validated model using 21 published datasets.

We compared the performance of Dynamically Dimensioned Search with Multi Swarm Particle Swarm Optimization (DDSMMLSPSO) on this model of coagulation against commonly used meta heuristics like Simulated Annealing (SA), Differential Evolution (DE), Particle Swarm Optimization (PSO) and also against Dynamically Dimensioned Search (DDS). To train the model parameters, we used data sets from TF-VIIa initiated coagulation with no anticoagulants. The objective function is a weighted linear combination of two different error functions that used data sets representing coagulation initiated with different concentrations of TF-VIIa (5pM, 5nM) (59,). We restricted the number of function evaluations to 4000 for each algorithm and performed 25 trials of this experiment. DDSMLSPSO exhibits a much faster rate of error convergence and has a much lower final error as compared to the other algorithms (Figure 3). Within the first 1000 function

evaluations (swarm phase) of DDSMLSPSO there is a very rapid drop in error. Subsequently, again after 2000 function evaluations (dynamically dimensioned phase) the error drops quickly. Overall at the end of 4000 function evaluations DDSMLSPSO minimizes the error (final objective error is 90456.9) to a much greater extent than any of the other algorithms. Amongst the rest of the algorithms DDS has a comparable error drop for the first 2000 function evaluations. However the drop in error remains constant for DDS after 2000 function evaluations. Using the parameters obtained at the end of 4000 function evaluations we examined the 'fits' between models predictions and experimental data (Figure 2). The solid lines represent the mean value of prediction over 25 trials and the shaded region represents the 99% confidence interval. Subsequently we compared the model predictions against completely 'unseen' or untrained experimental where coagulation was initiated with 500pM, 50pM, 10pM concentrations of TF-VIIa respectively (Figure 3).

Performance on Benchmark functions We compared the performance of these algorithms on commonly used test functions for global optimization. We used a 300 dimensional Rastrigin function and 300 dimensional Ackley function. Both Ackley and Rastrigin have multiple local minima and maxima and attain a global minimum value of 0. We tested the performance of the 5 different heuristic approaches on these two functions. In each experiment we again fixed the number of function evaluations at 4000 and ran 25 experiments. In both cases (Figure S6 A and B) we see that the error convergence rate for DDSMLSPSO is much faster as compared to the other four metaheuristics and it finds the global minimum of 0 in both cases.

Villaverde and co-workers recently published a set of benchmark problems to evaluate parameter estimation methods (40,). From a computational cost perspective problems they categorized the problems as most expensive, intermediate and least expensive. We evaluated the performance of our algorithms on a problem from the most expensive and

least expensive categories. The first problem is a genome wide kinetic model of *Saccharomyces cerevisiae* with 1759 parameters (henceforth referred to as problem B1). The second problem (henceforth referred to as problem B4) is a metabolic model of Chinese Hamster Ovary (CHO) with 35 metabolites, 32 reactions and 117 parameters. In both cases pseudo time series data was generated. For problem B1, the time series data consisted of 44 observables and for problem B4 the data corresponded to 13 different metabolites. We fixed the number of function evaluations at 4000 for DDSMLSPSO and trained both the models against the pseudo experimental data. We recaptured the 'nominal' parameters (Figure S7 A and B) in both cases within 4000 evaluations. The final objective function value (Table 1) is an order smaller for B1 possibly due to overfitting. In Table 1 we summarize the results obtained on the coagulation model and the benchmark problems.

Table 1: Table with optimization settings and results for coagulation and different benchmarks using DDSMLSPSO.

	Coagulation	Benchmarks			
	Experimental Data Set	B1	B4	Ackley 300D	Rastrigin 300D
Lower Bound	0.001.pnom	5.pnom	5.pnom	30	5.12
Upper Bound	1000.pnom	0.2.pnom	0.2.pnom	-15	-5.12
CPU Time	10.0835 hours	38.308 hours	6.2 minutes	2.8 seconds	2.6 seconds
Function Evaluations	4000	4000	4000	4000	4000
Initial Objective Value	1.11837e+07	1.4275e+07	1.8536e+07	21.12	99.985
Final Objective Value	90456.9	4.96e+05	38.9375	0	0
Nominal Objective Value	4.7785e+06	1.0986e+06	39.0676	0	0

Discussion

Our study presents a novel approach for high-dimensional parameter estimation in complex biological systems with relatively few function evaluations. In this approach we combined a variant of a well known meta heuristic particle swarm optimization with Dynamically Dimensioned Search (DDS). We tested our approach on an ODE model of coagulation with 148 parameters and 92 species. Coagulation is an ideal system to test our approach since the biology is well known and complex, with multiple feed back loops that are tightly regulated. We used experimental data with under different conditions to obtain optimal parameters and used these parameters to make predictions against unseen experimental data. We obtained good fits and made accurate enough predictions using parameters obtained from 4000 function evaluations. Further, we also used high-dimensional forms of commonly used test functions of global optimization and showed that we were able to find the global minimum for 300 dimensional Ackley and Rastrigin functions faster than other metaheuristics. We also considered two recently published benchmark problems to test parameter optimization approaches and showed that we were able to retrieve the nominal parameter vector within 4000 function evaluations.

Metaheuristic approaches are generally effective in finding close to optimum solutions of complex, multi-modal functions. In addition, they generally obviate the need for any *a priori* knowledge (like function derivative). However they take an exorbitant number of objective function evaluations to come close to an optimum. When the objective function evaluations tend to become expensive it is infeasible to take up a large number of evaluations. As the dimensionality of parameter space increases, the search region gets widened and thus the problem becomes more challenging. In addition, most of these approaches require optimization of 'algorithm parameters' before the actual optimization and also involve computationally expensive update operations. Tolson and Shoemaker, through DDS, showed that randomly perturbing a subset of dimensions in high dimen-

sional parameter space is an effective way to obtain near optimal solutions with few function evaluations. However their approach was based on a single solution. Single solutions based methods may prove ineffective in complex systems when they start from a 'bad' region of search or from a local minimum. In our approach, we tried to eliminate the probability of starting from a bad region of search using a variant of particle swarm optimization. Particle Swarm Optimization (PSO) is a population based meta heuristic that is known for rapid convergence without any complex operations like recombination, mutation or selection that are associated with other population based metaheuristics like Differential Evolution (DE) or Genetic Algorithm (GA). Several particle swarm variants have been proposed to improve the search ability and rate of convergence, that involve different neighborhood structures, multi-swarms or adaptive parameters. Multi-swarm PSO with small particle neighborhoods have been shown to better in searching on complex multi-modal solutions (50,). Multi swarm methods, in addition, avoid rapid convergence to a local optimum or stable point and are able to generate diverse solutions. Generation of diverse solutions in the early stage gives a better exploratory capability and thus converge of upon multiple optima.

We utilized this capacity of multi swarms to generate diverse candidate solutions which can be used as initial solutions for a DDS like search. Thus the solution vectors obtained at the end of multi swarm search phase have a better propensity to not get stuck in bad regions in DDS phase as opposed to starting with a totally random initial solution. Given a fixed number of function evaluations, we have been able to show that we were able to obtain better solutions for the coagulation model and the test functions faster than other commonly known metaheuristics and also DDS alone. Choosing the number of function evaluations is largely a function of cost and complexity of the objective function. Traditionally the stopping condition for a parameter optimization problem can be the number of function evaluations, percentage of initial error achieved or an absolute error threshold.

196 However in case of complex, expensive functions where we desire a value within a certain
197 period of time, the number of evaluations are used as a stopping criterion. In our current
198 study we used a value of 4000 which we based upon the time taken (approximately 8-10
199 seconds) for a single objective function evaluation in the coagulation case. We used the
200 same value of 4000 for benchmarks published by Villaverde and co-workers (40,). Quite
201 surprisingly we took a couple of orders lesser number of function evaluations ($1e3$) to
202 obtain the optimal parameter vector as compared to the enhanced Scatter Search (eSS)
203 with a local optimizer, which took around the order of $1e5$ number of evaluations. The
204 amount of CPU time taken (on an Intel Xeon processor 2.4 GHz) is lesser as compared
205 to eSS on a similar architecture.

206 A surprisingly remarkable aspect about our algorithm has been that we did not 'pre
207 optimize' any parameters of the algorithm to suit a specific problem. In the swarm phase
208 this includes the number of particles, number of sub-swarms, acceleration constants or
209 the number of generations after which the particles are redistributed and the neighbor-
210 hood perturbation parameter in DDS phase. We used the same parameters for all the
211 problems. The same rule was applied to the rest of the metaheuristics barring Simulated
212 Annealing. For SA, we optimized the cooling schedule for the coagulation model. Thus,
213 in this approach any overhead that usually comes with additional function evaluations to
214 optimize parameters was avoided. The only parameter that we adjusted was the frac-
215 tion of evaluations within swarm search. For the coagulation model it was set to be 0.4
216 and for the benchmarks it is at 0.6. This parameter was set based on empirical obser-
217 vations rather than any definitive analysis. When the error convergence rates stagnated
218 in the swarm phase we switched to DDS phase. A further improvement to our approach
219 could be to incorporate a meta intelligent way of switching in and switching out of both the
220 phases.

221 The performance of our approach seems impressive given that it performed well on

different complex systems with no specific conditioning being required. We comfortably outperformed common metaheuristics and were also able to find minima of high dimensional global optimization test functions. Thus this approach may be well suited to large scale global optimization. In addition, surprisingly, we were able to obtain optimal parameter vectors for two different large scale systems biology models with a couple of orders fewer number of function evaluations as compared a hybrid approach. However it is quite possible that highly optimized versions of common meta heuristics may outperform us on these systems. This aspect is currently beyond the scope of this study. Our approach can also be combined with local derivative based searches to improve upon the accuracy of the solutions.

Materials and Methods

Optimization Strategy Dynamically dimensioned multi-swarm particle swarm optimization (DDSMSPSO) is a novel optimization approach that combines elements from multi-swarm based PSO methods with DDS (Figure 2). The goal of this approach is to obtain optimal or near optimal parameters for high-dimensional complex biological systems within a pre-specified number of function evaluations.

We randomly initialized a swarm of \mathcal{K} -dimensional particles (represented as x_i), wherein each of these particles corresponds to a \mathcal{K} -dimensional parameter vector. After initialization, the particles were grouped into different sub-swarms randomly. Thereafter within each sub-swarm S_k , particles were updated according to the following rule.

$$\mathbf{x}_{i,j} = \theta_{1,j-1} \mathbf{x}_{i,j-1} + \theta_2 \mathbf{r}_1 (\mathcal{L}_i - \mathbf{x}_{i,j-1}) + \theta_3 \mathbf{r}_2 (\mathcal{G}\mathcal{L}_k - \mathbf{x}_{i,j-1}) \quad (1)$$

where $(\theta_1, \theta_2, \theta_3)$ are adjustable parameters, \mathcal{L}_i denotes the best local solution found by particle i till function evaluation $j-1$, and $\mathcal{G}\mathcal{L}_k$ denotes the best local solution found over the population of all particles within the swarm S_k . The quantities r_1 and r_2 denote uniform random vectors with the same dimension as the number of unknown model parameters ($\mathcal{K} \times 1$). In our algorithm the parameter $\theta_{1,j-1}$ depends on the function evaluations and is controlled according to the following equation

$$\theta_{1,j} = ((\mathbf{N} - j) * (\mathbf{w}_{max} - \mathbf{w}_{min})) / (\mathbf{N} - 1) + \mathbf{w}_{min} \quad (2)$$

where \mathbf{N} represents the total number of function evaluations, \mathbf{w}_{max} and \mathbf{w}_{min} are the maximum and minimum inertia weights respectively. While updating the particle, we made sure all dimensions of the solution represented by the particle were within bounds using

251 a reflection boundary condition. After every g function evaluations, the particles within all
 252 sub-swarms were mixed and then randomly redistributed to a new sub-swarm. The parti-
 253 cles were then again updated according Eq.1. This process continued till $\mathcal{FR} * \mathbf{N}$ number
 254 of functions evaluations, where \mathcal{FR} represents the fraction of evaluations with the multi-
 255 swarms. At the end of these function evaluations, we froze all the solutions represented
 256 by various particles and chose the particle with best solution among $\mathcal{GL}_1 \cdots \mathcal{GL}_{NS}$ as the
 257 initial candidate vector \mathcal{G} for the remaining $(1 - \mathcal{FR}) * \mathbf{N}$ number of function evaluations.
 258 This particle was then updated according to the following rule

$$\mathcal{G}_{new}(\mathbf{J}) = \mathcal{G}(\mathbf{J}) + \mathbf{r}_{normal}(\mathbf{J})\sigma(\mathbf{J}) \quad (3)$$

259 where \mathbf{J} represents the set containing the specific dimensions being perturbed, r_{normal}
 260 denotes a normal random vector of the same dimensions as \mathcal{G} . σ is the amplitude of
 261 perturbation given by following equation

$$\sigma = \mathbf{R}(\mathcal{MAX} - \mathcal{MIN}) \quad (4)$$

262 where \mathbf{R} is the scalar perturbation size parameter, \mathcal{MAX} and \mathcal{MIN} are $(\mathcal{K} \times 1)$ vec-
 263 tors that represent the maximum and minimum bounds on each dimension. The set \mathbf{J}
 264 was constructed using a probability function \mathcal{P}_j that represented the probability whether
 265 a specific dimension j was perturbed or not. This function is a monotonically decreasing
 266 function that decreases with the number of function evaluations. \mathcal{P}_j can be any monoton-
 267 ically decreasing function, in our approach we used the following function

$$\mathcal{P}_j = 1 - \log(j/(\beta(1 - \mathcal{FR}) * \mathbf{N})) \quad (5)$$

where β is the perturbation frequency probability modulator. Thus the number of dimensions of the candidate vector that are updated or perturbed decreases with the as the number of function evaluations increase. These updates are greedy in nature, so \mathcal{G}_{new} becomes the new solution vector only if it is better than the old one \mathcal{G} .

Acknowledgements

This study was supported by the National Science Foundation GK12 award (DGE-1045513) and by the National Science Foundation CAREER award (FILLMEIN).




Fig. 1: Schematic of the extrinsic and intrinsic coagulation cascade. Inactive zymogens upstream (grey) are activated by exposure to tissue factor (TF) following vessel injury. Tissue factor and activated factor VIIa (FVIIa) form a complex that activates factor X (fX) and IX (fIX). FXa activates downstream factors including factor VIII (fVIII) and fIX. Factor V (fV) is primarily activated by thrombin (FIIa). In addition, we included a secondary fV activation route involving FXa. FXa and FVa form a complex (prothrombinase) on activated platelets that converts prothrombin (fII) to FIIa. FIXa and FVIIIa can also form a complex (tenase) on activated platelets which catalyzes FXa formation. Thrombin also activates upstream coagulation factors, forming a strong positive feedback ensuring rapid activation. Tissue factor pathway inhibitor (TFPI) down-regulates FXa formation and activity by sequestering free FXa and TF-FVIIa in a FXa-dependent manner. Antithrombin III (ATIII) inhibits all proteases. Thrombin inhibits itself binding the surface protein thrombomodulin (TM). The IIa-TM complex catalyzes the conversion of protein C (PC) to activated protein C (APC), which attenuates the coagulation response by the proteolytic cleavage of fV/FVa and fVIII/FVIIIa




Fig. 2: Multi Swarm Particle Swarm Optimization with Dynamically Dimensioned Search. **A:** Each particle represents an N dimensional parameter vector. Particles are randomly initialized and grouped into different sub-swarms. Within each swarm the magnitude and direction of the movement a particle is influenced by the position of the best particle and also by its own experience. After every g number of function evaluations the particles are mixed and randomly assigned to different swarms. At the end of the evaluations (FR) assigned to swarm search, the global best particle (orange color) amongst all sub-swarms is chosen as the candidate parameter vector for Dynamically Dimensioned Search **B:** The candidate vector does a greedy search in a dynamic neighborhood. The search neighborhood is dynamically adjusted by varying the number of dimensions that are perturbed (in black) in each evaluation step. The probability that a dimension is perturbed decreases as the number of function evaluations increase. Thus as the evaluations increase the optimality of the solution is preserved.




Fig. 3: Error convergence rates of the 5 different algorithms on the coagulation model. The objective error is the mean over $N=25$ trials. DDSMLSPSO and DDS have the steepest drop in error during first 2000 function evaluations. Thereafter the error drop in DDS remains nearly constant whereas DDSMLSPSO drops further from around 2000 to 4000 function evaluations. At the end of 4000 function evaluations DDSMLSPSO attains the lowest error.




Fig. 4: Model fits on experimental data using DDSMLSPSO. The model parameters were estimated using DDSMLSPSO. Solid black lines indicate the simulated mean thrombin concentration using parameter vectors from $N=25$ trials. The grey shaded region represents the 99% confidence estimate of the mean simulated thrombin concentration. The experimental data is reproduced from the synthetic plasma assays of Mann and co-workers. Thrombin generation is initiated by adding Factor VIIa-TF (5nM - Red and 5pM - Green) to synthetic plasma containing 200 $\mu\text{mol/L}$ of phospholipid vesicles (PCPS) and a mixture of coagulation factors (II,V,VII,VIII,IX,X and XI) at their mean plasma concentrations.




Fig. 5: Model predictions on unseen experimental data using parameters obtained from DDSMLSPSO. The parameter estimates that were obtained using DDSMLSPSO were tested against data that was not used in the model training. Solid black lines indicate the simulated mean thrombin concentration using parameter vectors from $N=25$ trials. The grey shaded region represents the 99% confidence estimate of the mean simulated thrombin concentration. The experimental data is reproduced from the synthetic plasma assays of Mann and co-workers. Thrombin generation is initiated by adding Factor VIIa-TF (500pM - Blue, 50pM - Pink and 10pM - Orange respectively) to synthetic plasma containing 200 $\mu\text{mol/L}$ of phospholipid vesicles (PCPS) and a mixture of coagulation factors (II,V,VII,VIII,IX,X and XI) at their mean plasma concentrations.

References

2. Assmus HE, Herwig R, Cho KH, Wolkenhauer O (2006) Dynamics of biological systems: role of systems biology in medical research. Expert Review of Molecular Diagnostics .
3. van Riel NAW (2006) Dynamic modelling and analysis of biochemical networks: mechanism-based models and model-based experiments. Briefings in Bioinformatics 7: 364–374.

KEY: Riel:2006aa
ANNOTATION: 10.1093/bib/bbl040
4. Jaqaman K, Danuser G (2006) Linking data to models: data regression. Nat Rev Mol Cell Biol 7: 813–819.

KEY: Jaqaman:2006aa
ANNOTATION: 10.1038/nrm2030
5. Kitano H (2002) Systems biology: a brief overview. Science 295: 1662–1664.
6. Hood L, Heath JR, Phelps ME, Lin B (2004) Systems biology and new technologies enable predictive and preventative medicine. Science 306: 640–643.
7. Aldridge BB, Burke JM, Lauffenburger DA, Sorger PK (2006) Physicochemical modelling of cell signalling pathways. Nat Cell Biol 8: 1195–1203.

KEY: Aldridge:2006aa
ANNOTATION: 10.1038/ncb1497
8. Banga JR (2008) Optimization in computational systems biology. BMC systems biology 2: 47.
9. Ashyraliyev M, Fomekong-Nanfack Y, Kaandorp JA, Blom JG (2009) Systems biology: parameter estimation for biochemical models. Febs Journal 276: 886–902.

10. Moles CG, Mendes P, Banga JR (2003) Parameter estimation in biochemical pathways: a comparison of global optimization methods. *Genome research* 13: 2467–2474.
11. Chen WW, Schoeberl B, Jasper PJ, Niepel M, Nielsen UB, et al. (2009) Input–output behavior of erbb signaling pathways as revealed by a mass action model trained against dynamic data. *Molecular systems biology* 5.
12. Tasseff R, Nayak S, Song SO, Yen A, Varner JD (2011) Modeling and analysis of retinoic acid induced differentiation of uncommitted precursor cells. *Integrative Biology* 3: 578–591.
13. Luan D, Zai M, Varner JD (2007) Computationally derived points of fragility of a human cascade are consistent with current therapeutic strategies. *PLoS computational biology* 3: e142.
14. Mo ML, Jamshidi N, Palsson BØ (2007) A genome-scale, constraint-based approach to systems biology of human metabolism. *Mol BioSyst* 3: 598–603.
15. Orth JD, Conrad TM, Na J, Lerman JA, Nam H, et al. (2011) A comprehensive genome-scale reconstruction of escherichia coli metabolism—2011. *Molecular systems biology* 7.
16. Karr JR, Sanghvi JC, Macklin DN, Gutschow MV, Jacobs JM, et al. (2012) A whole-cell computational model predicts phenotype from genotype. *Cell* 150: 389–401.
17. Büchel F, Rodriguez N, Swainston N, Wrzodek C, Czauderna T, et al. (2013) Path2models: large-scale generation of computational models from biochemical pathway maps. *BMC systems biology* 7: 116.
18. Smallbone K, Simeonidis E, Swainston N, Mendes P (2010) Towards a genome-scale kinetic model of cellular metabolism. *BMC systems biology* 4: 6.

- 323 19. Beck JV, Arnold KJ (1977) Parameter estimation in engineering and science. James
324 Beck.
- 325 20. Nieman R, Fisher D, Seborg D (1971) A review of process identification and param-
326 eter estimation techniques†. International Journal of Control 13: 209–264.
- 327 21. Young P (1981) Parameter estimation for continuous-time models—a survey. Auto-
328 matica 17: 23–39.
- 329 22. Beck JV, Woodbury KA (1998) Inverse problems and parameter estimation: integra-
330 tion of measurements and analysis. Measurement Science and Technology 9:
331 839.
- 332 23. Hooke R, Jeeves TA (1961) “direct search” solution of numerical and statistical prob-
333 lems. Journal of the ACM (JACM) 8: 212–229.
- 334 24. Nelder JA, Mead R (1965) A simplex method for function minimization. The computer
335 journal 7: 308–313.
- 336 25. Moré JJ (1978) The levenberg-marquardt algorithm: implementation and theory. In:
337 Numerical analysis, Springer. pp. 105–116.
- 338 26. Esposito WR, Floudas CA (2000) Deterministic global optimization in nonlinear opti-
339 mal control problems. Journal of Global Optimization 17: 97–126.
- 340 27. Horst R, Tuy H (2013) Global optimization: Deterministic approaches. Springer Sci-
341 ence & Business Media.
- 342 28. Kirkpatrick S, Gelatt CD, Vecchi MP, et al. (1983) Optimization by simulated anneal-
343 ing. science 220: 671–680.
- 344 29. Storn R, Price K (1997) Differential evolution—a simple and efficient heuristic for
345 global optimization over continuous spaces. Journal of global optimization 11:
346 341–359.

30. Sun J, Garibaldi JM, Hodgman C (2012) Parameter estimation using metaheuristics in systems biology: a comprehensive review. *Computational Biology and Bioinformatics*, IEEE/ACM Transactions on 9: 185–202.
31. Mendes P, Kell D (1998) Non-linear optimization of biochemical pathways: applications to metabolic engineering and parameter estimation. *Bioinformatics* 14: 869–883.
32. Modchang C, Triampo W, Lenbury Y (2008) Mathematical modeling and application of genetic algorithm to parameter estimation in signal transduction: Trafficking and promiscuous coupling of g-protein coupled receptors. *Computers in Biology and Medicine* 38: 574–582.
33. Tsai KY, Wang FS (2005) Evolutionary optimization with data collocation for reverse engineering of biological networks. *Bioinformatics* 21: 1180–1188.
34. Wang FS, Su TL, Jang HJ (2001) Hybrid differential evolution for problems of kinetic parameter estimation and dynamic optimization of an ethanol fermentation process. *Industrial & engineering chemistry research* 40: 2876–2885.
35. Noman N, Iba H (2007) Inferring gene regulatory networks using differential evolution with local search heuristics. *IEEE/ACM Transactions on Computational Biology and Bioinformatics (TCBB)* 4: 634–647.
36. Tashkova K, Korošec P, Šilc J, Todorovski L, Džeroski S (2011) Parameter estimation with bio-inspired meta-heuristic optimization: modeling the dynamics of endocytosis. *BMC systems biology* 5: 159.
37. Villaverde AF, Egea JA, Banga JR (2012) A cooperative strategy for parameter estimation in large scale systems biology models. *BMC systems biology* 6: 75.
38. Rodriguez-Fernandez M, Egea JA, Banga JR (2006) Novel metaheuristic for parameter estimation in nonlinear dynamic biological systems. *BMC bioinformatics* 7:

483.

39. Egea JA, Rodríguez-Fernández M, Banga JR, Martí R (2007) Scatter search for chemical and bio-process optimization. *Journal of Global Optimization* 37: 481–503.
40. Villaverde AF, Henriques D, Smallbone K, Bongard S, Schmid J, et al. (2015) Biopredyn-bench: a suite of benchmark problems for dynamic modelling in systems biology. *BMC systems biology* 9: 8.
41. Fan M, Kuwahara H, Wang X, Wang S, Gao X (2015) Parameter estimation methods for gene circuit modeling from time-series mrna data: a comparative study. *Briefings in bioinformatics* : bbv015.
42. Gutenkunst RN, Waterfall JJ, Casey FP, Brown KS, Myers CR, et al. (2007) Universally sloppy parameter sensitivities in systems biology models. *PLoS computational biology* 3: e189.
43. Song SO, Chakrabarti A, Varner JD (2010) Ensembles of signal transduction models using pareto optimal ensemble techniques (poets). *Biotechnology journal* 5: 768–780.
44. Luan D, Szlam F, Tanaka KA, Barie PS, Varner JD (2010) Ensembles of uncertain mathematical models can identify network response to therapeutic interventions. *Molecular bioSystems* 6: 2272–2286.
45. Sagar A, Varner JD (2015) Dynamic modeling of the human coagulation cascade using reduced order effective kinetic models. *Processes* 3: 178–203.
46. Tolson BA, Shoemaker CA (2007) Dynamically dimensioned search algorithm for computationally efficient watershed model calibration. *Water Resources Research* 43.

47. Peer E, Van den Bergh F, Engelbrecht A (2003) Using neighbourhoods with the guaranteed convergence pso. In: Swarm Intelligence Symposium, 2003. SIS'03. Proceedings of the 2003 IEEE. IEEE, pp. 235–242.
48. Zhan ZH, Zhang J, Li Y, Chung HSH (2009) Adaptive particle swarm optimization. Systems, Man, and Cybernetics, Part B: Cybernetics, IEEE Transactions on 39: 1362–1381.
49. Li C, Liu Y, Zhou A, Kang L, Wang H (2007) A fast particle swarm optimization algorithm with cauchy mutation and natural selection strategy. In: Advances in computation and intelligence, Springer. pp. 334–343.
50. Zhao SZ, Liang JJ, Suganthan PN, Tasgetiren MF (2008) Dynamic multi-swarm particle swarm optimizer with local search for large scale global optimization. In: Evolutionary Computation, 2008. CEC 2008.(IEEE World Congress on Computational Intelligence). IEEE Congress on. IEEE, pp. 3845–3852.
51. Liang JJ, Suganthan PN (2005) Dynamic multi-swarm particle swarm optimizer with local search. In: Evolutionary Computation, 2005. The 2005 IEEE Congress on. IEEE, volume 1, pp. 522–528.
52. Mann KG, Butenas S, Brummel K (2003) The dynamics of thrombin formation. Arteriosclerosis, thrombosis, and vascular biology 23: 17–25.
53. Mann K, Brummel K, Butenas S (2003) What is all that thrombin for? Journal of Thrombosis and Haemostasis 1: 1504–1514.
54. Mann KG (2003) Thrombin formation. CHEST Journal 124: 4S–10S.
55. Vogler EA, Siedlecki CA (2009) Contact activation of blood-plasma coagulation. Biomaterials 30: 1857–1869.
56. Diamond SL (2013) Systems biology of coagulation. Journal of Thrombosis and

Haemostasis 11: 224–232.

57. Fogelson AL, Tania N (2005) Coagulation under flow: the influence of flow-mediated transport on the initiation and inhibition of coagulation. *Pathophysiology of haemostasis and thrombosis* 34: 91–108.
58. Anand M, Rajagopal K, Rajagopal K (2003) A model incorporating some of the mechanical and biochemical factors underlying clot formation and dissolution in flowing blood: review article. *Journal of Theoretical Medicine* 5: 183–218.
59. Hockin MF, Jones KC, Everse SJ, Mann KG (2002) A model for the stoichiometric regulation of blood coagulation. *Journal of Biological Chemistry* 277: 18322–18333.
60. Chatterjee MS, Denney WS, Jing H, Diamond SL (2010) Systems biology of coagulation initiation: kinetics of thrombin generation in resting and activated human blood. *PLoS computational biology* .
61. Mann KG, Brummel-Ziedins K, Orfeo T, Butenas S (2006) Models of blood coagulation. *Blood Cells, Molecules, and Diseases* 36: 108–117.




Fig. S6: Error convergence on 300 dimensional Ackley function and Rastrigin function. **(A)** Error convergence of 5 different metaheuristics on 300 dimensional Ackley function **(B)** Error convergence of 5 different metaheuristics on 300 dimensional Rastrigin function




Fig. S7: Difference between optimal and nominal parameter vector values on benchmark problems. **(A)** Problem B1: Genome wide kinetic model of *E.coli* *S.cerevisiae* with 1759 unknown parameters. **(B)** Problem B4: Metabolic model of Chinese Hamster Ovary Cells (CHO) cells with 117 parameters.