

A Dissertation

entitled

Something About Swirling Modes

with Asymmetric Price Information and No Goods

by

Elmer J. Fudd

Submitted to the Graduate Faculty as partial fulfillment of the requirements for the
Masters of Science Degree in Mechanical Engineering

Dr. Ray Hixon, Committee Chair

Dr. Anita Bath, Committee Member

Dr. Chris P. Bacon, Committee Member

Dr. Adam Baum, Committee Member

Dr. Corey O. Graff, Committee Member

Dr. Hugh Jass, Committee Member

Dr. Noah Lott, Committee Member

Dr. Jean Poole, Committee Member

Dr. Patricia R. Komuniecki, Dean
College of Graduate Studies

The University of Toledo

December 2021

Copyright 2021, Elmer J. Fudd

This document is copyrighted material. Under copyright law, no parts of this document may be reproduced without the expressed permission of the author.

An Abstract of
Something About Swirling Modes
with Asymmetric Price Information and No Goods

by

Elmer J. Fudd

Submitted to the Graduate Faculty as partial fulfillment of the requirements for the
Masters of Science Degree in Mechanical Engineering

The University of Toledo
December 2021

[Insert the abstract to your work here]

[Insert your dedication here]

Acknowledgments

[Insert your acknowledgements here]

Contents

Abstract	iii
Acknowledgments	v
Contents	vi
List of Tables	viii
List of Figures	ix
List of Abbreviations	x
List of Symbols	xi
Preface	xii
1 Insert the Heading to Chapter 1	1
1.1 Divergence operations in new coordinate systems	1
1.2 Using cylindrical basis vectors to create Kousen’s aerodynamic model	6
1.2.1 Aerodynamic Model	9
1.3 Mean Flow Equations	9
1.4 Back to buisness.. . . .	10
1.4.1 Axial Shear Flow	10
1.5 Accounting for solid body swirl	11
1.5.1 Linearizing the governing equations	13

1.5.1.1	Linearizing Conservation of Mass	13
1.5.1.2	Linearizing the Conservation of Momentum in the r direction	17
1.5.1.3	Linearizing the Conservation of Momentum in the θ direction	19
1.5.1.4	Linearizing the Conservation of Momentum in the x direction	21
1.5.1.5	Linearizing the Energy Equation	23
1.6	Substituting Perturbation Variables	25
1.7	Non-Dimensionalization	29
1.8	Appendix A: Speed of Sound	31
1.9	Appendix B: Isentropic Waves	35
2	Insert the Heading to Chapter 2	37
	References	38
A	Insert the Heading to Appendix A	39
B	Insert the Heading to Appendix B	40

List of Tables

List of Figures

List of Abbreviations

ABBREV	This is where you provide a brief definition of the abbreviation “ABBREV”
BB	B.B. King
BSE	Bovine Spongiform Encephalopathy (Mad Cow Disease)
CB	L.D. Caskey and J.D. Beazley, <i>Attic Vase Paintings in the Museum of Fine Arts</i> , Boston (Oxford 1931–1963)
GLE	Gauss’ law for electricity: $\nabla \cdot E = \frac{\rho}{\varepsilon_0} = 4\pi k\rho$
HHS	Department of Health and Human Services
IaR	I am root

List of Symbols

\ddagger	the degree to which the flayrod has gone out of skew on tredel
\triangle	the ratio of the M2 monetary aggregate to the Monetary Base
α	angle of rotation around internal rotation axis
β	the number of people named “Bob”
Q	Tobin’s q; the ratio of the market value of installed capital to the replacement cost of capital
Y	Gross Domestic Product (adjusted for inflation)

Preface

[Insert your preface here]

Chapter 1

Insert the Heading to Chapter 1

1.1 Divergence operations in new coordinate systems

The introduction of numbers as
coordinates is an act of violence.”

Hermann Weyl

Hermann Weyl was a renown mathematician and physicist who has made revolutionary contributions to the field of differential geometry and topology. In his work on manifolds, he proposed the idea of working without coordinates and showed the application of multi-variable without the need to define a coordinate system , using coordinates when only absolutely necessary. This perspective emphasizes the distinction between quantities and the various coordinates systems that can be used to describe their change and behavior. The divergence, (∇) , represents the operation of taking derivatives of a vector field. However, understanding the mathematical and physical representation of the divergence operator into new coordinate systems serves as a good prerequisite for the application of the Navier Stokes equations for the evaluation of aerodynamic models in unusual flow domains. Although there are many resources that will provide equations in varying coordinate systems, the derivation

offers insight into the advantages and drawbacks of using a new reference frame for a flow domain. The divergence operator in Cartesian coordinates is, This is also important because eigenmode analysis tells us the domain of a pulse traveling through the domain at a frequency that is intrinsic to the flow itself

$$\vec{\nabla} \equiv \hat{e}_x \frac{\partial}{\partial x} + \hat{e}_y \frac{\partial}{\partial y} + \hat{e}_z \frac{\partial}{\partial z} = 0$$

The vectors, $\hat{e}_x, \hat{e}_y, \hat{e}_z$ (commonly denoted in literature as $\hat{i}, \hat{j}, \hat{k}$) are the basis vectors of the Cartesian coordinate system. The vector hat ($\hat{\cdot}$) reminds us that divergence operation includes a scalar product of the basis vectors and the individual derivative terms themselves. These basis vectors *scale* with the derivatives d/dx d/dy d/dz in the direction of these basis vectors themselves. This implicitly captures the coordinate system and assumptions that corresponds to the basis vectors themselves.

To relate the basis vectors of the cylindrical coordinate system to the Cartesian coordinate system, we use the following relations,

$$\begin{aligned} r &= \sqrt{x^2 + y^2} \\ \theta &= \tan^{-1} \left(\frac{y}{x} \right) \\ &= \cos^{-1} \left(\frac{x}{r} \right) \\ &= \sin^{-1} \left(\frac{y}{r} \right) \end{aligned}$$

Note that the equation above also establishes $x = r \cos \theta$ and $y = r \sin \theta$. The Cartesian basis vectors are related to the cylindrical basis vectors of the new coordinate system by,

$$\hat{e}_r = \hat{e}_x \cos \theta + \hat{e}_y \sin \theta$$

$$\hat{e}_\theta = -\hat{e}_x \sin \theta + \hat{e}_y \cos \theta$$

$$\hat{e}_z = \hat{e}_z$$

Defining these relationships, (they'll be useful later)

$$\begin{aligned}\frac{\partial \hat{e}_r}{\partial r} &= \frac{\partial \hat{e}_\theta}{\partial r} = \frac{\partial \hat{e}_z}{\partial r} = 0 \\ \frac{\partial \hat{e}_r}{\partial \theta} &= -\hat{e}_x \sin \theta + \hat{e}_y \cos \theta = \hat{e}_\theta \\ \frac{\partial \hat{e}_\theta}{\partial \theta} &= -(\hat{e}_x \cos \theta + \hat{e}_y \sin \theta) = -\hat{e}_r\end{aligned}$$

The multi-variable chain rule for differentiation is then used to express the Cartesian variables, $\frac{\partial}{\partial x}, \frac{\partial}{\partial y}, \frac{\partial}{\partial z}$, with respect to the cylindrical variable.

$$\frac{\partial}{\partial x} = \frac{\partial}{\partial r} \frac{dr}{dx} + \frac{\partial}{\partial \theta} \frac{d\theta}{dx} + \frac{\partial}{\partial z} \frac{dz}{dx}$$

$$\frac{\partial}{\partial y} = \frac{\partial}{\partial r} \frac{dr}{dy} + \frac{\partial}{\partial \theta} \frac{d\theta}{dy} + \frac{\partial}{\partial z} \frac{dz}{dy}$$

By finding the derivatives of r & θ with respect to x and y , we can substitute terms in the Cartesian divergence definition. First, $\frac{dr}{dx}$ & $\frac{dr}{dy}$ is calculated,

$$\begin{aligned}
\frac{dr}{dx} &= \frac{d}{dx} \left([x^2 + y^2]^{1/2} \right) \\
&= \frac{1}{2} [x^2 + y^2]^{-1/2} (2x) \\
&= \frac{x}{\sqrt{x^2 + y^2}} \\
&= \frac{r \cos \theta}{r} \\
\boxed{\frac{dr}{dx} = \cos \theta}
\end{aligned}$$

$$\begin{aligned}
\frac{dr}{dy} &= \frac{d}{dy} \left([x^2 + y^2]^{1/2} \right) \\
&= \frac{1}{2} [x^2 + y^2]^{-1/2} (2y) \\
&= \frac{y}{\sqrt{x^2 + y^2}} \\
&= \frac{r \sin \theta}{r} \\
\boxed{\frac{dr}{dy} = \sin \theta}
\end{aligned}$$

Then, $\frac{d\theta}{dx}$ & $\frac{d\theta}{dy}$ is found.

$$\begin{aligned}
\frac{d\theta}{dx} &= \frac{d}{dx} \left(\tan^{-1} \left(\frac{y}{x} \right) \right) \\
&= \frac{d}{du} \tan^{-1}(u) \frac{d}{dx} \left(\frac{y}{x} \right) \\
&= \frac{1}{u^2 + 1} \frac{-y}{x^2} \\
&= -\frac{y}{y^2 + x^2} \\
\boxed{\frac{d\theta}{dx} = -\frac{\sin \theta}{r}}
\end{aligned}$$

$$\begin{aligned}
\frac{d\theta}{dy} &= \frac{d}{dy} \left(\tan^{-1} \left(\frac{y}{x} \right) \right) \\
&= \frac{d}{du} \tan^{-1}(u) \frac{d}{dy} \left(\frac{y}{x} \right) \\
&= \frac{1}{u^2 + 1} \frac{1}{x} \\
&= \frac{x}{y^2 + x^2} \\
\boxed{\frac{d\theta}{dy} = \frac{\cos\theta}{r}}
\end{aligned}$$

Through substitution back into the chain rule expansion,

$$\begin{aligned}
\frac{\partial}{\partial x} &= \frac{\partial}{\partial r} \cos \theta - \frac{\partial}{\partial \theta} \frac{1}{r} \sin \theta \\
\frac{\partial}{\partial y} &= \frac{\partial}{\partial r} \sin \theta + \frac{\partial}{\partial \theta} \frac{1}{r} \cos \theta
\end{aligned}$$

We can now convert our divergence operator, $\vec{\nabla}$

$$\begin{aligned}
\vec{\nabla} &= \frac{\partial}{\partial x} \hat{e}_x + \frac{\partial}{\partial y} \hat{e}_y + \frac{\partial}{\partial z} \hat{e}_z = 0 \\
&= \left(\frac{\partial}{\partial r} \cos \theta - \frac{\partial}{\partial \theta} \frac{1}{r} \sin \theta \right) \hat{e}_x + \left(\frac{\partial}{\partial r} \sin \theta + \frac{\partial}{\partial \theta} \frac{1}{r} \cos \theta \right) \hat{e}_y + \frac{\partial}{\partial z} \hat{e}_z = 0
\end{aligned}$$

Rearranging like terms (containing cylindrical derivative variables), and factoring out $1/r$

$$\begin{aligned}\vec{\nabla} &= \left(\frac{\partial}{\partial r} \cos \theta - \frac{\partial}{\partial \theta} \frac{1}{r} \sin \theta \right) \hat{e}_x + \left(\frac{\partial}{\partial r} \sin \theta + \frac{\partial}{\partial \theta} \frac{1}{r} \cos \theta \right) \hat{e}_y + \frac{\partial}{\partial z} \hat{e}_z = 0 \\ &= (\hat{e}_x \cos \theta + \hat{e}_y \sin \theta) \frac{\partial}{\partial r} + \frac{1}{r} (\hat{e}_y \cos \theta - \hat{e}_x \sin \theta) \frac{\partial}{\partial \theta} + \frac{\partial}{\partial z} \hat{e}_z = 0\end{aligned}$$

Recalling the definitions for \hat{e}_r and \hat{e}_θ , we can use these expressions to rewrite ∇ in polar coordinates

$$\vec{\nabla} = \hat{e}_r \frac{\partial}{\partial r} + \frac{1}{r} \hat{e}_\theta \frac{\partial}{\partial \theta} + \frac{\partial}{\partial z} \hat{e}_z = 0$$

1.2 Using cylindrical basis vectors to create Kousen's aerodynamic model

$$\frac{DV}{dt} = \frac{1}{\rho} \nabla \cdot \boldsymbol{\sigma}$$

$$\boldsymbol{\sigma} = -p\mathbf{I}_3 + \tau$$

where $[\mathbf{I}_3]$ is a 3 by 3 identity matrix and τ is the shear stress tensor. The velocity vector for a three dimensional flow.

$$\vec{V} = v_r(r, \theta, x, t)\hat{e}_r + v_\theta(r, \theta, x, t)\hat{e}_\theta + v_x(r, \theta, x, t)\hat{e}_x \quad (1.1)$$

In Kousen's work, a velocity vector is written as a function of radius, and the radial velocity component is neglected.

$$\vec{V} = v_\theta(r)\hat{e}_\theta + v_x(r)\hat{e}_x \quad (1.2)$$

We will go with the first definition and cancel out the radial velocity later on.

$$\frac{DV}{dt} = \frac{\partial \vec{V}}{\partial t} \frac{dt}{dt} + \frac{\partial \vec{V}}{\partial r} \frac{dr}{dt} + \frac{\partial \vec{V}}{\partial \theta} \frac{d\theta}{dt} + \frac{\partial \vec{V}}{\partial x} \frac{dx}{dt}$$

Starting with the first term,

$$\begin{aligned}
\frac{\partial \vec{V}}{\partial t} \frac{dt}{dt} &= \frac{\partial}{\partial t} (v_r \hat{e}_r + v_\theta \hat{e}_\theta + v_x \hat{e}_x) * 1 \\
&= \frac{\partial v_r}{\partial t} \hat{e}_r + \cancel{\frac{\partial \hat{e}_r}{\partial t} v_r} + \frac{\partial v_\theta}{\partial t} \hat{e}_\theta + \cancel{\frac{\partial \hat{e}_\theta}{\partial t} v_\theta} + \frac{\partial v_x}{\partial t} \hat{e}_x + \cancel{\frac{\partial \hat{e}_x}{\partial t} v_x} \\
\boxed{\frac{\partial \vec{V}}{\partial t} &= \frac{\partial v_r}{\partial t} \hat{e}_r + \frac{\partial v_\theta}{\partial t} \hat{e}_\theta + \frac{\partial v_x}{\partial t} \hat{e}_x}
\end{aligned}$$

$$\begin{aligned}
\frac{\partial \vec{V}}{\partial r} \frac{dr}{dt} &= \frac{\partial \vec{V}}{\partial r} v_r \\
&= \frac{\partial}{\partial r} [v_r \hat{e}_r + v_\theta \hat{e}_\theta + v_x \hat{e}_x] v_r \\
&= \left(\frac{\partial v_r}{\partial r} \hat{e}_r + \cancel{\frac{\partial \hat{e}_r}{\partial r} v_r} + \frac{\partial v_\theta}{\partial r} \hat{e}_\theta + \cancel{\frac{\partial \hat{e}_\theta}{\partial r} v_\theta} + \frac{\partial v_x}{\partial r} \hat{e}_x + \cancel{\frac{\partial \hat{e}_x}{\partial r} v_x} \right) v_r \\
\boxed{\frac{\partial \vec{V}}{\partial r} \frac{dr}{dt} &= \left[\frac{\partial v_r}{\partial r} \hat{e}_r + \frac{\partial v_\theta}{\partial r} \hat{e}_\theta + \frac{\partial v_x}{\partial r} \hat{e}_x \right] v_r}
\end{aligned}$$

Recalling that arc length is $ds = r d\theta$, and angular velocity is $d\theta/dt = v_\theta/r$

$$\begin{aligned}
\frac{\partial \vec{V}}{\partial \theta} \frac{d\theta}{dt} &= \frac{\partial \vec{V}}{\partial \theta} \frac{v_\theta}{r} \\
&= \frac{\partial}{\partial \theta} [v_r \hat{e}_r + v_\theta \hat{e}_\theta + v_x \hat{e}_x] \frac{v_\theta}{r} \\
&= \left[\frac{\partial v_r}{\partial \theta} \hat{e}_r + \underbrace{\frac{\partial \hat{e}_r}{\partial \theta}}_{\hat{e}_\theta} v_r + \frac{\partial v_\theta}{\partial \theta} \hat{e}_\theta + \underbrace{\frac{\partial \hat{e}_\theta}{\partial \theta}}_{-\hat{e}_r} v_\theta + \frac{\partial v_x}{\partial \theta} \hat{e}_x \right] \frac{v_\theta}{r} \\
\boxed{\frac{\partial \vec{V}}{\partial \theta} \frac{dr}{dt} &= \left[\left(\frac{\partial v_r}{\partial \theta} - v_\theta \right) \hat{e}_r + \left(\frac{\partial v_\theta}{\partial \theta} + v_r \right) \hat{e}_\theta + \frac{\partial v_x}{\partial \theta} \hat{e}_x \right] \frac{v_\theta}{r}}
\end{aligned}$$

$$\begin{aligned}
\frac{\partial \vec{V}}{\partial x} \frac{dx}{dt} &= \frac{\partial \vec{V}}{\partial x} v_x \\
&= \frac{\partial}{\partial x} [v_r \hat{e}_r + v_\theta \hat{e}_\theta + v_x \hat{e}_x] v_r \\
&= \left(\frac{\partial v_r}{\partial x} \hat{e}_r + \cancel{\frac{\partial \hat{e}_r}{\partial x} v_r} + \frac{\partial v_\theta}{\partial x} \hat{e}_\theta + \cancel{\frac{\partial \hat{e}_\theta}{\partial x} v_\theta} + \frac{\partial v_x}{\partial r} \hat{e}_x + \cancel{\frac{\partial \hat{e}_x}{\partial x} v_\theta} \right) v_x \\
\boxed{\frac{\partial \vec{V}}{\partial x} \frac{dx}{dt} &= \left[\frac{\partial v_r}{\partial x} \hat{e}_r + \frac{\partial v_\theta}{\partial x} \hat{e}_\theta + \frac{\partial v_x}{\partial x} \hat{e}_x \right] v_x}
\end{aligned}$$

Putting these terms together,

$$\begin{aligned}
\frac{DV}{dt} &= \left[\frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + \frac{v_\theta^2}{r} \frac{\partial v_r}{\partial \theta} - \frac{v_\theta}{r} + v_x \frac{\partial v_r}{\partial x} \right] \hat{e}_r + \\
&\quad \left[\frac{\partial v_\theta}{\partial t} + v_r \frac{\partial v_\theta}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_\theta}{\partial \theta} + \frac{v_r v_\theta}{r} + v_x \frac{\partial v_\theta}{\partial x} \right] \hat{e}_\theta + \\
&\quad \left[\frac{\partial v_x}{\partial t} + v_r \frac{\partial v_x}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_x}{\partial \theta} + v_x \frac{\partial v_x}{\partial x} \right] \hat{e}_x
\end{aligned}$$

If we neglect viscosity on the right hand side, we will arrive at the linearized Euler equations

$$\begin{aligned}
\nabla \sigma &= -\nabla p [\mathbf{I}_3] \\
&= -\frac{1}{\rho} \left\{ \begin{array}{ccc} \frac{\partial p}{\partial r} & 0 & 0 \\ 0 & \frac{1}{r} \frac{\partial p}{\partial \theta} & 0 \\ 0 & 0 & \frac{\partial p}{\partial x} \end{array} \right\}
\end{aligned}$$

1.2.1 Aerodynamic Model

We can rewrite the Euler equations in cylindrical form.

$$\begin{aligned}
\text{Conservation of Mass} &\rightarrow \frac{\partial \rho}{\partial t} + v_r \frac{\partial \rho}{\partial r} + \frac{v_\theta}{r} \frac{\partial \rho}{\partial \theta} + v_x \frac{\partial \rho}{\partial x} + \rho \left(\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{1}{r} \frac{\partial v_\theta}{\partial \theta} \right) \\
\text{Conservation of Momentum in the } \hat{e}_r \text{ direction} &\rightarrow \frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_r}{\partial \theta} - \frac{v_\theta^2}{r} + v_x \frac{\partial v_r}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial r} \\
\text{Conservation of Momentum in the } \hat{e}_\theta \text{ direction} &\rightarrow \frac{\partial v_\theta}{\partial t} + v_r \frac{\partial v_\theta}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_\theta}{\partial \theta} + \frac{v_r v_\theta}{r} + v_x \frac{\partial v_\theta}{\partial x} = -\frac{1}{\rho r} \frac{\partial p}{\partial \theta} \\
\text{Conservation of Momentum in the } \hat{e}_x \text{ direction} &\rightarrow \frac{\partial v_x}{\partial t} + v_r \frac{\partial v_x}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_x}{\partial \theta} + v_x \frac{\partial v_x}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial x} \\
\text{Conservation of Energy} &\rightarrow \frac{\partial p}{\partial t} + v_r \frac{\partial p}{\partial r} + \frac{v_\theta}{r} \frac{\partial p}{\partial \theta} + v_x \frac{\partial p}{\partial x} + \gamma p \left(\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{1}{r} \frac{\partial v_\theta}{\partial \theta} \right)
\end{aligned}$$

1.3 Mean Flow Equations

For steady flow, the continuity, momentum and entropy equations are

$$\nabla(\vec{V}\bar{\rho}) = 0$$

$$(\vec{V} \cdot \nabla)\vec{V}$$

$$\nabla S = 0$$

If we neglect radial velocity, the velocity vector in cylindrical coordinates are

$$\vec{V}(r, \theta, x) = V_x(r)\hat{e}_x + V_\theta(r)\hat{e}_\theta$$

See Appendix for speed of sound derivation

1.4 Back to buisness..

Kousen studied three specific flow configuration.

- axial shear flow
- solid body swirl
- free vortex swirl

1.4.1 Axial Shear Flow

In Kousen's paper, axial sheared flows through a constant area duct was also investigated. he only effect on the velocity gradient occurs along the x axis. All other primitive variables (pressure and density which is \propto speed of sound) are constant. As a result, the only changes that occur are in the x direction. This implies that $\partial/\partial\theta = 0$. For the conservation of mass,

$$\nabla(\vec{V}\bar{\rho}) = \left(\underbrace{\frac{\partial(\bar{\rho}v_r)}{\partial r}}_{v_r=0} + \underbrace{\frac{1}{r}\frac{\partial\bar{\rho}v_\theta}{\partial\theta}}_{\frac{\partial}{\partial\theta}} + \frac{\partial\bar{\rho}v_x}{\partial x} \right) = \frac{\partial\bar{\rho}v_x}{\partial x}$$

Conservation of Momentum in the radial direction becomes:

$$(\vec{V} \cdot \nabla)\vec{V} = v_r \cancel{\frac{\partial v_r}{\partial r}} + \frac{v_\theta}{r} \cancel{\frac{\partial v_r}{\partial \theta}} - \frac{v_\theta^2}{r} + v_x \cancel{\frac{\partial v_r}{\partial x}} = -\frac{1}{\rho} \frac{\partial p}{\partial r}$$

$$\frac{v_\theta^2}{r} = \frac{1}{\rho} \frac{\partial p}{\partial r}$$

$$\frac{\rho v_\theta^2}{r} = \frac{\partial p}{\partial r}$$

θ direction

$$(\vec{V} \cdot \nabla)\vec{V} = v_r \cancel{\frac{\partial v_\theta}{\partial r}} + \frac{v_\theta}{r} \cancel{\frac{\partial v_\theta}{\partial \theta}} + \frac{v_r v_\theta}{r} + v_x \frac{\partial v_\theta}{\partial x} = -\frac{1}{\rho r} \frac{\partial p}{\partial \theta}$$

Dividing v_x to the other side,

$$\frac{\partial v_\theta}{\partial x} = 0$$

Similarly for the x direction,

$$\frac{\partial v_x}{\partial x} = 0$$

In regards to the entropy equation, having an isentropic flow, $\nabla S = 0$ implies $a^2 = \frac{\nabla \bar{p}}{\nabla \bar{\rho}}$

1.5 Accounting for solid body swirl

If the flow contains a swirling component, then the primitive variables are nonuniform through the flow, and mean flow assumptions are not valid. To account to this, we integrate the momentum equation in the radial direction with respect to the radius.

Equation (2.5) in [?] is

$$P = \int_{\tilde{r}}^1 \frac{\bar{\rho} V_\theta^2}{\tilde{r}} d\tilde{r}$$

where \tilde{r} is the radius dimensional radius normalized by the tip diameter $r_t = r_{max}$

To show the work, we will start with the dimensional form of the equation,

$$\frac{\bar{\rho} v_\theta^2}{r} = \frac{\partial p}{\partial r}$$

Applying separation of variables

$$\int_r^{r_{max}} \frac{\bar{\rho} v_\theta^2}{r} \partial r = - \int_{P(r)}^{P(r_{max})} \partial p$$

Since $\tilde{r} = r/r_{max}$

$$r = \tilde{r} r_{max}$$

taking total derivatives (applying chain rule)

$$dr = d(\tilde{r}r_{max}) = d(\tilde{r})r_{max}$$

Substituting these back in and evaluating the right hand side,

$$\int_{\tilde{r}}^1 \frac{\bar{\rho} v_{\theta}^2}{\tilde{r}} d\tilde{r} = P(1) - P(\tilde{r})$$

For reference the minimum value of \tilde{r} is

$$\sigma = \frac{r_{max}}{r_{min}}$$

For

$$\frac{\partial a^2}{\partial r} = \frac{\partial}{\partial r} \left(\frac{\gamma P}{\rho} \right)$$

Using the quotient rule, we can extract the definition of the speed of sound.

$$\begin{aligned} &= \frac{\partial P}{\partial r} \frac{\gamma \bar{\rho}}{\bar{\rho}^2} - \left(\frac{\gamma P}{\bar{\rho}^2} \right) \frac{\partial \bar{\rho}}{\partial r} \\ &= \frac{\partial P}{\partial r} \frac{\gamma}{\bar{\rho}} - \left(\frac{a^2}{\bar{\rho}} \right) \frac{\partial \bar{\rho}}{\partial r} \\ \text{Using } \partial P / a^2 = \partial \rho \rightarrow &= \frac{\partial P}{\partial r} \frac{\gamma}{\bar{\rho}} - \left(\frac{1}{\bar{\rho}} \right) \frac{\partial \bar{P}}{\partial r} \\ &\frac{\partial a^2}{\partial r} = \frac{\partial P}{\partial r} \frac{\gamma - 1}{\bar{\rho}} \\ \text{or.. } \frac{\bar{\rho}}{\gamma - 1} \frac{\partial a^2}{\partial r} &= \frac{\partial P}{\partial r} \end{aligned}$$

Going back to the radial momentum equation, and rearranging the

$$\begin{aligned}
\frac{\bar{\rho} v_\theta^2}{r} &= \frac{\partial P}{\partial r} \\
\frac{\bar{\rho} v_\theta^2}{r} &= \frac{\bar{\rho}}{\gamma - 1} \frac{\partial a^2}{\partial r} \\
\frac{v_\theta^2}{r} (\gamma - 1) &= \frac{\partial a^2}{\partial r} \\
\text{Dividing both sides by } a^2 \rightarrow \frac{M_\theta}{r} (\gamma - 1) &= \frac{\partial a^2}{\partial r} \frac{1}{a^2}
\end{aligned}$$

$$\begin{aligned}
\text{Integrating both sides } \int_r^{r_{max}} \frac{M_\theta}{r} (\gamma - 1) \partial r &= \int_{a^2(r)}^{a^2(r_{max})} \frac{1}{a^2} \partial a^2 \\
\int_r^{r_{max}} \frac{M_\theta^2}{r} (\gamma - 1) \partial r &= \ln(a^2(r_{max})) - \ln(a^2(r)) \\
\int_r^{r_{max}} \frac{M_\theta^2}{r} (\gamma - 1) \partial r &= \ln\left(\frac{a^2(r_{max})}{a^2(r)}\right)
\end{aligned}$$

Defining non dimensional speed of sound $\tilde{a} = \frac{a(r)}{a(r_{max})}$

$$\begin{aligned}
\int_r^{r_{max}} \frac{M_\theta}{r} (\gamma - 1) \partial r &= \ln\left(\frac{1}{\tilde{a}^2}\right) \\
&= -2\ln(\tilde{a}) \\
\tilde{a}(r) &= \exp\left[-\int_r^{r_{max}} \frac{M_\theta}{r} \frac{(\gamma - 1)}{2} \partial r\right] \\
\text{replacing r with } \tilde{r} \rightarrow \tilde{a}(r) &= \exp\left[-\int_r^{r_{max}} \frac{M_\theta}{r} \frac{(\gamma - 1)}{2} \partial r\right] \\
\tilde{a}(\tilde{r}) &= \exp\left[\left(\frac{1 - \gamma}{2}\right) \int_{\tilde{r}}^1 \frac{M_\theta}{\tilde{r}} \partial \tilde{r}\right]
\end{aligned}$$

1.5.1 Linearizing the governing equations

1.5.1.1 Linearizing Conservation of Mass

To linearize the Euler equations, we substitute each flow variable with its equivalent mean and perturbation components. Note that the mean term is only a function

of space whereas the perturbation component is a dependent on both space and time (functional dependence is not explicitly written with each variable). Assuming that we can divide the variable into a known laminar flow solution to the Navier-Stokes equations and a small amplitude perturbation solution:

$$v_r = V_r(x) + v'_r \tag{1.3}$$

$$v_\theta = V_\theta + v'_\theta \tag{1.4}$$

$$v_x = V_x + v'_x \tag{1.5}$$

$$p = \bar{p} + p' \tag{1.6}$$

$$\rho = \bar{\rho} + \rho' \tag{1.7}$$

Starting with continuity,

$$\begin{aligned}
& \frac{\partial \rho}{\partial t} + v_r \frac{\partial \rho}{\partial r} + \frac{v_\theta}{r} \frac{\partial \rho}{\partial \theta} + v_x \frac{\partial \rho}{\partial x} + \rho \left(\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{1}{r} \frac{\partial v_\theta}{\partial \theta} + \frac{\partial v_x}{\partial x} \right) = 0 \\
& \frac{\partial \bar{\rho} + \rho'}{\partial t} + (V_r + v'_r) \frac{\partial \bar{\rho} + \rho'}{\partial r} + \frac{V_\theta + v'_\theta}{r} \frac{\partial \bar{\rho} + \rho'}{\partial \theta} + (V_x + v'_x) \frac{\partial \bar{\rho} + \rho'}{\partial x} + \\
& (\bar{\rho} + \rho') \left(\frac{1}{r} \frac{\partial(r(V_r + v'_r))}{\partial r} + \frac{1}{r} \frac{\partial(V_\theta + v'_\theta)}{\partial \theta} + \frac{\partial(V_x + v'_x)}{\partial x} \right) = 0 \\
& \frac{\partial \bar{\rho}}{\partial t} + \frac{\partial \rho'}{\partial t} + \\
& V_r \frac{\partial \bar{\rho}}{\partial r} + v'_r \frac{\partial \bar{\rho}}{\partial r} + V_r \frac{\partial \rho'}{\partial r} + v'_r \frac{\partial \rho'}{\partial r} + \\
& \frac{1}{r} \left(V_\theta \frac{\partial \bar{\rho}}{\partial \theta} + v'_\theta \frac{\partial \bar{\rho}}{\partial \theta} + V_\theta \frac{\partial \rho'}{\partial \theta} + v'_\theta \frac{\partial \rho'}{\partial \theta} \right) + \\
& V_x \frac{\partial \bar{\rho}}{\partial x} + v'_x \frac{\partial \bar{\rho}}{\partial x} + V_x \frac{\partial \rho'}{\partial x} + v'_x \frac{\partial \rho'}{\partial x} + \\
& \bar{\rho} \left(\frac{1}{r} \left(\frac{\partial(rV_r)}{\partial r} + \frac{\partial(rv'_r)}{\partial r} + \frac{\partial V_\theta}{\partial \theta} + \frac{\partial v'_\theta}{\partial \theta} \right) + \frac{\partial V_x}{\partial x} + \frac{\partial v'_x}{\partial x} \right) + \\
& \rho' \left(\frac{1}{r} \left(\frac{\partial(rV_r)}{\partial r} + \frac{\partial(rv'_r)}{\partial r} + \frac{\partial V_\theta}{\partial \theta} + \frac{\partial v'_\theta}{\partial \theta} \right) + \frac{\partial V_x}{\partial x} + \frac{\partial v'_x}{\partial x} \right) = 0
\end{aligned}$$

Important things to note

- The small disturbances are infinitesimal (thus linearized)
- Neglect second order terms.
- The continuity equation is comprised of mean velocity components. This is subtracted off in each of the governing equations

Blue will be used for terms that are removed after subtracting in the original continuity equation, green will be used to cancel higher(2nd) order terms. Red will be used if we take the radial velocity to be zero.

$$\begin{aligned}
&= \cancel{\frac{\partial \bar{\rho}}{\partial t}} + \frac{\partial \rho'}{\partial t} + \\
&\quad \cancel{V_r} \frac{\partial \bar{\rho}}{\partial r} + \cancel{v'_r} \frac{\partial \bar{\rho}}{\partial r} + \cancel{V_r} \frac{\partial \rho'}{\partial r} + \cancel{v'_r} \frac{\partial \rho'}{\partial r} + \\
&\quad \frac{1}{r} \left(\cancel{V_\theta} \frac{\partial \bar{\rho}}{\partial \theta} + \cancel{v'_\theta} \frac{\partial \bar{\rho}}{\partial \theta} + V_\theta \frac{\partial \rho'}{\partial \theta} + v'_\theta \frac{\partial \rho'}{\partial \theta} \right) + \\
&\quad \cancel{V_x} \frac{\partial \bar{\rho}}{\partial x} + \cancel{v'_x} \frac{\partial \bar{\rho}}{\partial x} + V_x \frac{\partial \rho'}{\partial x} + v'_x \frac{\partial \rho'}{\partial x} + \\
&\quad \bar{\rho} \left(\frac{1}{r} \left(\cancel{\frac{\partial(rV_r)}{\partial r}} + \frac{\partial(rv'_r)}{\partial r} + \cancel{\frac{\partial V_\theta}{\partial \theta}} + \frac{\partial v'_\theta}{\partial \theta} \right) + \cancel{\frac{\partial V_x}{\partial x}} + \frac{\partial v'_x}{\partial x} \right) + \\
&\quad \rho' \left(\frac{1}{r} \left(\cancel{\frac{\partial(rV_r)}{\partial r}} + \frac{\partial(rv'_r)}{\partial r} + \cancel{\frac{\partial V_\theta}{\partial \theta}} + \frac{\partial v'_\theta}{\partial \theta} \right) + \cancel{\frac{\partial V_x}{\partial x}} + \frac{\partial v'_x}{\partial x} = 0 \right)
\end{aligned}$$

$$\boxed{\frac{\partial \rho'}{\partial t} + \frac{V_\theta}{r} \frac{\partial \rho'}{\partial \theta} + V_x \frac{\partial \rho'}{\partial x} + \bar{\rho} \left(\frac{1}{r} \left(\frac{\partial r v'_r}{\partial r} + \frac{\partial v'_\theta}{\partial \theta} \right) + \frac{\partial v'_x}{\partial x} \right) = 0}$$

1.5.1.2 Linearizing the Conservation of Momentum in the r direction

Starting with the mean momentum equation

$$\frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_r}{\partial \theta} - \frac{v_\theta^2}{r} + v_x \frac{\partial v_r}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial r}$$

Looking at the left hand side first

$$\begin{aligned} & \frac{\partial(V_r + v'_r)}{\partial t} + (V_r + v'_r) \frac{\partial(V_r + v'_r)}{\partial r} + \frac{V_\theta + v'_\theta}{r} \frac{\partial(V_r + v'_r)}{\partial \theta} - \frac{(V_\theta + v'_\theta)^2}{r} + (V_x + v'_x) \frac{\partial(V_r + v'_r)}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial r} \\ & \quad \frac{\partial V_r}{\partial t} + \frac{\partial v'_r}{\partial t} + \\ & \quad \frac{V_r}{r} \frac{\partial V_r}{\partial r} + \frac{v'_r}{r} \frac{\partial V_r}{\partial r} + \frac{V_r}{r} \frac{\partial v'_r}{\partial r} + \frac{v'_r}{r} \frac{\partial v'_r}{\partial r} + \\ & \quad \frac{1}{r} \left(V_\theta \frac{\partial V_r}{\partial \theta} + v'_\theta \frac{\partial V_r}{\partial \theta} + V_\theta \frac{\partial v'_r}{\partial \theta} + v'_\theta \frac{\partial v'_r}{\partial \theta} \right) - \\ & \quad \frac{1}{r} \left(V_\theta^2 + 2V_\theta v'_\theta + v'^2_\theta \right) + \\ & \quad \frac{V_x}{r} \frac{\partial V_r}{\partial x} + \frac{v'_x}{r} \frac{\partial V_r}{\partial x} + V_x \frac{\partial v'_r}{\partial x} + v'_x \frac{\partial v'_r}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial r} \\ & \quad \frac{\partial v'_r}{\partial t} + V_r \frac{\partial v'_r}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_r}{\partial \theta} - \frac{2V_\theta v'_\theta}{r} + V_x \frac{\partial v'_r}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial r} \end{aligned}$$

Now looking at the right side, Expanding the $1/\rho$ using a Taylor series approximation

$$\begin{aligned}
 \frac{1}{\bar{\rho} + \rho'} &= \frac{1}{\bar{\rho}} + \left(\frac{1}{\bar{\rho} + \rho'} - \frac{1}{\bar{\rho}} \right) \\
 &= \frac{1}{\bar{\rho}} + \left(\frac{\bar{\rho}}{\bar{\rho}(\bar{\rho} + \rho')} - \frac{1}{\bar{\rho}} \frac{\bar{\rho} + \rho'}{\bar{\rho} + \rho'} \right) \\
 &= \frac{1}{\bar{\rho}} - \left(\frac{\bar{\rho} - \bar{\rho} + \rho'}{\bar{\rho}(\bar{\rho} + \rho')} \right) \\
 &= \frac{1}{\bar{\rho}} - \frac{\rho'}{\bar{\rho}} \underbrace{\left(\frac{1}{\bar{\rho} + \rho'} \right)}_{\text{This is what we're solving for!}} \\
 &= \frac{1}{\bar{\rho}} - \frac{\rho'}{\bar{\rho}} \underbrace{\left[\frac{1}{\bar{\rho}} + \left(\frac{1}{\bar{\rho} + \rho'} - \frac{1}{\bar{\rho}} \right) \right]}_{\text{This is from step 1}} \\
 &= \frac{1}{\bar{\rho}} - \frac{\rho'}{\bar{\rho}^2} + \underbrace{\left[\left(\frac{\rho'}{\bar{\rho}} \right)^2 \frac{1}{\bar{\rho} + \rho'} \right]}_{\text{These are higher order terms that will go to } \infty}
 \end{aligned}$$

Plugging this back in to the right hand side, (don't forget the negative!) $\rightarrow \frac{1}{\rho} \frac{\partial p}{\partial r} = \left(-\frac{1}{\bar{\rho}} + \frac{\rho'}{\bar{\rho}^2} \right) \left(\dots \right)$

$$\begin{aligned}
 \frac{1}{\rho} \frac{\partial p}{\partial r} &= -\cancel{\frac{1}{\bar{\rho}} \frac{\partial \bar{p}}{\partial r}} - \frac{1}{\bar{\rho}} \frac{\partial p'}{\partial r} + \frac{\rho'}{\bar{\rho}^2} \frac{\partial \bar{p}}{\partial r} \\
 \frac{1}{\rho} \frac{\partial p}{\partial r} &= -\frac{1}{\bar{\rho}} \frac{\partial p'}{\partial r} + \frac{\rho'}{\bar{\rho}^2} \frac{\partial \bar{p}}{\partial r}
 \end{aligned}$$

$$\boxed{\frac{\partial v'_r}{\partial t} + \frac{V_\theta}{r} \frac{\partial v'_r}{\partial \theta} - \frac{2V_\theta v'_\theta}{r} + V_x \frac{\partial v'_r}{\partial x} = \frac{1}{\bar{\rho}} \frac{\partial p'}{\partial r} + \frac{\rho'}{\bar{\rho}^2} \frac{\partial \bar{p}}{\partial r}}$$

1.5.1.3 Linearizing the Conservation of Momentum in the θ direction

Starting with the mean momentum equation

$$\frac{\partial v_\theta}{\partial t} + v_r \frac{\partial v_\theta}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_\theta}{\partial \theta} + \frac{v_r v_\theta}{r} + v_x \frac{\partial v_\theta}{\partial x} = -\frac{1}{\rho r} \frac{\partial p}{\partial \theta}$$

Looking at the left hand side first

$$\begin{aligned} & \frac{\partial(V_\theta + v'_\theta)}{\partial t} + (V_r + v'_r) \frac{\partial(V_\theta + v'_\theta)}{\partial r} + \frac{V_\theta + v'_\theta}{r} \frac{\partial(V_\theta + v'_\theta)}{\partial \theta} + \frac{(V_r + v'_r)(V_\theta + v'_\theta)}{r} + (V_x + v'_x) \frac{\partial(V_\theta + v'_\theta)}{\partial x} \\ & \quad + \cancel{\frac{\partial V_\theta}{\partial t}} + \cancel{\frac{\partial v'_\theta}{\partial t}} + \cancel{V_r \frac{\partial V_\theta}{\partial r}} + \underbrace{\cancel{v'_r \frac{\partial V_\theta}{\partial r}}}_{?} + \cancel{V_r \frac{\partial v'_\theta}{\partial r}} + \cancel{v'_r \frac{\partial v'_\theta}{\partial r}} + \\ & \quad \frac{1}{r} \left(\cancel{V_\theta \frac{\partial V_\theta}{\partial \theta}} + \cancel{v'_\theta \frac{\partial V_\theta}{\partial \theta}} + V_\theta \frac{\partial v'_\theta}{\partial \theta} + \cancel{v'_\theta \frac{\partial v'_\theta}{\partial \theta}} \right) + \\ & \quad \frac{1}{r} (\cancel{V_r V_\theta} + v'_r V_\theta + \cancel{V_r v'_\theta} + \cancel{v'_r v'_\theta}) + \\ & \quad \cancel{V_x \frac{\partial V_\theta}{\partial x}} + \cancel{v'_x \frac{\partial V_\theta}{\partial x}} + V_x \frac{\partial v'_\theta}{\partial x} + \cancel{v'_x \frac{\partial v'_\theta}{\partial x}} + \\ & \quad \frac{\partial v'_\theta}{\partial t} + v'_r \frac{\partial V_\theta}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{v'_r V_\theta}{r} + V_x \frac{\partial v'_\theta}{\partial x} \end{aligned}$$

Now looking at the right side, Expanding the $1/\rho$ using a Taylor series approximation

$$\begin{aligned} & \rightarrow -\frac{1}{\rho r} \frac{\partial p}{\partial \theta} = \left(-\frac{1}{\bar{\rho}} + \frac{\rho'}{\bar{\rho}^2} \right) \left(\frac{\partial \bar{p} + p'}{\partial \theta} \right) \\ & \frac{1}{\rho r} \frac{\partial p}{\partial \theta} = \cancel{-\frac{1}{\bar{\rho}} \frac{\partial \bar{p}}{\partial \theta}} - \frac{1}{\bar{\rho} r} \frac{\partial p'}{\partial \theta} + \frac{\rho'}{\bar{\rho}^2 r} \frac{\partial \bar{p}}{\partial \theta} + \frac{\rho'}{\bar{\rho}^2 r} \frac{\partial p'}{\partial \theta} \\ & \frac{1}{\rho r} \frac{\partial p}{\partial \theta} = -\frac{1}{\bar{\rho}} \frac{\partial p'}{\partial \theta} \end{aligned}$$

$$\boxed{\frac{\partial v'_\theta}{\partial t} + v'_r \frac{\partial V_\theta}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{v'_r V_\theta}{r} + V_x \frac{\partial v'_r}{\partial x} = -\frac{1}{\bar{\rho} r} \frac{\partial p'}{\partial \theta}}$$

1.5.1.4 Linearizing the Conservation of Momentum in the x direction

Starting with the mean momentum equation

$$\frac{\partial v_x}{\partial t} + v_r \frac{\partial v_x}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_x}{\partial \theta} + v_x \frac{\partial v_x}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial x}$$

$$\begin{aligned} \frac{\partial(V_x + v'_x)}{\partial t} + (V_r + v'_r) \frac{\partial(V_x + v'_x)}{\partial r} + \frac{V_\theta + v'_\theta}{r} \frac{\partial(V_x + v'_x)}{\partial \theta} + (V_x + v'_x) \frac{\partial(V_x + v'_x)}{\partial x} &= -\frac{1}{\rho} \frac{\partial p}{\partial x} \\ &\quad \frac{\cancel{V_x}}{\cancel{\partial t}} + \frac{\partial v'_x}{\partial t} + \\ &\quad \cancel{V_r} \frac{\cancel{\partial V_x}}{\partial r} + v'_r \frac{\partial V_x}{\partial r} + \cancel{V_r} \frac{\cancel{\partial v'_x}}{\partial r} + v'_r \frac{\partial v'_x}{\partial r} + \\ &\quad \frac{1}{r} \left(\cancel{V_\theta} \frac{\cancel{\partial V_x}}{\partial \theta} + \cancel{v'_\theta} \frac{\cancel{\partial V_x}}{\partial \theta} + V_\theta \frac{\partial v'_x}{\partial \theta} + v'_\theta \frac{\partial v'_x}{\partial \theta} \right) + \\ &\quad \cancel{V_x} \frac{\cancel{\partial V_x}}{\partial x} + \cancel{v'_x} \frac{\cancel{\partial V_x}}{\partial x} + V_x \frac{\partial v'_x}{\partial x} + v'_x \frac{\partial v'_x}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial x} \\ &\quad \boxed{\frac{\partial v'_x}{\partial t} + v'_r \frac{\partial V_x}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_x}{\partial \theta} + V_x \frac{\partial v'_x}{\partial x} = -\frac{1}{\rho} \frac{\partial p}{\partial x}} \end{aligned}$$

$$\begin{aligned}
\rightarrow -\frac{1}{\rho} \frac{\partial p}{\partial x} &= \left(-\frac{1}{\bar{\rho}} + \frac{\rho'}{\bar{\rho}^2} \right) \left(\frac{\partial \bar{p} + p'}{\partial x} \right) \\
\frac{1}{\rho} \frac{\partial p}{\partial x} &= -\cancel{\frac{1}{\bar{\rho}} \frac{\partial \bar{p}}{\partial x}} - \frac{1}{\bar{\rho}} \frac{\partial p'}{\partial x} + \cancel{\frac{\rho'}{\bar{\rho}^2 r} \frac{\partial \bar{p}}{\partial x}} + \cancel{\frac{\rho'}{\bar{\rho}^2 r} \frac{\partial p'}{\partial x}} \\
\frac{1}{\rho} \frac{\partial p}{\partial x} &= -\frac{1}{\bar{\rho}} \frac{\partial p'}{\partial x}
\end{aligned}$$

$$\boxed{\frac{\partial v'_x}{\partial t} + v'_r \frac{\partial V_x}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_x}{\partial \theta} + V_x \frac{\partial v'_x}{\partial x} = -\frac{1}{\bar{\rho}} \frac{\partial p'}{\partial x}}$$

1.5.1.5 Linearizing the Energy Equation

$$\frac{\partial p}{\partial t} + v_r \frac{\partial p}{\partial r} + \frac{v_\theta}{r} \frac{\partial p}{\partial \theta} + v_x \frac{\partial p}{\partial x} + \gamma p \left(\frac{1}{r} \frac{\partial r v_r}{\partial r} + \frac{1}{r} \frac{\partial v_\theta}{\partial \theta} + \frac{\partial v_x}{\partial x} \right) = 0$$

$$\begin{aligned} \frac{\partial(\bar{P} + P')}{\partial t} + (V_r + v'_r) \frac{\partial(\bar{P} + P')}{\partial r} + \frac{(V_\theta + v'_\theta)}{r} \frac{\partial(\bar{P} + P')}{\partial \theta} + (V_x + v'_x) \frac{\partial(\bar{P} + P')}{\partial x} + \dots \\ \gamma(\bar{P} + P') \left(\frac{1}{r} \frac{\partial r(V_r + v'_r)}{\partial r} + \frac{1}{r} \frac{\partial(V_\theta + v'_\theta)}{\partial \theta} + \frac{\partial(V_x + v'_x)}{\partial x} \right) = 0 \end{aligned}$$

$$\begin{aligned} & \frac{\partial \bar{P}}{\partial t} + \frac{\partial P'}{\partial t} + \\ & V_r \frac{\partial \bar{P}}{\partial r} + V_r \frac{\partial P'}{\partial r} + V'_r \frac{\partial \bar{P}}{\partial r} + V'_r \frac{\partial P'}{\partial r} + \\ & \frac{V_\theta}{r} \frac{\partial \bar{P}}{\partial \theta} + \frac{V_\theta}{r} \frac{\partial P'}{\partial \theta} + \frac{v'_\theta}{r} \frac{\partial \bar{P}}{\partial \theta} + \frac{v'_\theta}{r} \frac{\partial P'}{\partial \theta} + \\ & V_x \frac{\partial \bar{P}}{\partial x} + V_x \frac{\partial P'}{\partial x} + v'_x \frac{\partial \bar{P}}{\partial x} + v'_x \frac{\partial P'}{\partial x} + \\ & \gamma \bar{P} \left(\frac{1}{r} \frac{\partial r V_r}{\partial r} + \frac{1}{r} \frac{\partial r v'_r}{\partial r} + \frac{1}{r} \frac{\partial V_\theta}{\partial \theta} + \frac{\partial v'_\theta}{\partial \theta} + \frac{\partial V_x}{\partial x} + \frac{\partial v'_x}{\partial x} \right) \\ & \gamma P' \left(\frac{1}{r} \frac{\partial r V_r}{\partial r} + \frac{1}{r} \frac{\partial r v'_r}{\partial r} + \frac{1}{r} \frac{\partial V_\theta}{\partial \theta} + \frac{\partial v'_\theta}{\partial \theta} + \frac{\partial V_x}{\partial x} + \frac{\partial v'_x}{\partial x} \right) \end{aligned}$$

$$\boxed{\frac{\partial p'}{\partial t} + v'_r \frac{\partial P}{\partial r} + \frac{V_\theta}{r} \frac{\partial p'}{\partial \theta} + V_x \frac{\partial p'}{\partial x} + \gamma P \left(\frac{1}{r} \frac{\partial(r v'_r)}{\partial r} + \frac{1}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{\partial v'_x}{\partial x} \right) = 0}$$

The linearized Euler equations are,

$$\begin{aligned}
\frac{\partial \rho'}{\partial t} + \frac{V_\theta}{r} \frac{\partial \rho'}{\partial \theta} + V_x \frac{\partial \rho'}{\partial x} + \bar{\rho} \left(\frac{1}{r} \left(\frac{\partial r v'_r}{\partial r} + \frac{\partial v'_\theta}{\partial \theta} \right) + \frac{\partial v'_x}{\partial x} \right) &= 0 \\
\frac{\partial v'_r}{\partial t} + \frac{V_\theta}{r} \frac{\partial v'_\theta}{\partial \theta} - \frac{2V_\theta v'_\theta}{r} + V_x \frac{\partial v'_r}{\partial x} &= -\frac{1}{\bar{\rho}} \frac{\partial p'}{\partial r} + \frac{\rho'}{\bar{\rho}^2} \frac{\partial \bar{p}}{\partial r} \\
\frac{\partial v'_\theta}{\partial t} + v'_r \frac{\partial V_\theta}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{v'_r V_\theta}{r} + V_x \frac{\partial v'_r}{\partial x} &= -\frac{1}{\bar{\rho} r} \frac{\partial p'}{\partial \theta} \\
\frac{\partial v'_x}{\partial t} + v'_r \frac{\partial V_x}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_x}{\partial \theta} + V_x \frac{\partial v'_x}{\partial x} &= -\frac{1}{\bar{\rho}} \frac{\partial p'}{\partial x} \\
\frac{\partial p'}{\partial t} + v'_r \frac{\partial P}{\partial r} + \frac{V_\theta}{r} \frac{\partial p'}{\partial \theta} + V_x \frac{\partial p'}{\partial x} + \gamma P \left(\frac{1}{r} \frac{\partial (r v'_r)}{\partial r} + \frac{1}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{\partial v'_x}{\partial x} \right) &= 0
\end{aligned}$$

Recalling:

$$\frac{\partial P}{\partial r} = \frac{\bar{\rho} V_\theta^2}{r}$$

$$\gamma P = \bar{\rho} A^2$$

$$\rho' = \frac{1}{A^2} p'$$

We can rearrange the equations to reflect Equations 2.33-2.36. Note that the momentum equation in the θ and x directions remain unchanged. The term $\frac{\partial(rv'_r)}{\partial r} = \frac{\partial(r)}{\partial r} v'_r + \frac{\partial v'_r}{\partial r} r$ in the Energy equation

$$\begin{aligned}
\frac{1}{\bar{\rho} A^2} \left(\frac{\partial p'}{\partial t} + \frac{V_\theta}{r} \frac{\partial p'}{\partial \theta} + V_x \frac{\partial p'}{\partial x} \right) + \frac{V_\theta^2}{A^2 r} v'_r + \frac{\partial v'_r}{\partial r} + \frac{v'_r}{r} + \frac{1}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{\partial v'_x}{\partial x} &= 0 \\
\frac{\partial v'_r}{\partial t} + \frac{V_\theta}{r} \frac{\partial v'_\theta}{\partial \theta} - \frac{2V_\theta v'_\theta}{r} + V_x \frac{\partial v'_r}{\partial x} &= \frac{1}{\bar{\rho}} \frac{\partial p'}{\partial r} + \frac{V_\theta}{\bar{\rho} r A^2} p' \\
\frac{\partial v'_\theta}{\partial t} + v'_r \frac{\partial V_\theta}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{v'_r V_\theta}{r} + V_x \frac{\partial v'_\theta}{\partial x} &= -\frac{1}{\bar{\rho} r} \frac{\partial p'}{\partial \theta} \\
\frac{\partial v'_x}{\partial t} + v'_r \frac{\partial V_x}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_x}{\partial \theta} + V_x \frac{\partial v'_x}{\partial x} &= -\frac{1}{\bar{\rho}} \frac{\partial p'}{\partial x}
\end{aligned}$$

1.6 Substituting Perturbation Variables

$$v'_r = v_r(r)e^{i(k_x x + m\theta - \omega t)}$$

$$v'_\theta = v_\theta(r)e^{i(k_x x + m\theta - \omega t)}$$

$$v'_x = v_x(r)e^{i(k_x x + m\theta - \omega t)}$$

$$p' = p(r)e^{i(k_x x + m\theta - \omega t)}$$

Conservation of Energy

$$\frac{1}{\bar{\rho}A^2} \left(\frac{\partial p'}{\partial t} + \frac{V_\theta}{r} \frac{\partial p'}{\partial \theta} + V_x \frac{\partial p'}{\partial x} \right) + \frac{V_\theta^2}{A^2 r} v'_r + \frac{\partial v'_r}{\partial r} + \frac{1}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{\partial v'_x}{\partial x} = 0$$

LHS derivatives:

$$\frac{\partial p'}{\partial t} = \underbrace{\frac{\partial p(r)}{\partial t}}_0 e^{i(k_x x + m\theta - \omega t)} + p(r) (-i\omega e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial p'}{\partial \theta} = \underbrace{\frac{\partial p(r)}{\partial \theta}}_0 e^{i(k_x x + m\theta - \omega t)} + p(r) (im e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial p'}{\partial x} = \underbrace{\frac{\partial p(r)}{\partial x}}_0 e^{i(k_x x + m\theta - \omega t)} + p(r) (ik_x e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial v'_r}{\partial r} = \frac{\partial v_r(r)}{\partial r} e^{i(k_x x + m\theta - \omega t)} + v_r(r) \underbrace{\frac{\partial}{\partial r} (e^{i(k_x x + m\theta - \omega t)})}_0$$

$$\frac{\partial v'_\theta}{\partial \theta} = \frac{\partial v_\theta(r)}{\partial \theta} e^{i(k_x x + m\theta - \omega t)} + v_\theta(r) (im e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial v'_x}{\partial x} = \underbrace{\frac{\partial v_x(r)}{\partial x}}_0 e^{i(k_x x + m\theta - \omega t)} + v_x(r) (ik_x e^{i(k_x x + m\theta - \omega t)})$$

After substituting and canceling common terms,

$$\begin{aligned} & \frac{1}{\bar{\rho}A^2} \left(p(r) (-i\omega e^{i(k_x x + m\theta - \omega t)}) + \frac{V_\theta}{r} p(r) (ime^{i(k_x x + m\theta - \omega t)}) + V_x p(r) (ik_x e^{i(k_x x + m\theta - \omega t)}) \right) + \\ & \frac{V_\theta^2}{A^2 r} v'_r + \frac{\partial v_r(r)}{\partial r} e^{i(k_x x + m\theta - \omega t)} + \frac{1}{r} (v_\theta(r) (ime^{i(k_x x + m\theta - \omega t)})) + v_x(r) (ik_x e^{i(k_x x + m\theta - \omega t)}) = 0 \end{aligned}$$

$$\begin{aligned} & \frac{1}{\bar{\rho}A^2} \left(-i\omega + \frac{imV_\theta}{r} + ik_x V_x + \right) p(r) \\ & \frac{V_\theta^2}{A^2 r} v'_r + \frac{v'_r}{r} + \frac{\partial v_r(r)}{\partial r} + \frac{im}{r} v_\theta(r) + ik_x v_x(r) = 0 \end{aligned}$$

conservation of momentum in the r direction,

$$\frac{\partial v'_r}{\partial t} + \frac{V_\theta}{r} \frac{\partial v'_r}{\partial \theta} - \frac{2V_\theta}{r} v'_r + V_x \frac{\partial v'_r}{\partial x} = \frac{\partial p'}{\partial r} + \frac{\rho'}{\bar{\rho}^2} \frac{\partial P}{\partial r}$$

LHS derivatives:

$$\frac{\partial v'_r}{\partial t} = \underbrace{\frac{\partial v_r(r)}{\partial t}}_0 e^{i(k_x x + m\theta - \omega t)} + v_r(r) (-i\omega e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial v'_r}{\partial \theta} = \underbrace{\frac{\partial v_r(r)}{\partial \theta}}_0 e^{i(k_x x + m\theta - \omega t)} + v_r(r) (im e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial v'_r}{\partial x} = \underbrace{\frac{\partial v_r(r)}{\partial x}}_0 e^{i(k_x x + m\theta - \omega t)} + v_r(r) (ik_x e^{i(k_x x + m\theta - \omega t)})$$

RHS:

$$\frac{\partial p'}{\partial r} = \frac{\partial P(r)}{\partial r} e^{i(k_x x + m\theta - \omega t)} + P(r) \underbrace{\frac{\partial}{\partial r}}_0 e^{i(k_x x + m\theta - \omega t)}$$

$$\text{Recalling } p'/\rho' = A^2 \rightarrow \rho' = \frac{1}{A^2} p' \frac{\partial \bar{P}}{\partial r} = \frac{\bar{\rho} v_\theta^2}{r}$$

$$\frac{\rho'}{\bar{\rho}^2} \frac{\partial \bar{P}}{\partial r} = \frac{V_\theta^2}{A^2} \frac{1}{\bar{\rho} r} p'$$

After substituting and canceling common terms,

$$\begin{aligned} v_r (-i\omega e^{i(k_x x + m\theta - \omega t)}) + \frac{V_\theta}{r} v_r (im e^{i(k_x x + m\theta - \omega t)}) - \frac{2V_\theta}{r} v_r e^{i(k_x x + m\theta - \omega t)} + V_x (v_r (ik_x e^{i(k_x x + m\theta - \omega t)})) \\ = \left(-\frac{1}{\bar{\rho}} \frac{\partial P(r)}{\partial r} e^{i(k_x x + m\theta - \omega t)} + \frac{V_\theta^2}{A^2} \frac{1}{\bar{\rho} r} P(r) e^{i(k_x x + m\theta - \omega t)} \right) \end{aligned}$$

$$\left(-i\omega + \frac{imV_\theta}{r} + ik_x V_x \right) v_r - \frac{2V_\theta}{r} v_\theta = -\frac{1}{\bar{\rho}} \frac{\partial P}{\partial r} + \frac{V_\theta^2}{A^2} \frac{1}{\bar{\rho} r} p$$

Continuing with conservation of momentum in the θ direction,

$$\frac{\partial v'_\theta}{\partial t} + v'_r \frac{\partial V_\theta}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_\theta}{\partial \theta} + \frac{v'_r V_\theta}{r} + V_x \frac{\partial v'_\theta}{\partial x} = -\frac{1}{\bar{\rho} r} \frac{\partial p'}{\partial \theta}$$

$$\frac{\partial v'_\theta}{\partial t} = \underbrace{\frac{\partial v_\theta(r)}{\partial t}}_0 e^{i(k_x x + m\theta - \omega t)} + v_\theta(r) (-i\omega e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial v'_\theta}{\partial \theta} = \underbrace{\frac{\partial v_\theta(r)}{\partial \theta}}_0 e^{i(k_x x + m\theta - \omega t)} + v_\theta(r) (im e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial v'_\theta}{\partial x} = \underbrace{\frac{\partial v_\theta(r)}{\partial x}}_0 e^{i(k_x x + m\theta - \omega t)} + v_\theta(r) (ik_x e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial p'}{\partial \theta} = \underbrace{\frac{\partial P(r)}{\partial \theta}}_0 e^{i(k_x x + m\theta - \omega t)} + P(r) \underbrace{\frac{\partial}{\partial \theta} e^{i(k_x x + m\theta - \omega t)}}_{me^{i(k_x x + m\theta - \omega t)}}$$

After substituting and canceling common terms

$$\left(-i\omega + \frac{imV_\theta}{r} + ik_x V_x\right) v_\theta + \left(\frac{V_\theta}{r} + \frac{\partial V_\theta}{\partial r}\right) v_\theta = -\frac{m}{\bar{\rho} r} p$$

Next, the conservation of momentum in the x direction,

$$\frac{\partial v'_x}{\partial t} + v'_r \frac{\partial V_x}{\partial r} + \frac{V_\theta}{r} \frac{\partial v'_x}{\partial \theta} + V_x \frac{\partial v'_x}{\partial x} = -\frac{1}{\bar{\rho}} \frac{\partial p'}{\partial x}$$

$$\frac{\partial v'_x}{\partial t} = \underbrace{\frac{\partial v_x(r)}{\partial t}}_0 e^{i(k_x x + m\theta - \omega t)} + v_x(r) (-i\omega e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial v'_x}{\partial \theta} = \underbrace{\frac{\partial v_x(r)}{\partial \theta}}_0 e^{i(k_x x + m\theta - \omega t)} + v_x(r) (im e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial v'_x}{\partial x} = \frac{\partial v_x(r)}{\partial x} e^{i(k_x x + m\theta - \omega t)} + v_x(r) (ik_x e^{i(k_x x + m\theta - \omega t)})$$

$$\frac{\partial p'}{\partial x} = 0 + ik_x p e^{i(k_x x + m\theta - \omega t)}$$

$$\left(-i\omega + \frac{imV_\theta}{r} + ik_x V_x\right) v_x + \frac{\partial V_x}{\partial r} v_r = -\frac{ik_x}{\bar{\rho}} p$$

The Linearized Euler equations now become

$$r\text{-direction: } i\left(-\omega + \frac{m}{r} + k_x V_x\right) v_r - \frac{2\bar{v}_\theta}{r} v_\theta = -\frac{1}{\bar{\rho}} \frac{\partial P}{\partial r} + \frac{V_\theta^2}{A^2} \frac{1}{\bar{\rho} r} p$$

$$\theta\text{-direction: } i\left(-\omega + \frac{m}{r} + k_x V_x\right) v_\theta + \left(\frac{V_\theta}{r} + \frac{\partial V_\theta}{\partial r}\right) v_r = -\frac{m}{\bar{\rho} r} p$$

$$x\text{-direction: } i\left(-\omega + \frac{mV_\theta}{r} + k_x V_x\right) v_x + \frac{\partial V_x}{\partial r} v_r = -\frac{ik_x}{\bar{\rho}} p$$

$$\text{Energy: } \frac{1}{\bar{\rho} A^2} \left(-i\omega + \frac{imV_\theta}{r} + ik_x V_x + \right) p(r) + \frac{V_\theta^2}{A^2 r} v'_r + \frac{v'_r}{r} + \frac{\partial v_r(r)}{\partial r} + \frac{im}{r} v_\theta(r) + ik_x v_x(r) = 0$$

1.7 Non-Dimensionalization

Defining

$$r_T = r_{max}$$

$$A_T = A(r_{max})$$

$$k = \frac{\omega r_T}{A_T}$$

$$\bar{\gamma} = k_x r_T$$

$$\tilde{r} = \frac{r}{r_T}$$

$$\frac{\partial}{\partial r} = \frac{\partial \tilde{r}}{\partial r} \frac{\partial}{\partial \tilde{r}} = \frac{1}{r_T} \frac{\partial}{\partial \tilde{r}}$$

$$V_\theta = M_\theta A$$

$$V_x = M_x A$$

$$\tilde{A} = \frac{A}{A_T}$$

$$v_x = \tilde{v}_x A$$

$$v_r = \tilde{v}_r A$$

$$v_\theta = \tilde{v}_\theta A$$

$$p = \tilde{p} \bar{\rho} A^2$$

$$r\text{-direction: } i \left(-\omega + \frac{mV_\theta}{r} + k_x V_x \right) v_r - \frac{2\tilde{v}_\theta}{r} v_\theta = -\frac{1}{\bar{\rho}} \frac{\partial P}{\partial r} + \frac{V_\theta^2}{A^2} \frac{1}{\bar{\rho} r} p$$

$$\theta\text{-direction: } i \left(-\omega + \frac{m}{r} + k_x V_x \right) v_\theta + \left(\frac{V_\theta}{r} + \frac{\partial V_\theta}{\partial r} \right) v_\theta = -\frac{m}{\bar{\rho} r} p$$

$$x\text{-direction: } i \left(-\omega + \frac{mV_\theta}{r} + k_x V_x \right) v_x + \frac{\partial V_x}{\partial r} v_r = -\frac{ik_x}{\bar{\rho}} p$$

$$\text{Energy: } \frac{1}{\bar{\rho} A^2} i \left(-\omega + \frac{mV_\theta}{r} + k_x V_x \right) p(r) + \frac{V_\theta^2}{A^2 r} v'_r + \frac{v'_r}{r} + \frac{\partial v_r(r)}{\partial r} + \frac{im}{r} v_\theta(r) + ik_x v_x(r) = 0$$

Substituting the non dimensional quantities, and noting r_T and A^2 in each term

$$i \left[-\frac{k}{\tilde{A}} + \frac{mM_\theta}{\tilde{r}} + \bar{\gamma} M_x \right] \tilde{v}_r - \frac{2M_\theta \tilde{v}_\theta}{\tilde{r}} = \frac{1}{\bar{\rho} A^2} \frac{\partial \tilde{p} \bar{\rho} A^2}{\partial \tilde{r}} + M_\theta \frac{\tilde{P}}{\tilde{r}}$$

Similarly for the θ and x directions:

$$i \left[-\frac{k}{\tilde{A}} + \frac{mM_\theta}{\tilde{r}} + \bar{\gamma} M_x \right] \tilde{v}_\theta + \left(\frac{M_\theta}{\tilde{r}} + \frac{1}{A} \frac{\partial M_\theta A}{\partial \tilde{r}} \right) \tilde{v}_r = \frac{im}{\tilde{r}} \tilde{P}$$

$$i \left[-\frac{k}{\tilde{A}} + \frac{mM_\theta}{\tilde{r}} + \bar{\gamma} M_x \right] \tilde{v}_x + \frac{1}{A} \frac{\partial M_x A}{\partial \tilde{r}} \tilde{v}_r = -i\bar{\gamma} \tilde{P}$$

and for the Energy equation:

$$i \left[\frac{k}{\tilde{A}} + \frac{mM_\theta}{\tilde{r}} - \bar{\gamma}M_x \right] \tilde{p} + \frac{M_\theta^2}{\tilde{r}} \tilde{v}_r + \frac{1}{A} \frac{\partial(\tilde{v}_r A)}{\partial \tilde{r}} + \frac{\tilde{v}_r}{\tilde{r}} + \frac{im}{\tilde{r}} \tilde{v}_\theta + i\bar{\gamma} \tilde{v}_x = 0$$

Expanding mean derivatives (using product rule) $\frac{\partial \tilde{p} \bar{\rho} A^2}{\partial \tilde{r}}$

$$i \left[-\frac{k}{\tilde{A}} + \frac{mM_\theta}{\tilde{r}} + \bar{\gamma}M_x \right] \tilde{v}_r - \frac{2M_\theta \tilde{v}_\theta}{\tilde{r}} = \frac{1}{\bar{\rho} A^2} \left(\frac{\partial \tilde{p}}{\partial \tilde{r}} + \frac{\partial \bar{\rho} A^2}{\partial \tilde{r}} \right) + M_\theta \frac{\tilde{P}}{\tilde{r}}$$

$$i \left[-\frac{k}{\tilde{A}} + \frac{mM_\theta}{\tilde{r}} + \bar{\gamma}M_x \right] \tilde{v}_\theta + \left(\frac{M_\theta}{\tilde{r}} + \frac{1}{A} \frac{\partial M_\theta A}{\partial \tilde{r}} \right) \tilde{v}_r = \frac{im}{\tilde{r}} \tilde{P}$$

$$i \left[-\frac{k}{\tilde{A}} + \frac{mM_\theta}{\tilde{r}} + \bar{\gamma}M_x \right] \tilde{v}_x + \frac{1}{A} \frac{\partial M_x A}{\partial \tilde{r}} \tilde{v}_r = -i\bar{\gamma} \tilde{P}$$

1.8 Appendix A: Speed of Sound

Sound wave is a pressure disturbance that moves with at a speed a (insErt sound wave figure here)

By applying a rectangular control volume around this pressure wave, we can apply our conservation equations. We are assuming that these properties are increasing by a small increment. This is why each variable is added by a infinitesimally small term.

Recalling the conservation of mass (continuity equation), $\dot{m} = \text{constant}$

$$\dot{m}_{left} = \dot{m}_{right}$$

Recalling he definition of density, $\rho = m/\bar{V}$ and rewriting $\bar{V} = uA$ (check the units)

$$\rho a \cancel{A} = (\rho + d\rho)(a + da) \cancel{A}$$

Further expanding gives,

$$\rho a = (\rho a + \rho da + a d\rho + dad\rho)$$

We say that $dad\rho$ is so small, we can assume it is zero. This is often referred to as "neglecting higher order terms (H.O.T)". The expression then becomes

$$\frac{da}{a} = -\frac{d\rho}{\rho}$$

For the momentum equation $P + \rho u^2 = \text{constant}$

$$P + \rho a^2 = P + dP + (\rho + d\rho)(a + da)(a + da)$$

But we just said that $\rho a = (\rho + d\rho)(a + da)$

$$P + \rho a^2 = P + dP + \rho a(a + da)$$

$$dP + \rho a da = a$$

Multiplying the second term by a and divide by a, this is essentially multiplying the second term by one.

$$dP + \rho a^2 \frac{da}{a} = a$$

recalling the relation $\frac{da}{a} = -\frac{d\rho}{\rho}$

$$dP - a^2 d\rho = 0$$

$$a^2 = \frac{dP}{d\rho}$$

Since a sound wave is a very weak wave, when it travels through a medium, it only increases the pressure and density, etc. slightly. The effect of this is that friction and heat transfer can be neglected. Since friction cannot be undone, we call this an irreversible process. Whenever there is no transfer of heat, it is called this adiabatic. Thus, the propagation of sound is an adiabatic, reversible process, otherwise called isentropic. Isentropic implies no increase in entropy, which is *not* true in the presence of shock waves.

In the case of a thermally perfect gas, we can say $P = \rho RT$

For a calorically perfect gas we can say $pv^\gamma = \text{constant}$, where v is volume per unit mass, or specific volume

Differentiating and recalling that $v = 1/\rho$

$$a = \sqrt{\frac{\gamma P}{\rho}} = \sqrt{\gamma RT}$$

$$dm = (\rho u)_2 - (\rho u)_1$$

$$D(mV) = (\rho u^2 + P)_2$$

For Steady flow,

$$dm = (\rho u)_2 - (\rho u)_1$$

$$(\rho u)_1 = (\rho u)_2$$

Similarly, for the Momentum equation,

$$(\rho u^2 + P)_1 = (\rho u^2 + P)_2$$

Let us change the coordinate system motion for the traveling wave be independent of time, and thus corresponds to *steady state* wave propagation.

$$u_1 = \bar{u} + a - \frac{1}{2}\partial u$$

$$u_2 = \bar{u} + a + \frac{1}{2}\partial u$$

where, \bar{u} is the average flow velocity and a is the wave speed.

Substituting this back into the conservation of mass

$$(\rho u)_1 = (\rho u)_2$$

$$\left(\rho - \frac{1}{2}\partial\rho\right)\left(\bar{u} - a - \frac{1}{2}\partial u\right) = \left(\rho + \frac{1}{2}\partial\rho\right)\left(\bar{u} - a + \frac{1}{2}\partial u\right)$$

Further expanding

$$\cancel{\rho\bar{u}} - \cancel{\rho a} + \frac{1}{2}(-\rho\partial u - \bar{u} - \bar{u}\partial\rho + a\partial\rho) + \frac{1}{2}\cancel{\partial\rho\partial u} = \cancel{\rho\bar{u}} - \cancel{\rho a} + \frac{1}{2}(\rho\partial u + \bar{u} - \bar{u}\partial\rho - a\partial\rho) + \frac{1}{2}\cancel{\partial\rho\partial u}$$

$$\frac{1}{2}(-\rho\partial u - \bar{u}\partial\rho + a\partial\rho) = \frac{1}{2}(\rho\partial u + \bar{u}\partial\rho - a\partial\rho)$$

$$\rho\partial u + \bar{u}\partial\rho - a\partial\rho = 0$$

$$\rho\partial u + (u - a)\partial\rho = 0$$

Momentum Equation

$$(\rho u^2 + P)_1 = (\rho u^2 + P)_2$$

1.9 Appendix B: Isentropic Waves

$$dU = dW + dQ$$

For adiabatic, reversible processes, the work done by a system with constant pressure and a change in volume is $-pdV$ and the change in heat energy is zero. Hence,

$$dU = -pdV$$

.

The change in enthalpy of such a system can be found by taking the derivative of its expression for a thermodynamic process

$$H = U + pV$$

$$dH = dU + pdV + vdP$$

$$dH = -pdV + pdV + vdP$$

$$dH = vdP$$

The specific heats at constant pressure and constant volume

$$\left(\frac{\partial U}{\partial T}\right)_v = C_v$$

$$\left(\frac{\partial H}{\partial T}\right)_p = C_p$$

$$\gamma = \frac{C_p}{C_v} = \frac{dH}{dU} = -\frac{VdP}{pdV} = -\frac{V}{dV} \frac{dP}{p}$$

Integrating both sides

$$\gamma \frac{dV}{V} = \frac{-dP}{P} \rightarrow \gamma \int \frac{1}{V} dV = - \int \frac{1}{P} dP$$

$$\gamma \ln(V) + \ln(P) = C$$

Using log rules

$$\ln(V^\gamma) + \ln(P) = C$$

$$\ln(pV^\gamma) = C$$

$$pV^\gamma = e^C = C$$

$$\frac{p}{\rho^\gamma}$$

[Insert your text to chapter 1 here. A pretend example of a silly table is provided below (i.e., Table ??).]

Chapter 2

Insert the Heading to Chapter 2

[Insert your text to chapter 2 here. A pretend example of a silly figure is provided below (i.e., Figure ??).]

References

First example: references generated by the “single” option

Friedman, Milton, “The Role of Monetary Policy,” *American Economic Review*, March 1968, 58(1), 1–17.

Keynes, John Maynard, *The General Theory of Employment, Interest, and Money*, New York: Harcourt Brace Jovanovic, 1936.

Smith, Adam, *An Inquiry into the Nature and Causes of the Wealth of Nations*, Edwin Cannan, ed., London: Methuen & Co., Ltd. 1904.

Tobin, James, “A Dynamic Aggregative Model,” *Journal of Political Economy*, April 1955, 63(2), 103–115.

Second example: references generated by the “double” option

Friedman, Milton, “The Role of Monetary Policy,” *American Economic Review*, March 1968, 58(1), 1–17.

Keynes, John Maynard, *The General Theory of Employment, Interest, and Money*, New York: Harcourt Brace Jovanovic, 1936.

Smith, Adam, *An Inquiry into the Nature and Causes of the Wealth of Nations*, Edwin Cannan, ed., London: Methuen & Co., Ltd. 1904.

Tobin, James, “A Dynamic Aggregative Model,” *Journal of Political Economy*, April 1955, 63(2), 103–115.

Appendix A

Insert the Heading to Appendix A

[Insert text to Appendix A (if appendix is needed)]

Appendix B

Insert the Heading to Appendix B

[Insert text to Appendix B (if appendix is needed)]