Knowledge, concepts, and views


One knowledge model; rival theories of semantic memory and concepts, compared by proof

Jeff Shrager

October 2026

2026-10-29


Knowledge, concepts, and views



This talk is about knowledge in CogLean. Until now the library has been about memory and retrieval. Here I'll describe one knowledge model, semantic nets whose nodes are terms, and show three theories built on it: two rival theories of semantic memory, a theory of conceptual combination, and my own 1987 theory of view application. They're compared the same way the memory families are: phenomena stated as laws, and a matrix of which theory has which. The payoff is a result none of them gives alone: a view that turns graded, over-extended number concepts into exact ones, while leaving typicality untouched.


One knowledge model

- A **knowledge net**: labelled links between nodes; one label is the hierarchy (*isa*).
- Nodes are **terms**: atoms (*canary*), structured values (*set the program-plan to MOVE FORWARD 9*), and typed *holes* (*a Real-World-Action*).
- **Everything is links**: frames and slots, patterns, a concept's prototype (its votes), and even *how* a concept decides membership.
- **Processes are generic**: inheritance, verification, prototype similarity, categorization, view application. A theory supplies data and choices, not a new representation.




First, the representation. A knowledge net is a set of labelled links between nodes, with one label for the hierarchy. The nodes are terms: atoms like canary, structured values like "set the program-plan to move forward nine", and typed holes, unfilled places like "a real-world action". Everything a theory knows is links: frames and their slots, patterns, a concept's prototype with its votes, and even the method a concept uses to decide membership. The processes that run on it are generic and proved once in the library. A theory supplies data and a few choices, not a new representation. That's what makes it a foundation rather than a set of separate models.

Semantic nets: what is proved for every net



- **Inheritance**: a property stored once at a superordinate is found by every subordinate (cognitive economy).
- **Override**: a single-valued property stored nearer wins (an ostrich can't fly).
- **Accumulation**: many-valued properties collect up the hierarchy (a canary has wings *and* skin).
- **Distance**: the least number of *isa* links.



The base layer is the semantic net, and its theorems hold for every net. A property stored once at a superordinate is found by every subordinate: that's cognitive economy. A single-valued property stored nearer overrides one higher up, so the ostrich can't fly though birds can. Many-valued properties accumulate: a canary has wings from bird and skin from animal. My first version got this wrong, stopping at the first level that stored any "has" property, so a canary had no skin. The canary test caught it, which is what the worked examples are for. And the distance between two concepts is the least number of isa links between them.

Two theories of semantic verification


Hierarchical network
(Collins & Quillian 1969)

- Move up from the subject, searching properties at each node.
- Each move and each retrieval costs; costs add.
- Cost depends only on *where* things are stored.

Feature comparison
(Smith, Shoben & Rips 1974)

- Stage 1: overall similarity of feature lists; very high, *true*; very low, *false*.
- Otherwise stage 2: compare defining features only.
- Cost depends on *similarity*.

Costs are **ordinal**, steps or stages: the theories disagree about the *order* of verification times, and that is what is proved.




On these nets, two classic rival theories of how people verify "a canary is a bird". Collins and Quillian's hierarchical network moves up from the subject, searching properties at each node, and every move and retrieval costs time, additively. So cost depends only on where things are stored. Smith, Shoben and Rips's feature comparison model compares feature lists: very high overall similarity says true at once, very low says false, and otherwise a second stage checks only the defining features. So cost depends on similarity. I count costs in steps or stages, not milliseconds: the theories disagree about the order of times, and that's what gets proved.

Laws of verification

Stated for *any* verifier, against a hierarchy that says what is true:

- **Distance effect**: the farther category costs more (*a canary is an animal* after *a canary is a bird*).
- **Typicality effect**: two instances equally far below a category, verified at different costs (*robin* faster than *chicken*).
- **Reversal**: an instance verified faster as a member of the farther category (*a chicken is an animal* faster than *a chicken is a bird*).

Proved once: a reversal contradicts the distance effect.



As with memory, the phenomena are laws, stated for any verifier. The distance effect: a farther category costs more. The typicality effect: two instances equally far below a category, like robin and chicken under bird, verified at different costs. And a reversal: an instance verified faster as a member of the farther category, as when a chicken is an animal is faster than a chicken is a bird. One theorem relates them: a reversal contradicts the distance effect.

The semantic-memory matrix

	Distance	Typicality	Reversal
Hierarchical (C&Q)	**has**	**never**	**never**
Feature comparison (SSR)	lacks	can hold	can hold
People (RSS 1973; SSR 1974)	mostly	yes	yes

- C&Q's cells hold for *every* net: cost is distance, so equally distant instances always cost the same.
- The feature model shows both effects with bird features; for every setting, a more similar instance is never slower.
- C&Q's Figure 1 gives the six sentence types of Fig. 2 in the paper's order.

The semantic-memory matrix

	Distance	Typicality	Reversal
Hierarchical (C&Q)	**has**	**never**	**never**
Feature comparison (SSR)	lacks	can hold	can hold
People (RSS 1973; SSR 1974)	mostly	yes	yes

- C&Q's cells hold for every net: cost is distance, so equally distant instances always cost the same.
- The feature model shows both effects with bird features; for every setting, a more similar instance is never slower.
- C&Q's Figure 1 gives the six sentence types of Fig. 2 in the paper's order.

Here's the matrix. The hierarchical model has the distance effect for every net, and can never produce a typicality effect or a reversal, at any setting, because its cost is exactly the distance. The feature model shows both effects with a set of bird features, and so lacks the distance effect; and for every setting, a more similar instance is never slower. The evidence, typicality effects and reversals, refutes the hierarchical model's never cells, which is the history of the field written as theorems. As a faithfulness check, Collins and Quillian's own Figure 1 gives their six sentence types in the order of their Figure 2.

Concepts: combination and over-extension

- **Selective modification** (Smith, Osherson, Rips & Keane 1988): *red* shifts the color votes of *apple* to red and boosts color's diagnosticity.
- **Threshold membership** (Hampton 2007): membership is a nondecreasing function of the same similarity.
- Proved for every setting: the **conjunction effect**, hence **over-extension** (more a member of *red apple* than of *apple*).
- The paper's figures reproduced exactly.

Prototypes are links in the knowledge net, so these theorems apply to any concept held there.

Concepts: combination and over-extension

- **Selective modification** (Smith, Osherson, Rips & Keane 1988): *red* shifts the color votes of *apple* to red and boosts color's diagnosticity.
- **Threshold membership** (Hampton 2007): membership is a nondecreasing function of the same similarity.
- Proved for every setting: the **conjunction effect**, hence **over-extension** (more a member of *red apple* than of *apple*).
- The paper's figures reproduced exactly.

Prototypes are links in the knowledge net, so these theorems apply to any concept held there.

Concepts. The selective modification model combines an adjective with a noun by modifying the noun's prototype: red moves apple's color votes onto red and makes color more diagnostic. With Hampton's threshold model, membership is a nondecreasing function of the same similarity. Proved for every setting: the conjunction effect, and from it over-extension, being more a member of red apple than of apple, which fuzzy logic forbids. The paper's figures come out exactly. And because prototypes are just links in the knowledge net, these theorems apply to any concept held there.

The trouble with numbers

- *multiple of 3*, learned from 3, 6, . . . , 30; *even multiple of 3* by modification.
- 14 is an *even multiple of 3* to degree .80, a *multiple of 3* to .06.
- **Incoherent**: more a member of the combination than of its head.
- **False**: Lean proves 14 is not a multiple of 3.

People know better. So for numbers, something replaces similarity as the arbiter of membership, without removing the prototype.

The trouble with numbers

- *multiple of 3*, learned from 3, 6, . . . , 30; *even multiple of 3* by modification.
- 14 is an *even multiple of 3* to degree .80, a *multiple of 3* to .05.
- **Incoherent**: more a member of the combination than of its head.
- **False**: Lean proves 14 is not a multiple of 3.

People know better. So for numbers, something replaces similarity as the arbiter of membership, without removing the prototype.

Now the problem. Learn multiple of three from the exemplars three through thirty, and form even multiple of three by modification. Then fourteen is an even multiple of three to degree point eight and a multiple of three to degree point oh six. That's incoherent, and Lean proves it false. People know better: for numbers, something other than similarity decides membership. But it can't simply delete the prototype, because people still find some even numbers more typical than others. My 1987 theory of view application offers a mechanism.

View application (Shrager 1987)


A *view* is an abstract schema from outside the domain. Applying it to a theory:

1. **copy** the view;
2. **merge** the theory: match type frames by abstract type, or at random within a kind; the view wins on matched slots;
3. **coerce** re-parented instances through their old and new parents' patterns;
4. **bind** the view's holes from the theory;
5. **single function**: an object bound to one operation leaves the others.

Random ties, never revisited: application gives a *distribution* over theories. Proved for every view and theory: the view is kept, the view wins on matched frames, unmatched frames survive, instances are re-parented.

Knowledge, concepts, and views

View application (Shrager 1987)



View application is the mechanism from my 1987 Machine Learning paper. A view is an abstract schema from outside the domain, such as programmable device or clock time. Applying it copies the view, merges the theory in, matching frames by type, and on a match the view wins, which makes the change non-monotonic. Re-parented instances are coerced through their old and new parents' patterns, the view's holes are bound from the theory, and an object bound to one operation leaves the others. The paper resolves ambiguity at random and never revisits it, so here application gives a distribution over theories. The general properties are proved for every view and theory.

Faithfulness: the paper's Table 4

- Tables 1 and 2 of the paper as data: a BigTrak theory and the CODE.AND.STARTUP view.
- Applying the view gives **Table 4 exactly**, with probability 1/2.
- The other half: *Action-operation* matched to *Immediate-operation* instead of *Memory-operation*, the random choice the paper describes.
- *Do (MOVE FORWARD 9)* becomes *Set the program-plan to (MOVE FORWARD 9)* by coercion; GO leaves Sequence-1; the script runs the memory operation, then the immediate one.

All five steps are the library's; BigTrak is only data.

Faithfulness: the paper's Table 4

- Tables 1 and 2 of the paper as data: a BigTrak theory and the CODE-AND-STARTUP view.
- Applying the view gives **Table 4 exactly**, with probability 1/2.
- The other half: *Action-operation* matched to *Immediate-operation* instead of *Memory-operation*, the random choice the paper describes.
- *Do (MOVE FORWARD 9)* becomes *Set the program-plan to (MOVE FORWARD 9)* by coercion; GO leaves Sequence-1; the script runs the memory operation, then the immediate one.

All five steps are the library's; BigTrak is only data.

Is the formalization faithful? The paper works one example: Tables 1 and 2 are a theory of the BigTrak toy and the code-and-startup view, and Table 4 is the result. Given the two tables as data, the generic process gives Table 4 exactly, half the time. The other half, action-operation is matched to immediate-operation instead, which is exactly the random choice the paper says it makes. You can see each step at work: coercion turns "do move forward nine" into "set the program-plan to move forward nine", GO leaves the sequence, and the script now runs the memory operation and then the immediate one.

An ARITHMETIC view for number concepts


The learner's theory

- *category*: membership by similarity (threshold); combination by modification.
- *multiple of 3*, *even*: prototypes learned from exemplars.

The ARITHMETIC view

- *category*: membership by divisibility (divisor from the concept's name); combination by conjunction.

Applying it: *category* matches *category*, so the view's test and combination win. The concepts' prototypes are not matched, so they are **kept**.



Now apply a view to number concepts. In the learner's theory, the category type frame decides membership by similarity with a threshold, and combines by modification; multiple of three and even have prototypes learned from exemplars. The arithmetic view has its own category frame: membership by divisibility, with the divisor read from the concept's name, and combination by conjunction. Applying it with exactly the same process as the BigTrak: category matches category, so the view's test and combination win. The concepts' own frames, with their prototypes, aren't matched, so they're kept.

Before and after the view

	Before	After
14 in *multiple of 3*	.06	0
14 in *even multiple of 3*	.80 (over-extension)	0
even multiple of 3	similarity, modified prototype	**exactly** $6 \mid n$, every n
Over-extension	at 14	**never**, at any n
Typicality		**unchanged**, every n

- **Dissociation**: 14 as an *even multiple of 3* is more typical (-16) than 9 as a *multiple of 3* (-23), yet only 9 is a member. Before the view, impossible: membership is a nondecreasing function of typicality.
- Graded typicality for an all-or-none concept: Armstrong, Gleitman & Gleitman (1983), *odd number*.

Before and after the view

	Before	After
14 in *multiple of 3*	.06	0
14 in *even multiple of 3*	.80 (over-extension)	0
even multiple of 3	similarity, modified prototype	**exactly 6** | n, every n
Over-extension	at 14	**never**, at any n
Typicality		**unchanged**, every n

- **Dissociation**: 14 as an *even multiple of 3* is more typical (−16) than 9 as a *multiple of 3* (−23), yet only 9 is a member. Before the view, impossible: membership is a nondecreasing function of typicality.
- Graded typicality for an all-or-none concept: Armstrong, Gleitman & Gleitman (1983), *odd number*.

Here's the result. Before the view, fourteen is over-extended. After it, membership in even multiple of three is exactly divisibility by six, proved for every number, so there's no over-extension anywhere. And typicality is unchanged for every number, because the view never touched the prototypes. So typicality and membership come apart: fourteen as an even multiple of three is more typical than nine as a multiple of three, yet only nine is a member. Before the view that's impossible, and it's a theorem: when membership is a nondecreasing function of typicality, a more typical judgment is never less a member. That's what Armstrong, Gleitman and Gleitman found for odd number: people rate some odd numbers as better examples, while insisting membership is all or none. Here it's a derived result.

The concept matrix

	Distance	Typicality	Reversal	Conj. effect	Over-ext.	Dissociation
Hierarchical net	**has**	**never**	**never**	–	–	–
Feature comparison	lacks	can hold	can hold	–	–	–
Selective modification	–	–	–	**has**	**has**	**never**
+ ARITHMETIC view	–	–	–	**has**	**never**	can hold
People	mostly	yes	yes	yes	yes	yes

- **has**/**never**: every setting (conditions stated). lacks/can hold: one setting. –: not stated for that theory.
- Without a view, membership never goes against typicality (any nondecreasing threshold); with it, over-extension never occurs for number concepts.

The concept matrix

	Distance	Typicality	Reversal	Conj. effect	Over-ext.	Dissociation
Hierarchical net	**has**	**never**	**never**	–	–	–
Feature comparison	lacks	can hold	can hold	–	–	–
Selective modification	–	–	–	**has**	**has**	**never**
+ ARITHMETIC view	–	–	–	**has**	**never**	can hold
People	mostly	yes	yes	yes	yes	yes

- **has**/**never**: every setting (conditions stated). lacks/can hold: one setting. –: not stated for that theory.
- Without a view, membership never goes against typicality (any nondecreasing threshold); with it, over-extension never occurs for number concepts.


Putting it together, the concept matrix. The verification theories are rows on the left, the combination theories on the right. The hierarchical net has the distance effect and never the other two; feature comparison lacks it and can show both. Selective modification has the conjunction effect and over-extension at every setting, and because membership is a nondecreasing function of typicality, it can never dissociate them: that's a theorem too. Add the arithmetic view and over-extension never occurs for number concepts, while the conjunction effect in typicality survives, so the dissociation becomes possible. The dashes are honest: those phenomena aren't stated for those theories yet. The people row is a judgment of the evidence, kept apart from the theorems as in the memory matrix.

What this adds, and next

- **One model, many theories**: semantic memory, concept combination and theory change share nets, terms and processes; each theory is data and choices.
- **A rival-theory matrix for knowledge**, as for memory.
- **View application, formalized**: the paper's example exactly, and a new consequence for concepts.

Next:

- **View selection** by EPAM recognition of cues (the 1987 paper had no principled account).
- Spreading activation (Collins & Loftus 1975) as a third family; feature lists as net links.
- Learning views; a cognitive-skills package (problem solving).



So what does this add? One knowledge model carrying several theories: semantic memory, conceptual combination and theory change share the same nets, terms and processes, and each theory is data plus a few choices. A matrix of rival theories for knowledge, like the one for memory. And view application formalized for the first time: the paper's own example comes out exactly, and applied to concepts it yields a consequence the 1987 paper never considered. Next: view selection by EPAM recognition of cues, which would join the two theories and supply what the 1987 paper lacked, a principled account of how a view is chosen; spreading activation as a third family of semantic memory; learning the views themselves; and a cognitive-skills package for problem solving.