Inside the proofs

Recognition, retrieval and confident errors, in Lean
(partner to "Recognition, retrieval and confident errors")

Jeff Shrager

October 2026

Inside the proofs



- This deck walks through the actual Lean code behind the companion talk. Code is quoted from the repository, lightly trimmed; "– ..." marks omissions.
- The point is architecture: how one behavioral theorem, confident errors, is assembled from small, general pieces, and then inherited.

The proof, layer by layer

`MultiDigit/AnyMemory`, `Experiments/FaceNaming`: instances

`Phenomena/RetrievalLaws`: laws; `confident_errors_of_laws`

`Process/RecognizeRetrieve`: the composition; `confident_errors`


`Process/SampledRetrieval`: DOA search; closed forms $(1 - R)^n$, $Q \cdot G_n$

`Memory/DiscriminationNet`: nets, `select`, `path`; Lemma A (confusions agree on the path)

`Rep/Distribution`: exact finite distributions; `bind`, `prob`, the two-stage lemma

Inside the proofs

The proof, layer by layer



- Each layer imports only the ones below it. CogLib (the bottom five) imports no theory.
- The top-level theorem's proof is a few lines because the work is factored into these layers, the way Mathlib factors algebra.


Exact distributions

```
abbrev Dist (α : Type) := List (α × Rat)

/-- The distribution certain of `a`. -/
def pure (a : α) : Dist α := [(a, 1)]

/-- A two-stage process: draw `a` from `d`, then draw from `f a`. -/
def bind (d : Dist α) (f : α → Dist β) : Dist β :=
  match d with
  | [] => []
  | (a, p) :: d => ((f a).map fun (b, q) => (b, p * q)) ++ bind d f

/-- The probability of an event. -/
def prob : Dist α → (α → Bool) → Rat
  | [], _ => 0
  | (a, p) :: d, e => (if e a then p else 0) + prob d e
```


Exact distributions

```
abbrev Dist (α : Type) := List (α × Rat)

/-- The distribution certain of `a`. -/
def pure (a : α) : Dist α := [(a, 1)]

/-- A two-stage process: draw `a` from `d`, then draw from `f a`. -/
def bind (d : Dist α) (f : α → Dist β) : Dist β :=
  match d with
  | [] => []
  | (a, p) :: d => ((f a).map fun (b, q) => (b, p * q)) ++ bind d f

/-- The probability of an event. -/
def prob : Dist α → (α → Bool) → Rat
  | [], _ => 0
  | (a, p) :: d, e => (if e a then p else 0) + prob d e
```

- A distribution is a list of outcomes with exact rational probabilities. No floating point, no measure theory, no Mathlib.
- Outcomes may repeat; an event's probability sums them. That keeps `bind` simple, at the cost of long lists when runs are computed.
- Because everything is computable, the same definitions are run (`#eval`) and proved about.

The two-stage lemma


```
/-- A mixture: the probability of an event after a two-stage process is the
sum, over first-stage outcomes, of each one's probability times the event's
probability after it. -/
theorem prob_bind_sum (d : Dist α) (f : α → Dist β) (e : β → Bool) :
    prob (bind d f) e = (d.map fun ap => ap.2 * prob (f ap.1) e).sum := by
  induction d with
  | nil => simp [bind, prob]
  | cons x d ih => obtain ⟨a, p⟩ := x; rw [prob_bind_cons, ih]; simp
```

Its specializations do most of the work above:

- `prob_bind_pure`: relabelling outcomes relabels the event;
- `prob_bind_split`: a second stage that is certain on one set of outcomes and constant on another.

Inside the proofs

The two-stage lemma



- Induction on the list. The cons case uses `prob_bind_cons` (probability of the first outcome's branch, scaled, plus the rest), then the induction hypothesis.
- Nearly every probabilistic proof in the talk reduces to this lemma or one of its specializations.

Discrimination nets

```
inductive Net where
  | leaf : Option Item → Net
  | test : Feature → Net → Net → Net

/-- Selection: sort a code to a terminal and return its image. -/
def select : Net → Item → Option Item
  | leaf img, _ => img
  | test f n0 n1, x => if x.feat f then n1.select x else n0.select x

/-- The features examined while sorting `x`: the path it takes. -/
def path : Net → Item → List Feature
  | leaf _, _ => []
  | test f n0 n1, x => f :: (if x.feat f then n1.path x else n0.path x)
```

Discrimination nets

```
inductive Net where
  | leaf : Option Item → Net
  | test : Feature → Net → Net → Net

/-- Selection: sort a code to a terminal and return its image. -/
def select : Net → Item → Option Item
  | leaf img, _ => img
  | test f a0 a1, x => if x.feat f then a1.select x else a0.select x

/-- The features examined while sorting `x`: the path it takes. -/
def path : Net → Item → List Feature
  | leaf _, _ => []
  | test f a0 a1, x => f :: (if x.feat f then a1.path x else a0.path x)
```

- EPAM's net, directly: a terminal holds an image or nothing; a test branches on one binary feature.
- Learning (`Net.learn`, not shown) replaces a confused terminal by a test on the first noticed difference.

Lemma A: a confusion agrees on the path

```
theorem confusion_agrees_on_path (N : Net) (x y : Item) (hnd : N.images.Nodup)
    (hy : N.select y = some y) (hx : N.select x = some y) :
    ∀ f ∈ N.path x, x.feat f = y.feat f := by
  induction N with
  | leaf img => simp [path]
  | test f n0 n1 ih0 ih1 =>
    -- ...
    cases hxf : x.feat f <;> cases hyf : y.feat f <;> simp [hxf, hyf] at hx hy hg
    · -- both go to n0: the tested feature agrees, recurse
      rcases hg with rfl | hg
      · rw [hxf, hyf]
      · exact ih0 hnd0 hy hx g hg
    · -- x to n0, y to n1: y would be stored in both subtrees
      exact absurd rfl (hdisj y (select_mem_images n0 x y hx) y (select_mem_images n1 y y
      ↪ hy))
    -- ... (the two symmetric cases)
```

Lemma A: a confusion agrees on the path

```
theorem confusion_agrees_on_path (H : Set) (x y : Item) (hxd : H.images.Nodup)
    (hy : H.select y = some y) (hx : H.select x = some x) :
    ∀ f ∈ H.path x, x.feat f = y.feat f → hy
induction H with
| leaf lag => simp [path]
| test f n1 ih0 ih1 =>
  -- ...
  cases hxf : x.feat f <;> cases hyf : y.feat f <;> simp [hxf, hyf] at hx hy hg
  -- ... (the two cases the tested feature agrees; recurse
    · exact ih0 hx0 hy hg
    · rw [hxf, hyf]
    · exact ih1 hx0 hy hg
  -- x to n0, y to n1: y would be stored in both subtrees
    exact absurd rfl (hxd.ne) y (select_mem_images n0 x y hx) y (select_mem_images n1 y y
      rfl hy))
  -- ... (the two symmetric cases)
```

- Structural induction on the net. At a test, case on the tested feature for x and for y.
- If they go the same way, the feature agrees and the induction hypothesis covers the rest of the path.
- If they go different ways, y would be stored on both sides, contradicting `Nodup` of the images. That hypothesis (each image stored once) is what EPAM's learning guarantees: `learnAll_clean`.
- This lemma is behind every near-miss prediction, and behind EPAM's `AgreesOn` law.

DOA search, and a closed form

```
def search (as : List α) (s : α → Rat) (cc : Rat) : Nat → Nat → Dist (Retrieval α)
  | _, 0 => Dist.pure .exhausted
  | k, n + 1 => Dist.bind (sample as s) fun a =>
      if above s cc a then Dist.pure (.stated a (k + 1)) else search as s cc (k + 1) n

theorem prob_exhausted (as : List α) (s : α → Rat) (cc : Rat) (hT : total as s ≠ 0) :
    ∀ n k, prob (search as s cc k n) Retrieval.isExhausted = (1 - reach as s cc) ^ n := by
  intro n
  induction n with
  | zero => intro k; simp [search, prob_pure, Retrieval.isExhausted]
  | succ n ih =>
    intro k
    simp only [search]
    rw [prob_bind_split _ _ _ (fun _ => false) (fun a => !above s cc a) ((1 - reach as s
    ↪  cc) ^ n)]
    · rw [prob_false, prob_not_above as s cc hT, Rat.pow_succ]; grind
    · intro a
      by_cases ha : above s cc a
      · simp [ha, prob_pure, Retrieval.isExhausted]; grind
      · simp [ha, ih]; grind
```

Inside the proofs

DOA search, and a closed form



- Search is a recursive distribution: sample, state if above criterion, otherwise search again.
- The closed form is proved by induction on the search length, splitting each step with `prob_bind_split`: above criterion ends the search (never exhausted), below it continues (exhausted with probability $(1 - R)^n$ by induction).
- The hypothesis `total` $\neq$ `0` is real: with zero total strength, `sample` divides by zero. The blind simulation found that gap.

The composition


```
def afterRecognition (str : Item → A → Rat) (as : List A) (cc : Rat) (n : Nat)
    (backup : P → Dist A) (x : P) : Option Item → Dist (Route × A)
  | none => Dist.bind (backup x) fun r => Dist.pure (.backup, r)
  | some y => Dist.bind (search as (str y) cc 0 n) fun
      | .stated a _ => Dist.pure (.whole, a)
      | .exhausted => Dist.bind (backup x) fun r => Dist.pure (.backup, r)

/-- Recognize, then retrieve, else back up. -/
def recognizeRetrieve (code : P → Item) (retrieve : Item → Dist (Option Item))
    (str : Item → A → Rat) (as : List A) (cc : Rat) (n : Nat) (backup : P → Dist A) (x
    ↪  : P) :
    Dist (Route × A) :=
  Dist.bind (retrieve (code x)) (RR.afterRecognition str as cc n backup x)
```

Generic in the problem type `P`, the answer type `A`, and the memory (`retrieve`).

Inside the proofs

The composition




- The composition is just `bind`: what memory calls up, then what follows.
- Neither arithmetic nor EPAM appears here. Memory is any function from a probe to a distribution over stored codes.

Confident errors: the proof is a composition

```
theorem confident_errors (correct : P → A) (x q : P) (hT : ∀ y, total as (str y) ≠ 0)
    (hbx : mass (backup x) = 1) (hbq : mass (backup q) = 1)
    (hq : retrieve (code q) = pure (some (code q)))
    (hx : retrieve (code x) = pure (some (code q)))
    (hs : Sharp str cc (code q) (correct q)) (hne : correct x ≠ correct q) :
    prob (recognizeRetrieve code retrieve str as cc n backup q) (wholeWrong correct q) = 0
    ↪ ∧
      prob (recognizeRetrieve code retrieve str as cc n backup x) (wholeWrong correct x) =
        prob (recognizeRetrieve code retrieve str as cc n backup x) isWhole ∧
      prob (recognizeRetrieve code retrieve str as cc n backup x) isBackup =
        prob (recognizeRetrieve code retrieve str as cc n backup q) isBackup := by
  refine ⟨confusion_gives_neighbours_answer code retrieve str as cc n backup correct q q
  ↪ (hT _) hq hs,
    wrong_eq_whole_of_sharp code retrieve str as cc n backup correct x _ _ (hT _) hx hs
    ↪ hne, ?_⟩
  rw [backup_prob_certain code retrieve str as cc n backup x _ hx hbx hT,
    backup_prob_certain code retrieve str as cc n backup q _ hq hbq hT]
```

Confident errors: the proof is a composition



```
theorem confident_errors (correct : P → A) (x q : P) (hT : ∀ y, total_as (str y) ≠ 0)
    (hbs : mass (backup x) = 1) (hbq : mass (backup q) = 1)
    (hq : retrieves (code q) = pure (some (code q)))
    (hx : retrieves (code x) = pure (some (code q)))
    (hne : #{any str cc (code q) (correct q)} (hne : correct x ≠ correct q) :
  prob (recognizeOnRetrieve code retrieve str as cc x backup q) (ValueAbout correct q) = 0 ∧
  prob (recognizeOnRetrieve code retrieve str as cc x backup q) (ValueAbout correct x) =
      prob (recognizeOnRetrieve code retrieve str as cc x backup x) toWhole ∧
    prob (recognizeOnRetrieve code retrieve str as cc x backup x) toBackup =
        prob (recognizeOnRetrieve code retrieve str as cc x backup q) toBackup := by
  refine ⟨confusion_gives_neighbours_answer code retrieve str as cc x backup correct q q
    (by _ hq hx _
      wrong_eq_choice_of_sharp code retrieve str as cc x backup correct x _ _ (hT _) hx hx
        hne _
    by [backup_prob_certain code retrieve str as cc x backup x _ hx hbs hT,
      backup_prob_certain code retrieve str as cc x backup q _ hq hbq hT]
```


- Three conjuncts, three earlier lemmas. The first is the neighbour's-answer lemma applied to q itself; the second says that on sharp associations, every stated answer to x is wrong; the third rewrites both backup probabilities to the same closed form $(1 - R_q)^n$, after which the goal is an identity.
- Note the hypotheses: retrieval is certain (`= pure (some ...)`). That is exactly what ACT-R never satisfies, and what the laws later supply.

One supporting lemma

```
theorem confusion_gives_neighbours_answer (correct : P → A) (x q : P)
    (hT : total as (str (code q)) ≠ 0) (h : retrieve (code x) = pure (some (code q)))
    (hs : Sharp str cc (code q) (correct q)) :
    prob (recognizeRetrieve code retrieve str as cc n backup x)
      (wholeSuch fun a => a != correct q) = 0 := by
  rw [whole_depends_only_on_route code retrieve str as cc n backup x _ _ h,
    prob_stated _ _ _ _ hT]
  have : reachSuch as (str (code q)) cc (fun a => a != correct q) = 0 := by
    simp only [reachSuch]
    rw [prob_congr _ _ (fun _ => false), prob_false]
    intro a
    by_cases ha : above (str (code q)) cc a
    · simp [hs a ha]
    · simp [ha]
  rw [this]; grind
```

Inside the proofs

One supporting lemma


One supporting lemma

```
theorem confusion_gives_neighbours_answer {correct : P → A} (x q : P)
    (hd : 0 < dist (code x) (code q)) (hy : retrieve (code x) = pure (some (code q)))
    (hz : ∃ z, dist (code q) (code z) < dist (code x) (code z)) :
    prob (recognizeRetrieve code retrieve str as cc a backup x)
      (fun a => a ≠ correct q) = 0 := by
  rw [whole_depends_only_on_route code retrieve str as cc a backup x _ _ h,
    prob_stated _ _ _ hy]
  have : reachBuck as (str (code q)) cc (fun a => a ≠ correct q) = 0 := by
    simp only [reachBuck]
    rw [prob_congr _ _ (fun _ => false), prob_false]
    intro a
    by_cases ha : above (str (code q)) cc a
    · simp [ha = ha]
    · simp [ha]
  rw [this]; grind
```

- Step 1: whole-problem retrieval on x is retrieval on q's associations (`whole_depends_only_on_route`, itself from `recognizeRetrieve_certain` and `bind_pure_left`).
- Step 2: DOA's closed form for stating an answer with a property (`prob_stated`): reach-with-property times a geometric factor.
- Step 3: the reach for "an answer other than q's" is zero, because sharpness says only q's answer clears the criterion. Pointwise reasoning, then `prob_false`.

Memory as an interface


```
structure Retriever (State Stim : Type) where
  study : State → Stim → State
  retrieve : State → Stim → Dist (Option Stim)

-- EPAM: what a net's probe calls up, for certain
def Net.retrieve (N : Net) : Item → Dist (Option Item) := fun y => Dist.pure (N.select y)
def netRetriever (order : NoticingOrder) : Retriever Net Item := (netLearner
↪  order).toRetriever

-- ACT-R (decay 1, temperature 1): sample in proportion to weight, failure included
def retrieve (P : ActParams) (s : ActState) (x : Item) : Dist (Option Item) :=
  Dist.sample (outcomes s) (weight P s x)

/-- Retrieval is never certain. Failure is always among the outcomes. -/
theorem retrieve_not_certain (P : ActParams) (s : ActState) (x y : Item) :
    retrieve P s x ≠ Dist.pure (some y) := by
  intro h
  simp [retrieve, Dist.sample, outcomes, Dist.pure] at h
```

Memory as an interface



```
structure Retriever (State Stim : Type) where
  study : State → Stim → State
  retrieve : State → Stim → Dist (Option Stim)

-- EPAM: what a net's probe calls up, for certain
def Net.retrieve (N : Net) : Item → Dist (Option Item) := fun y => Dist.pure (N.select y)
def netRetriever (order : RoticingOrder) : Retriever Net Item := ⟨netLearner
  · order⟩ !isRetriever

-- ACT-R (decay 1, temperature 1): sample in proportion to weight, failure included
def retrieve (P : ActParams) (s : ActState) (i : Item) : Dist (Option Item) :=
  Dist.sample (outcomes s) (weight P s i)

/-- Retrieval is never certain. Failure is always among the outcomes. -/
theorem retrieve_not_certain (P : ActParams) (s : ActState) (x y : Item) :
    retrieve P s x ≠ Dist.pure (some y) := by
  intro h
  simp [retrieve, Dist.sample, outcomes, Dist.pure] at h
```

- ACT-R's weight for a chunk is $\sum_k 1/(t - t_k)$ times $\mu^{\text{mismatches}}$, with a failure weight θ: Boltzmann retrieval with decay 1 and temperature 1, exactly rational.
- `retrieve_not_certain` is a one-line `simp`: the outcome list starts with `none`, so it can never equal `[(some y, 1)]`.

The bridge to multi-digit addition


```
/-- The generic routes, in this model's names. -/
def relabel : Cog.Route × Nat → Route × Nat
  | (.whole, a) => (.whole, a)
  | (.backup, a) => (.columns, a)

theorem prob_trialWith (x : Problem) (e : Route × Nat → Bool) :
    prob (trialWith retrieve E str as cc n backup x) e =
      prob (recognizeRetrieve E.code retrieve str as cc n backup x) (fun o => e (relabel
      ↪  o)) := by
  unfold trialWith recognizeRetrieve
  rw [prob_bind_sum, prob_bind_sum]
  congr 1
  apply List.map_congr_left
  intro rp _
  rw [prob_after]

-- then each multi-digit theorem is two lines:
theorem confident_errors ... := by
  simp only [prob_trialWith, wholeWrong_relabel, isWhole_relabel, isColumns_relabel]
  exact RR.confident_errors E.code retrieve str as cc n backup Problem.sum x q ...
```

Inside the proofs

The bridge to multi-digit addition



- The multi-digit model keeps its own definitions and route names (so its exported numbers are byte-identical). One lemma carries every probability across, by the two-stage lemma on both sides.
- Event identities (`isColumns` after relabelling is `isBackup`, and so on) are `funext` plus `cases`, closed by `rfl`.

Laws

```
def Certainty (R : Retriever S Item) (s0 : S) (U : List Item) : Prop :=
  ∀ s, Reachable R s0 U s → ∀ y ∈ U, pRet R (R.study s y) y y = 1

def Stability (R : Retriever S Item) (s0 : S) (U : List Item) : Prop :=
  ∀ s, Reachable R s0 U s → ∀ y ∈ U, ∀ z ∈ U, z ≠ y → pRet R (R.study s z) y y = pRet R
  ↪  s y y

def Determinate (R : Retriever S Item) (s0 : S) (U : List Item) : Prop :=
  ∀ s, Reachable R s0 U s → ∀ x, ∃ r, R.retrieve s x = Dist.pure r


/-- Under determinacy, a positive chance of retrieving `y` is certainty. -/
theorem retrieve_of_pRet_pos (R : Retriever S Item) (s0 : S) (U : List Item)
    (hd : Determinate R s0 U) (s : S) (hs : Reachable R s0 U s) (x y : Item)
    (h : 0 < pRet R s x y) : R.retrieve s x = Dist.pure (some y)
```

`pRet R s x y`: the chance that probe `x` retrieves `y`. `Reachable`: reached from `s0` by studying items of `U`.

Inside the proofs

Laws

- Laws are `Prop`-valued definitions over the interface: no mechanism appears.
- Each matrix cell is a theorem that a family's retriever has a law, or its negation.




Studied items retrieve themselves

```
theorem studied_selfRetrieval (R : Retriever S Item) (s0 : S) (U : List Item)
    (hc : Certainty R s0 U) (hs : Stability R s0 U) (xs : List Item)
    (hU : ∀ x ∈ xs, x ∈ U) (hnd : xs.Nodup) (y : Item) (hy : y ∈ xs) :
    pRet R (R.studyAll s0 xs) y y = 1 := by
  obtain ⟨pre, post, hsplit⟩ := List.append_of_mem hy    -- xs = pre ++ y :: post
  -- ... y ∉ post, from Nodup
  rw [hsplit, show pre ++ y :: post = (pre ++ [y]) ++ post by simp,
    stable_after R s0 U hs y hyU post (pre ++ [y]) _ hpost,   -- studying post changes
    ↪  nothing
    studyAll_append]
  exact hc _ ⟨pre, hpre, rfl⟩ y hyU                          -- certainty, just after y
```

`stable_after` is an induction on `post`, applying stability once per item.

Inside the proofs

Studied items retrieve themselves



```
theorem studied_selfRetrieval (R : Retriever S Item) (st : S) (y : List Item)
    (hs : Certainty R st 0) (ha : Stability R st 0) (xs : List Item)
    (h0 : ∀ x ∈ xs, x ∈ 0) (hnd : xs.Nodup) (p : Item) (hy : y ∈ xs) :
    pNet R (b.study[b1 st xs] y) y = 1 := by
  obtain ⟨pre, post, hsplit⟩ : ∃ l₁ l₂, List.append_of_mem hy    -- xs = pre ++ y :: post
  -- ... y ∉ post, from Nodup
  rw [hsplit, show pre ++ y :: post = (pre ++ [y]) ++ post by simp,
    stable_after R st 0 ha p hy0 post (pre ++ [y]) _ hpost,   -- studying post changes
      nothing
    ← hsplit, append]
  exact hs _ (pre, hpre, rfl) y hy0                          -- certainty, just after y
```

`stable_after` is an induction on post, applying stability once per item.

- Split the study list at y. Certainty gives probability 1 just after y is studied; stability, applied item by item to everything studied later (none of which is y, by `Nodup`), keeps it at 1.
- This is also the whole content of the flat serial-position curve in the study-test experiment.

Confident errors from laws

```
theorem confident_errors_of_laws (R : Retriever S Item) (s0 : S) (U : List Item)
    (hdet : Determinate R s0 U) (hcert : Certainty R s0 U) (hstab : Stability R s0 U)
    (xs : List Item) (hxs : ∀ y ∈ xs, y ∈ U) (hnd : xs.Nodup)
    (correct : P → A) (x q : P) (hq : code q ∈ xs)
    (hconf : 0 < pRet R (R.studyAll s0 xs) (code x) (code q))
    -- ... totals, backups, sharpness, correct x ≠ correct q
    := by
  have hr : Reachable R s0 U (R.studyAll s0 xs) := ⟨xs, hxs, rfl⟩
  have hq' := retrieve_of_pRet_one R s0 U hdet _ hr (code q) (code q)
    (studied_selfRetrieval R s0 U hcert hstab xs hxs hnd (code q) hq)
  have hx' := retrieve_of_pRet_pos R s0 U hdet _ hr (code x) (code q) hconf
  exact confident_errors code _ str as cc n backup correct x q hT hbx hbq hq' hx' hs hne
```

Laws supply the two certain-retrieval hypotheses; the composition theorem does the rest.

Inside the proofs

Confident errors from laws

Confident errors from laws

```
theorem confident_errors_of_laws (R : Retriever S Item) (inf : S) (I : List Item)
    (hdet : Deterministic R inf I) (hcert : Certainty R inf I) (hstab : Stability R inf I)
    (xs : List Item) (hxs : ∀ y ∈ xs, y ∈ I) (hsub : xs.Nodup)
    (incorrect : P → A) (q : P) (hq : code q ∉ xs)
    (hcond : ∃ r, ghat R (R.study@[] inf xs) (code x) (code q))
    -- ... totals, backups, sharpness, correct x ≠ correct q
    := by
  have hsr : Reachable R inf (R.study@[] inf xs) := ⟨xs, hxs, rfl⟩
  have hq' := retrieve_of_ghat_pos R inf I hdet _ hsr (code q) (code q)
    (studied_selfRetrieval R inf I hcert hstab xs hxs hsd (code q) hq)
  have hx' := retrieve_of_ghat_pos R inf I hdet _ hsr (code x) (code q) hcondf
  exact confident_errors code _ etc ac cc n backup correct x q hI hhx hbq hq' hx' hs hne
```

Laws supply the two certain-retrieval hypotheses; the composition theorem does the rest.


- This is where the matrix and the composition meet: `hq'` and `hx'` were per-state assumptions; now they are consequences of three laws and one observable fact (the stranger can be taken for q).
- Only the discrimination family has all three laws.

Using it: confident misnaming

```
theorem epam_confident_misnaming_of_laws (n : Nat) : ... :=
  RR.confident_errors_of_laws Person.face str names (1 / 2) n backup (netRetriever F3)
  ↪  (Net.leaf none)
    U3 (Discrimination.determinate F3 U3) (Discrimination.certainty F3 U3 noticeable_U3)
    (Discrimination.stability F3 U3) [ann.face, bob.face] (by decide) (by decide)
    ↪  Person.name carl bob
    (by decide) (by decide +kernel) total_ne (mass_backup carl) (mass_backup bob)
    ↪  sharp_bob
    (by decide)
```

- Three matrix cells for EPAM, cited by name.
- One computed fact, closed by `decide +kernel`: Carl's face can be taken for Bob's.
- No proof script: the theorem is a term, an application of the general result.

Using it: confident misnaming



```
theorem epam_confident_misnaming_of_lain (a : Rat) : ... :=
  EM.confident_errors_of_last Person.face str names (1 / 2) a backup (setOfCriterion P3)
    -- Context hypotheses
    (Discrimination.deterministic P3 U3) (Discrimination.certainty P3 U3 noticeable_U3)
    (Discrimination.stability P3 U3) [mms.face, kob.face] (by decide) (by decide)
    -- Person.name carl bob
    (by decide) (by decide <kernel>) total_ne (mms_backup carl) (mms_backup bob)
    -- sharp_bob
    (by decide)
```

- Three matrix cells for EPAM, cited by name.
- One computed fact, closed by `decide <kernel>`: Carl's face can be taken for Bob's.
- No proof script: the theorem is a term, an application of the general result.


- The instance proof is a single application. The `by decide` side conditions are finite checks (list membership, no repeats, names differ).

Computing inside the proof checker

```
theorem example_values :
    prob (trial bcd net str answers (1 / 2) 1 backup x) (wholeSuch (· == 200)) = 45 / 46 ∧
      prob (trial bcd net str answers (1 / 2) 1 backup x) (fun o => o.2 == 250) = 1 / 46
      ↪  := by
  decide +kernel
```

- `decide +kernel`: the kernel evaluates the definitions and checks the equation. Plain `decide` gets stuck on `Rat`.
- The same definitions run under `#eval`: the exported exact distributions that the blind simulation was checked against.
- Counterexample cells (“lacks”) are proved this way, on the eight 3-bit codes.

- Kernel evaluation is slow but trusted: no compiler or external solver is in the trusted base.
- Because `Dist` doesn't merge duplicate outcomes, long computations grow; the exporter merges them, and needs a large stack.




What is checked, and what is not

```
#print axioms Cog.RR.confident_errors_of_laws
'Cog.RR.confident_errors_of_laws' depends on axioms: [propext, Classical.choice,
↪  Quot.sound]
```

- No `sorry` anywhere; only Lean's three standard axioms.
- Core Lean only: no Mathlib, so everything computes.
- **Not checked**: that the definitions say what EPAM, DOA or ACT-R say. That is what the prose specification, the blind simulation, and (planned) comparison with PyACTUp are for.

Inside the proofs

What is checked, and what is not



- The three axioms are those every Lean development uses: propositional extensionality, choice, and quotient soundness.
- Code: `CogLib/CogLib/Rep/Distribution.lean`, `Memory/DiscriminationNet.lean`, `Process/SampledRetrieval.lean`, `Process/RecognizeRetrieve.lean`, `Phenomena/RetrievalLaws.lean`; `MultiDigit/MultiDigit/AnyMemory.lean`; `Experiments/Experiments/FaceNaming.lean`.