# Concept Formation by View Application

## A second domain on shared foundations in CogLean

Jeff Shrager

November 2026

**Draft for Comment**

# Concept Formation by View Application





This talk goes with a paper of the same name, which is a draft for comment and hasn't been carefully checked: think of it as an over-starched blog post, and constructive feedback is welcome. It follows the CogLean paper, which introduced the library and the method using multi-digit arithmetic. This one is not an introduction to CogLean. It asks whether the library carries over to a completely different area of cognition, concept formation, and what it brings with it when it does.

# The question

- CogLean is designed as a general, Mathlib-like library of cognitive processes: build *any* model on it, with proofs *and* executability.
- The CogLean paper's first worked example: **multi-digit arithmetic**.
- One example can't show the design worked. **The test:** a second model, in a very different domain.

*Take CogLean to concept formation: how people understand something new by applying concepts they already have.*




Here's the question. CogLean is designed as a general library, on the model of Mathlib: reusable cognitive representations, mechanisms and processes, on which you can build any model, with its consequences both proved and executable. The first paper introduced it, and multi-digit arithmetic was just the first example worked out in it. But one example can't show that the design worked. The test is a second model in a very different domain, built from the same parts. So we built one for concept formation: how people make sense of something new by applying concepts they already have.

# Forming concepts from old ones

- Concepts live inside theories (Murphy & Medin 1985); they change by restructuring (Carey 1985; Rumelhart & Norman 1976).
- Analogy maps a known structure onto a new one (Gentner 1983); frames supply defaults (Minsky 1975).
- Learners build mental models of devices (Kieras & Bovair 1984).
- **View application** (Shrager 1987): a learner exploring a device with no instructions (Shrager & Klahr 1986) revises its theory by merging in a *view*, a schema of a familiar kind of thing.

Left open in 1987: **which** view is brought in, and **when** the theory is revised.

# Concept Formation by View Application

## Forming concepts from old ones

Forming concepts from old ones

- Concepts live inside theories (Murphy & Medin 1985); they change by restructuring (Carey 1985; Rumelhart & Norman 1976).
- Analogy maps a known structure onto a new one (Gentner 1983); frames supply defaults (Minsky 1975).
- Learners build mental models of devices (Kieras & Bovair 1984).
- **View application** (Shrager 1987): a learner exploring a device with no instructions (Shrager & Klahr 1986) revises its theory by merging in a view, a schema of a familiar kind of thing.

Left open in 1987: **which** view is brought in, and **when** the theory is revised.

Concept formation has been described in many ways. Concepts are embedded in theories that make them coherent. Children's concepts change by restructuring, not just by adding facts. Analogy maps the structure of something known onto something new, and frames supply defaults. People learning a device build a mental model of it. View application, from my 1987 paper, is a computational version of part of this. A learner exploring a device with no instructions has a theory of it, and changes that theory by applying a view: a schema of a familiar kind of thing, like a device that stores a program and runs it. The view is merged into the theory, overriding it where they conflict. That account left two things open: which view a learner brings in, and when the theory gets revised. Both, it turns out, were already in the library.

# View application in CogLib


Theories and views are **knowledge nets**: semantic nets over terms, the same representation as CogLib's concepts and semantic memory.

1. copy the view; 2. merge the theory in (match types; at random where ambiguous);
3. coerce re-parented instances; 4. bind holes; 5. one function per object.

Proved for any view and theory:

- the view is kept; **the view wins** on matched frames (non-monotonic change);
- unmatched theory frames survive; instances of matched types are re-parented.

Already in the library: BigTrak's Table 4 reproduced exactly (probability $1/2$).




In CogLib, theories and views are knowledge nets: semantic nets whose nodes are terms, with frames, slots and patterns. It's the same representation the library uses for concepts and semantic memory, so view application doesn't bring a representation of its own. The process has the 1987 paper's five steps: copy the view, merge the theory into it, coerce re-parented instances, bind holes, and give each object a single function. Ambiguity is resolved at random, so applying a view gives a distribution over theories. For any view and theory, we prove the view is kept, that where both speak, the view wins, which is a non-monotonic change, that unmatched parts of the theory survive, and that instances get re-parented. And the library already reproduces the 1987 paper's BigTrak example exactly, half the time, which is what its random tie-breaking implies.

# A concept result already there: number concepts

- Prototype concepts (*even*, *multiple of 3*) combined by selective modification (Smith et al. 1988), graded membership (Hampton 2007): 14 is an *even multiple of 3* to degree $\approx .80$. Over-extension.
- Apply an **ARITHMETIC view**:
  - *even multiple of 3* becomes exactly divisibility by 6, for every number;
  - no over-extension anywhere; **typicality unchanged**, for every number.
- So typicality and membership **dissociate**, as Armstrong, Gleitman & Gleitman (1983) found for *odd number*; impossible before the view.

A concept result already there: number concepts
- Prototype concepts (*even*, *multiple of 3*) combined by selective modification (Smith et al. 1988), graded membership (Hampton 2007): 14 is an *even multiple of 3* to degree ≈ .80. Over-extension.
- Apply an **ARITHMETIC view**:
  - *even multiple of 3* becomes exactly divisibility by 6, for every number;
  - no over-extension anywhere; **typicality unchanged**, for every number.
- So typicality and membership **dissociate**, as Armstrong, Gleitman & Gleitman (1983) found for *odd number*; impossible before the view.

There's already a concept-formation result in the library. Number concepts like even and multiple of three, learned as prototypes and combined by selective modification with graded membership, over-extend: fourteen counts as an even multiple of three to degree about point eight. Apply an arithmetic view, which replaces how the concept frame categorizes, and even multiple of three becomes exactly divisibility by six, for every number. Over-extension disappears everywhere, but typicality is unchanged, for every number. So typicality and membership come apart, which is what Armstrong and the Gleitmans found for odd number: graded typicality in a concept with all-or-none membership. Before the view that's provably impossible. A change of theory, not of examples, turned a prototype concept into a definitional one.

# Which view? Retrieval through the shared memory

- Already: **spreading activation** (Collins & Loftus 1975). The same "+" key: *adds* with probability 2/3 for a naive learner; *appends a step* with 3/5 for one whose theory has a memory.
- New: **retrieval**. A cue (a key's label, the display) is coded and recognized by a memory, through CogLib's `Retriever` interface, the one the arithmetic model used. The stored view is applied.

For any memory:

- a cue confused with another brings in the other's view;
- a memory with the law of **determinacy** brings in one view per cue, at every attempt.

EPAM's net has determinacy at every setting; ACT-R's memory at none (the memory matrix).

Which view? Retrieval through the shared memory

- Already: **spreading activation** (Collins & Loftus 1975). The same "+" key: *adds* with probability 2/3 for a naive learner; *appends a step* with 3/5 for one whose theory has a memory.
- New: **retrieval**. A cue (a key's label, the display) is coded and recognized by a memory, through CogLib's `Retriever` interface, the one the arithmetic model used. The stored view is applied.

For any memory:

- a cue confused with another brings in the other's view;
- a memory with the law of **determinacy** brings in one view per cue, at every attempt.

EPAM's net has determinacy at every setting; ACT-R's memory at none (the memory matrix).

So, which view? The library already had one selector: spreading activation, where the same plus key is read as adding by a naive learner but as appending a program step by a learner whose theory already includes a memory. The new selector is retrieval. A cue, like a key's label or the display, is coded and recognized by a memory through the same retriever interface the arithmetic model used to recognize problems. Whatever's called up has a view stored with it, and that view is applied. Because it's the same interface, what we proved about memories applies. A cue confused with another brings in the other's view. And a memory with the law of determinacy brings in one view per cue, the same every time. The memory matrix from the first paper proves EPAM's net has that law at every setting and ACT-R's memory has it at none.

# When to revise? The decision cycle, again

| Learning by revision | Decision cycle (as in the arithmetic solver) |
|---|---|
| theory, memory, episodes to explain | the state |
| accept the prediction | `confirm`: precondition, it's right |
| **a failed prediction** | **an impasse** |
| **revise, prompted by a cue** | **a repair** |
| which cues to consult | repair heuristics |
| don't consult a cue twice per failure | a critic |

Not a new control structure: the decision cycle that ran the arithmetic backup.

When to revise? The decision cycle, again

| Learning by revision | Decision cycle (as in the arithmetic solver) |
|---|---|
| theory, memory, episodes to explain | the state |
| accept the prediction | confirm: precondition, it's right |
| **a failed prediction** | **an impasse** |
| **revise, prompted by a cue** | **a repair** |
| which cues to consult | repair heuristics |
| don't consult a cue twice per failure | a critic |

Not a new control structure: the decision cycle that ran the arithmetic backup.

And when to revise? The arithmetic model's backup was a problem solver running on CogLib's decision cycle, with impasses and repairs, in the tradition of repair theory and Soar. Revising a theory when a prediction fails has exactly that shape. The state is the theory, the memory and the episodes still to explain. Confirming a prediction is an operator whose precondition is that the prediction is right. A failed prediction is an impasse. Revising the theory, prompted by some cue, is the repair. Which cues to consult are the repair heuristics, and not consulting the same cue twice for one failure is a critic. So the learning loop is not a new control structure. It's the same decision cycle.


# In words: the next slide

The loop asks a learner for only three things:

- how a theory **predicts** the response to a sequence of actions;
- how a cue **revises** a theory: any process, any memory, a distribution of results;
- which **cues** an episode offers.

No knowledge nets, no views, no devices. Proved for every such learner:

- an impasse is exactly a failed prediction;
- a theory that predicts every episode is never revised.





The next slide shows the Lean definition, so here it is in words. The loop asks a learner for only three things: how a theory predicts the response to a sequence of actions, how a cue revises a theory, which can be any process with any memory and gives a distribution over results, and which cues an episode offers. There's nothing about knowledge nets, views or devices at this level. And for every such learner we prove two things: being at an impasse is exactly having a failed prediction, and a theory that predicts every episode is never revised, whatever the revision process is.

# The learner, in Lean

```
structure Reviser (Θ M Act Resp C B : Type) where
  predicts : Θ → List Act → Option Resp
  revise   : C → Θ → M → Dist (Θ × M × B)
  cues     : List Act × Resp → List C
  once     : Bool
```

- `CogLib/Process/TheoryRevision`: the loop, for any `Reviser`.
- `CogLib/Process/ViewRevision`: view application is *one* reviser.
- Others (rule induction; hypothesis-space search, Klahr & Dunbar 1988) can plug in and inherit the loop's theorems.




Here's the definition. A reviser has a theory type, a memory type, actions, responses, cues, and whatever a revision brings in. It supplies predicts, revise, cues, and a flag for whether a cue may be consulted twice. The loop is defined for any reviser. View application is one of them, in its own module. Others could be added, rule induction, say, or search in a hypothesis space guided by experiments, and they'd inherit the loop's theorems without reproving them.

# A phenomenon that transfers


The CogLean paper's **confusion-error pattern**, stated for arithmetic, apart from any mechanism:

- the familiar $q$ is never answered wrongly by retrieval;
- every retrieved answer to the confused $x$ is wrong;
- $x$ falls back exactly as often as $q$.

For view retrieval (answer = the revised theory's prediction; fallback = exploration), the **same predicate holds**, given:

- both cues call up the same stored view, for certain;
- that view predicts $q$ correctly and $x$ wrongly.

**Confident misinterpretation.** A different mechanism; the phenomenon carried over unchanged.




Now the phenomena. The first paper defined the confusion-error pattern for arithmetic, as a predicate that names no mechanism: the familiar problem is never answered wrongly by retrieval, every retrieved answer to the confused one is wrong, and the confused one falls back exactly as often as the familiar one. For view retrieval, read the answer as the revised theory's prediction, and the fallback as exploring. Then the same predicate holds, given that both cues call up the same view for certain and that view predicts one correctly and the other wrongly. That's confident misinterpretation. The mechanism is different: there's no associative search with a criterion here. We deliberately didn't force view retrieval into the arithmetic mechanism. What transfers is the phenomenon, and that's exactly what stating phenomena apart from mechanisms is for.

# New phenomena: garden paths and perseveration

- **Garden path**: the first interpretation adopted is later replaced.
- **Perseveration**: the same interpretation adopted at two successive failures.

Both stated over the sequence of interpretations, naming no mechanism.

**Perseveration, for a class of memories.** For *every* memory with determinacy (unchanged by revising): revisions by a given cue bring in one and the same retrieval, every time, from every theory.

- A learner who keeps consulting that cue keeps re-applying a failed interpretation: a relative of *Einstellung* (Luchins 1942).
- ACT-R's memory lacks the law and can escape.
- Sufficient, not necessary; and not a claim that people's memories have the law.

New phenomena: garden paths and perseveration

- **Garden path**: the first interpretation adopted is later replaced.
- **Perseveration**: the same interpretation adopted at two successive failures.

Both stated over the sequence of interpretations, naming no mechanism.

**Perseveration, for a class of memories.** For *every* memory with determinacy (unchanged by revising): revisions by a given cue bring in one and the same retrieval, every time, from every theory.

- A learner who keeps consulting that cue keeps re-applying a failed interpretation: a relative of *Einstellung* (Luchins 1942).
- ACT-R's memory lacks the law and can escape.
- Sufficient, not necessary; and not a claim that people's memories have the law.

There are two new phenomena, both defined over the sequence of interpretations a learner brings in. A garden path: the first interpretation is later replaced. Perseveration: the same interpretation is adopted at two failures in a row. Then a class-level result. For every memory with the law of determinacy, provided revising doesn't change it, revisions by a given cue always bring in the same thing. So a learner who keeps consulting that cue keeps re-applying an interpretation that already failed. That's a formal relative of Einstellung, and the persistence comes from a property of memory, not of the device or the view. ACT-R's memory lacks the law and can escape. As always: the law is sufficient, not shown necessary, and nothing here says people's memories have it.

# Views from parts

- SET-A-TIME bundles two ideas. Decomposed:
  - **SET-A-NUMBER**: the key enters a number;
  - **NUMBER-IS-A-TIME** / **NUMBER-IS-A-DURATION**: what the number means.
- Each mentions one slot of the key's type. View application's merge lets a view win only on what it mentions, so a later view **keeps** what an earlier one said about other slots.
- In the microwave: one part predicts nothing; two compose, in either order.
- A revision can replace the meaning and **keep** "enters a number": tuning, not restructuring.

(Commutation of views on disjoint slots: certified in instances; open in general.)

Views from parts

- SET-A-TIME bundles two ideas. Decomposed:
  - **SET-A-NUMBER**: the key enters a number;
  - **NUMBER-IS-A-TIME** / **NUMBER-IS-A-DURATION**: what the number means.
- Each mentions one slot of the key's type. View application's merge lets a view win only on what it mentions, so a later view **keeps** what an earlier one said about other slots.
- In the microwave: one part predicts nothing; two compose, in either order.
- A revision can replace the meaning and **keep** "enters a number": tuning, not restructuring.

(Commutation of views on disjoint slots: certified in instances; open in general.)

A view like set-a-time actually bundles two ideas: that the key enters a number, and that the number is a time of day. So we split views into parts: set-a-number, and number-is-a-time or number-is-a-duration. Each one mentions one slot of the key's type. View application's merge lets a view win only on the slots it mentions, so a later view keeps what an earlier one said about other slots; that's proved in general. In the microwave, no single part predicts anything, and any two of the right kind do, in either order. And a revision can now replace just the meaning and keep the fact that the key enters a number: tuning, rather than restructuring. That views on separate slots always commute is open in general; the instances are certified.

# Why concepts must split

- Views act on **types**: every instance of a type changes together.
- Proved: actions of one type are **read alike**.
- So, for *every* theory in which TIME COOK and CLOCK share a type and both enter a number:
  9 0 START is predicted alike after either, and **no such theory predicts both** "cooks 90 s" and "invalid time".

No view, and no amount of revising, fixes this. The concept has to **differentiate**.


Why concepts must split

- Views act on **types**: every instance of a type changes together.
- Proved: actions of one type are **read alike**.
- So, for every theory in which TIME COOK and CLOCK share a type and both enter a number:
  0 0 START is predicted alike after either, and **no such theory predicts both** "cooks 90 s" and "invalid time".


No view, and no amount of revising, fixes this. The concept has to **differentiate**.

Now the important part. Views act on types: every instance of a type changes together. We prove that two actions of one type are read alike. In the microwave that becomes an impossibility theorem for every theory: if TIME COOK and CLOCK share a type and both enter a number, then nine zero START is predicted the same after either, so no such theory can predict both cooking for ninety seconds and an invalid clock time. No choice of view, no amount of revision, fixes that. The concept has to split. Accounts of conceptual change call that differentiation.

# A split, step by step




- (a) CLOCK fails; re-interpreting the shared type would break TIME COOK.
- (b) Copy the type for CLOCK: **nothing predicts differently yet**.
- (c) Aim NUMBER-IS-A-TIME at the copy: CLOCK changes, TIME COOK doesn't.
- A split isn't free (one more type to keep track of), so the learner splits only when forced.





Here's a split, step by step. In panel a, after the first episode, both keys are instances of one type, which enters a number and says the number is a duration. CLOCK's episode fails: the theory predicts cooking, and the device says invalid time. Re-interpreting the shared type as a time would fix CLOCK and break TIME COOK, which the learner already explained. So in panel b the learner copies the type for CLOCK. The copy has the same slots, so nothing predicts differently yet: that's the conservativeness theorem. In panel c, number-is-a-time is aimed at the copy alone, and now each key has its own type and both are right. Two details. A view names the type it re-interprets, so to aim it at the copy we rename the view's frame; and view application now reserves a view frame for the theory frame of the same name, which was needed for that, and changed none of the earlier results. And a split isn't free: the theory gains a type to keep track of. That's why the learner splits only when forced, when re-interpreting the shared type would undo an explanation.

# Differentiation: split, then re-interpret

- **Split** copies an action's type and moves the action to the copy. Proved:
  - a split **changes no prediction** (it's conservative);
  - it **separates** the action from its old type's other instances.
- **When**: if re-interpreting the failing key's type would break an explained episode, split first.

Episodes: TIME COOK, CLOCK, TIME COOK (EPAM; 12 cycles).

| Learner | knows both | finishes | oscillates |
|---|---|---|---|
| cannot split | 0 | 5/6 | 5/6 |
| splits on conflict | 5/6 | 5/6 | 0 |




So we add splitting. A split copies an action's type and moves the action to the copy. Two general results: the split by itself changes no prediction, so differentiation is conservative; it changes what the learner can come to believe, not what it believes. And it separates the action from the other instances of its old type. The learner splits when re-interpreting the failing key's type would break an episode it has already explained. With the episodes TIME COOK, CLOCK, TIME COOK again: a learner that can't split never ends up knowing both, as the theorem says, and every one that finishes oscillates, the clock meaning pushing out the cooking meaning and back. A learner that splits on conflict knows both whenever it finishes, and never oscillates. This is about representation, not memory, so these sessions use EPAM only.

# What was shared, and what was new

| CogLib component | Arithmetic | Concepts |
|---|---|---|
| Exact distributions; `bind` | yes | yes |
| Retriever interface; EPAM; ACT-R | yes | yes |
| Laws of memory | yes | yes |
| `ConfusionErrorPattern` | yes | yes |
| Decision cycle, impasses, repairs | solver | revision loop |
| Knowledge nets; view application | — | yes |
| *New, general:* theory execution, view retrieval, the revision loop, view composition, type splitting; garden paths, perseveration, oscillation | — | new |

Reused by *citing proofs*, not by imitation. The device is data in its own package.

What was shared, and what was new

| CogLib component | Arithmetic | Concepts |
|---|---|---|
| Exact distributions; `bind` | yes | yes |
| Retriever interface; EPAM; ACT-R | yes | yes |
| Laws of memory | yes | yes |
| `ConfusionErrorPattern` | yes | yes |
| Decision cycle, impasses, repairs | solver | revision loop |
| Knowledge nets; view application | — | yes |
| *New, general:* theory execution, view retrieval, the revision loop, view composition, type splitting; garden paths, perseveration, oscillation | — | new |

Reused by *citing proofs*, not by imitation. The device is data in its own package.

Here's the accounting. Exact distributions, the retriever interface with EPAM and ACT-R, the laws of memory, the confusion-error pattern and the decision cycle were all used in arithmetic and all used again here. Knowledge nets and view application come from the library's concept work. And what's new, theory execution, view retrieval, the revision loop and the two phenomena, went into CogLib in general form, with nothing about devices in it. Two points. The shared parts were reused by citing their proofs, not by writing look-alikes. And the microwave you're about to see is just data in its own package.

# A worked case: learning a microwave

- Keys TIME COOK, CLOCK, 9, 0, START. After TIME COOK, 9 0 START cooks 90 seconds; after CLOCK, 90 is an invalid time.
- The learner understands digits and START; TIME COOK and CLOCK: unknown. It's at an impasse at once.
- Views: **SET-A-TIME**, **DURATION**. Prior knowledge: a VCR's SET TIME (with SET-A-TIME), a kitchen timer (with DURATION).
- EPAM's net notices the countdown first: **both labels call up the VCR**. ACT-R: graded.

| | EPAM | ACT-R |
|---|---|---|
| label + display | garden path when the label comes first; always solved | garden paths rarer; usually solved |
| label only | **certain perseveration**; never solved | escapes; usually solved |

A worked case: learning a microwave

- Keys TIME COOK, CLOCK, 9, 0, START. After TIME COOK, 9 0 START cooks 90 seconds; after CLOCK, 90 is an invalid time.
- The learner understands digits and START; TIME COOK and CLOCK: unknown. It's at an impasse at once.
- Views: **SET-A-TIME**, **DURATION**. Prior knowledge: a VCR's SET TIME (with SET-A-TIME); a kitchen timer (with DURATION).
- EPAM's net notices the countdown first: **both labels call up the VCR**. ACT-R: graded.

| | EPAM | ACT-R |
|---|---|---|
| label + display | garden path when the label comes first; always solved | garden paths rarer; usually solved |
| label only | **certain perseveration**; never solved | escapes; usually solved |

The worked case is a generic microwave. After TIME COOK, nine zero START cooks for ninety seconds; after CLOCK, ninety is an invalid time. The learner understands the digits and START but not TIME COOK or CLOCK, so its first prediction fails. There are two views, set-a-time and duration, and the learner's prior knowledge is a VCR's SET TIME key and a kitchen timer. EPAM's net happens to notice the countdown first, so both key labels call up the VCR. ACT-R retrieves gradedly. With the label and the display as cues, EPAM goes down a garden path whenever it looks at the label first, set-a-time, fails, then duration, and always ends up right. With the label only, EPAM perseverates for certain, exactly as the class-level theorem says, and never gets it. ACT-R's graded retrieval usually escapes. Exact values are in the paper's appendix; they're witnesses, not predictions about people.

# What it says about concept formation

- **Which prior concept is recruited is a memory question.** Properties of memory become predictions: determinacy $\Rightarrow$ perseveration; confusion $\Rightarrow$ confident misinterpretation.
- **When to revise is problem solving**: the impasse structure, connecting theory change to repair theory and Soar.
- **Concepts must sometimes split.** Views act on types, so shared types can't be told apart (proved). Differentiation is necessary, and conservative: the split changes nothing, later re-interpretation does (Carey; Thagard).

What it says about concept formation

- **Which prior concept is recruited is a memory question.** Properties of memory become predictions: determinacy ⇒ perseveration; confusion ⇒ confident misinterpretation.
- **When to revise is problem solving**: the impasse structure, connecting theory change to repair theory and Soar.
- **Concepts must sometimes split.** Views act on types, so shared types can't be told apart (proved): Differentiation is necessary, and conservative: the split changes nothing, later re-interpretation does (Carey; Thagard).

What does formalizing this say about concept formation? Three things. First, which prior concept gets recruited is a memory question, so properties of memory turn into predictions about concept formation: determinacy gives perseveration, confusion gives confident misinterpretation. Second, when to revise isn't a separate learning mechanism; it's the impasse structure of problem solving. Third, because views act on types, concepts sometimes have to split: no theory with a shared type can tell its instances apart. Differentiation is then necessary, and it's conservative: the split itself changes nothing; it's the later re-interpretation that separates the concepts. And conflict-driven splitting is the difference between oscillating forever and settling on both.

# Limitations, and next

**Limitations**

- Memory doesn't learn during revision.
- Splitting is conflict-driven, not weighed against overwriting.
- View commutation proved only in instances.
- An illustrative device; no data.
- ACT-R without retrieval as use.
- Parts of the 1987 learner not formalized.

**Next**

- Learning which views succeed for which cues.
- Choosing between splitting and overwriting.
- A second reviser on the same loop.
- Contact with data: instructionless-learning protocols (Shrager & Klahr 1986).

Limitations, and next

**Limitations**
- Memory doesn't learn during revision.
- Splitting is conflict-driven, not weighed against overwriting.
- View commutation proved only in instances.
- An illustrative device; no data.
- ACT-R without retrieval as use.
- Parts of the 1987 learner not formalized.

**Next**
- Learning which views succeed for which cues.
- Choosing between splitting and overwriting.
- A second reviser on the same loop.
- Contact with data: instructionless-learning protocols (Shrager & Klahr 1986).

The limitations are real. Memory doesn't learn while the theory is being revised, so a cue never comes to retrieve a better view. Splitting is driven by conflict and isn't weighed against overwriting, and the commutation of views is certified only in instances. The device and the prior knowledge are illustrative, and there's no data. ACT-R appears without retrieval changing memory, as in the first paper. And several mechanisms of the 1987 learner aren't formalized. Next: learning which views succeed for which cues; a learner that chooses between splitting and overwriting; a second, different reviser on the same loop, to see the loop's results transfer between revision processes the way the confusion pattern transferred between domains; and contact with data, starting with the instructionless-learning protocols.

# Take-home

- CogLean: a general library; arithmetic was only its first example. For concept formation, it supplied:
  - the memory interface and its laws;
  - a phenomenon first stated in the arithmetic example;
  - the decision cycle.
- The new parts went into the library in general form: view retrieval, the revision loop, view composition, type splitting.
- Differentiation: necessary when types are shared (proved), conservative, and what ends oscillation.
- Results at every level: for every learner; for every memory with a law; at a setting, as witnesses.
- Complementary to architectures (Soar, ACT-R, the Common Model): it accumulates proved results about mechanisms, across architectural commitments.

*That's what a cumulative library should do.*

Take-home
- CogLean: a general library; arithmetic was only its first example. For concept formation, it supplied:
  - the memory interface and its laws;
  - a phenomenon first stated in the arithmetic example;
  - the decision cycle.
- The new parts went into the library in general form: view retrieval, the revision loop, view composition, type splitting.
- Differentiation: necessary when types are shared (proved), conservative, and what ends oscillation.
- Results at every level: for every learner; for every memory with a law; at a setting, as witnesses.
- Complementary to architectures (Soar, ACT-R, the Common Model): it accumulates proved results about mechanisms, across architectural commitments.

*That's what a cumulative library should do.*

To sum up. CogLean is designed as a general library of cognitive processes; arithmetic was only the first example built on it. Building a model in a very different domain, concept formation, the library supplied the memory interface and its laws, a phenomenon first written down for arithmetic, and the decision cycle. What had to be added went into the library in general form, ready for the next domain. And the results came out at the levels the first paper laid out: for every learner, for every memory with a law, and at a particular setting, as a witness. None of this competes with cognitive architectures. Soar, ACT-R and the Common Model have long made theory cumulative by giving models shared mechanisms, and a view-application learner could be built in either. What CogLean adds is accumulated proved results: the decision cycle's theorems carried over to theory revision without being re-established, and perseveration proved for every memory with the law of determinacy, which covers EPAM's net and not ACT-R's memory. The law is sufficient, not shown necessary, and nothing here says architectures are equivalent or diverge in general. The library is still small. But that's the behavior a cumulative library should show.