Semantic Governance Guide v2.4 — Amendment Set (Draft): Glossaries and Acronyms

Nov 6, 2026 · @jeffrey

Document control and how to read this set

This set proposes version 2.4 of the Semantic Governance Standards Guide as twelve amendments (A13 to A24) that bring glossaries and acronyms under the same governance as vocabularies, taxonomies, ontologies, lexicons and mappings. It amends the v2.2 Draft of November 1, 2026 as already amended by the v2.3 Amendment Set of November 5, 2026 (A1 to A12). It does not restate the guide: each amendment names the section it changes and gives replacement or added text. Numbering continues from v2.3, so an amendment ID is unambiguous across both sets.

Item	Value
Edition	v2.4, Draft
Date	November 6, 2026
Amends	v2.2 Draft, as amended by the v2.3 Amendment Set (A1 to A12; not yet merged into a full guide)
Source design	Design Proposal: Extensible Vocabulary-to-Glossary Mapping (PEO Semantic Service), November 6, 2026
Versioning	MAJOR.MINOR. A minor version adds content within the existing structure, as v2.2 did when it added two asset types
Normative words	MUST, MUST NOT and SHOULD are normative, as in Graph Naming. Example names and numbers are illustrative

The design proposal is the architecture; this set is how the guide absorbs it. Where the proposal and the guide disagree, the amendments follow the guide and the departure is named in the next section, because the guide's identifier, graph and tenant rules are

already implemented in the KE Workbench and a second convention would split the repository.

ID	Section changed	Change	Type
A13	3.2 Graph Naming; 3.11	Glossary becomes the sixth asset type, at the domain, enterprise and customer tiers	Add
A14	3.2 URI Conventions and Graph Naming; 3.11	Glossary identifiers, IRIs, versions, and the reserved segments label and index	Replace
A15	3.8	Glossary entry model: a concept with SKOS-XL labels; the glossary owner holds definitions and expansions	Add
A16	3.2 Avoiding Acronyms; 3.8	Acronyms are scoped label resources and never resolve globally	Replace
A17	3.2; Appendix F; ingestion configuration	A scoped acronym register replaces the flat approved list	Replace
A18	3.5; 3.9	Weakest true predicate; no owl:sameAs across sources; exactMatch limits	Add
A19	3.2 (GN-D5); 3.11	Mapping records and mapping sets carry status, scope and provenance	Add
A20	3.3; 3.4	Mapping lifecycle, the mapping steward, and the human-in-the-loop gate	Add
A21	2.7; 3.2 (GN-8); 3.8	Consumption rules: accepted links only, scoped acronym lookup, the facade resolves graphs; derived index graph	Replace
A22	1.4; 2.7; 3.10; Appendix E	One onboarding procedure for every source, including third-party ontologies and customer terms	Add

ID	Section changed	Change	Type
A23	3.4; 3.11	Glossary and mapping shapes, load gates and the dangling-reference report	Add
A24	3.6; A11; A12	Glossary and mapping measures with an emitting check each; KE Workbench impact	Add

Gaps, and where the proposal conflicts with the guide

v2.2 and v2.3 already supply about half of the design. What is missing is a home for definitions someone else owns, acronyms that resolve in context, mappings that explain themselves, and one repeatable way to onboard a source.

Design element	Already in the guide	Where
Labels held apart from concepts, by tier	Lexicon at the domain, enterprise and customer tiers; label records point to concepts by IRI	3.2 GN-9; 3.8
Mappings as their own asset	Mapping asset type holding match relations between assets	3.2; 3.11
Acronym as a typed label	core:hasTermType with core:Acronym; SKOS-XL labels; skos:altLabel written at publish for SKOS-only consumers	3.8; 3.11
Lateral links never replace derivation	Three edge types and the allowed-edge matrix	A4
Unresolved terms go to a person	Pending state and four dispositions	A8
Tenant isolation	Opaque tenant IDs; no path joins two tenant graphs	3.2; A9
Graph per release	Current release at the asset IRI; archived releases immutable at version IRIs	3.2 GN-6
Registry	Catalog graph and catalog records	3.2; 3.11

Design element	Already in the guide	Where
Decision gate	AI circuit breaker gateway evaluates every agent and human decision	2.7
Third-party models keep their own IRIs	BFO 2020, RO Core and the RO extract, never ingested	3.10

Gap	Effect today	Closed by
No home for definitions an outside owner publishes	A vocabulary requires genus-and-differentia definitions and Part III identifiers, so third-party text is rewritten or left out, and its licence and source are lost	A13 to A15
Acronyms resolve globally: Appendix F and the configuration hold one flat list of approved expansions	A collision (the same letters, two meanings) cannot be represented, so one expansion shows everywhere	A16, A17
Match relations carry no status, scope or provenance, and no rule picks the predicate	Nobody can say who linked two terms, why, or in what context; transitive exactMatch errors cascade	A18, A19
No lifecycle or steward for mappings	Agent-proposed links have no queue other than the generic human review	A20
No consumption rule for mappings and acronyms	A consumer can read an unreviewed link or an unscoped acronym	A21
No standard way to onboard a source	Each glossary or ontology repeats the integration work	A22
No stale-link check	A source reload leaves links to missing or deprecated terms unnoticed	A23
No measures	The design cannot show it works	A24

Nine conflicts between the proposal and the guide

Each row names the proposal's text, the guide's text, and the resolution this set adopts.

#	The proposal says	The guide says	Resolution	Amendment
1	Term URIs are opaque IDs and never embed the label	Section 3.2 has one readable identifier rule: lower-case words joined by hyphens, implemented in the builders and checks	Keep the guide's rule. An identifier is minted once from the full-form label and never changes, so a later label change breaks no link. The proposal's aim is met by immutability, not opacity	A14
2	Graph IRI is /graph/{type}/{source}/v{n}; the registry is /graph/meta	The graph is the asset IRI; archives sit at asset URI + SemVer; the catalog is the registry	Keep the guide's. The registry pointer is the catalog record's current version. Integer versions become SemVer, and a breaking change is a MAJOR version	A14

#	The proposal says	The guide says	Resolution	Amendment
3	Mapping records live at /id/map/{mapSet}/{id} and use an ex: mapping ontology	Mapping assets live at /mapping/{tier}-{name}/ (GN-D5 pending); core: is the published ontology namespace	Records are minted under the mapping asset. The mapping terms are added to core: in a core release, because core terms change only that way (A1)	A19
4	Mapping status Proposed, Accepted, Deprecated lives in the mapping graph	Assets move Draft, Candidate, Released, Deprecated, Retired; unresolved labels are pending (A8)	They are different things: record status and asset lifecycle. Proposed records are held in the mapping asset's draft graph, never in the current release	A20
5	A glossary entry is a skosxl:Label that carries skos:definition	Five asset types and no glossary; definitions belong to concepts	Glossary is the sixth asset type. An entry is a skos:Concept; its names are SKOS-XL labels	A13, A15

#	The proposal says	The guide says	Resolution	Amendment
6	An acronym is tied to its expansion by ex:isAcronymOf	core:hasTermType core:Acronym already exists, and a concept's preferred label is its full form	Reuse it. The acronym label is an alternate label of the concept whose preferred label is the expansion; add a resolution scope	A16
7	Consumers write FROM lists and pin graph IRIs in queries	GN-8: a service MUST NOT accept a graph IRI from a caller	The facade derives graphs from tenant, persona and catalog. A caller pins a version number, never an IRI. The proposal's SPARQL is for stewards and internal services	A21
8	Link source to source where core has no home	Mappings run through the core (Sections 1.5 and 3.9); primitives are minted only at the core or a top-level domain (A2); a core gap is a change request (A8)	Allowed as an interim, flagged for a core change request, and replaced when the core term exists	A22

#	The proposal says	The guide says	Resolution	Amendment
9	Examples such as g:term-FMLA and g:term-FamilyMedicalLeaveAct	No acronyms in identifiers; polymorphic identifiers are hyphenated	Examples are corrected throughout this set	A14, A16

A13 to A15: The glossary asset

A glossary is a new asset type that holds definitions exactly as their owner publishes them, so third-party and customer wording is kept intact, tied to its source, and linked to the design only through mappings.

A13 (Sections 3.2 Graph Naming and 3.11): add the glossary asset type

In the Asset Names table, extend the type row to six values: vocabulary, taxonomy, ontology, lexicon, mapping, glossary. Replace GN-2 with: **GN-2. The asset type MUST be vocabulary, taxonomy, ontology, lexicon, mapping, or glossary. The word "module" MUST NOT be used.** Add the glossary to the tier table:

Tier	Allowed types (v2.4)	Glossary holds
core	vocabulary, taxonomy, ontology, mapping	Not allowed. The core holds Insperity's own governed meaning (GN-3)
domain	vocabulary, taxonomy, ontology, lexicon, mapping, glossary	Definitions and acronyms an owner publishes for one domain
enterprise	vocabulary, taxonomy, lexicon, mapping, glossary	Definitions and acronyms valid for every tenant
customer	vocabulary, taxonomy, lexicon, mapping, glossary	One tenant's own glossary, in that tenant's graphs

The three label and definition assets differ in who owns the wording and what they may do:

Asset	Holds	Definition rule	May be a derivation parent
Vocabulary	Primitives and terms Insperity governs	Genus and differentia (Section 3.7)	Yes
Lexicon	Labels only, for concepts in other assets	None; a lexicon holds no definitions	No
Glossary	Entries with the owner's published definition, labels and acronyms	As published, not rewritten; present and sourced	No

Examples: glossary-enterprise-employee-benefits; glossary-domain-payroll-operations; glossary-customer-t7f3a9c21-plan-terms. Add these rules after GN-14 (A9):

- **GN-15.** A glossary MUST name one owner, the only party who changes its definitions and acronym expansions.
- **GN-16.** A glossary MUST declare its source, licence and sensitivity in its catalog record.
- **GN-17.** A glossary MUST NOT hold match relations. Links to other assets live only in mapping assets (A19).
- **GN-18.** No vocabulary, taxonomy or ontology refers to a glossary. References run one way: a mapping points to a glossary entry, and nothing points back (the rule A7 sets for lexicons).
- **GN-19.** A customer-tier glossary follows GN-14: it lives in graphs named with the tenant ID, and no path joins it to another tenant.

In Section 3.11, add a Glossary row to the identifier table (A14) and a Glossary Metadata block beside Lexicon and Mapping Metadata. The header carries the common asset fields and these; the properties are chosen when the headers are written, as v2.2 did for lexicons:

Field	Card.	Notes
Owner and steward	1	The glossary owner (GN-15); name and team
Source	1..*	The publisher and edition the entries come from; each entry cites it

Field	Card.	Notes
Licence and sensitivity	1	Coverage, licence terms and data classification (GN-16)
Refresh cadence	1	Event-driven, weekly or quarterly
Acronym scopes	0..*	The concept schemes in which this glossary's acronyms resolve (A16)
Expected volume	1	Entries, acronyms and mappings; used for the platform-limit check

A14 (Sections 3.2 URI Conventions and Graph Naming, 3.11): glossary identifiers, graphs and versions

Add these rows to the URI Conventions table and the 3.11 identifier table. Prefixes follow GN-13: {scope}gls for a glossary, for example benefitsgls:.

Item	Pattern	Example
Glossary asset and scheme	https://www.insperity.com/glossary/{tier}-{name}/	.../glossary/enterprise-employee-benefits/
Entry (concept)	{asset URI}{identifier}	.../enterprise-employee-benefits/family-and-medical-leave-act
Label resource	{asset URI}label/{identifier}-{term-type}[-{n}]	.../enterprise-employee-benefits/label/family-and-medical-leave-act-acronym
Archived release	{asset URI}{SemVer}/	.../enterprise-employee-benefits/2.0.0/

1. **One identifier rule.** An entry identifier is the full-form label in lower-case words joined by hyphens, with "&" as and and no acronym (Section 3.2). This replaces the proposal's opaque IDs: the guide's identifiers are readable, and the builders and checks depend on that.

2. **Minted once, immutable.** An identifier never changes. If the owner rewords a label, the label changes and the IRI stays. If the meaning changes, the entry is deprecated with owl:deprecated true and dcterms:isReplacedBy, and a new entry is minted. An entry is never deleted.
3. **Label resources** take the entry identifier plus the term type: family-and-medical-leave-act-acronym. A second label of the same type adds -2. The acronym letters appear only as the literal form, never in an IRI.
4. **Graphs and versions follow GN-6.** The current release is held at the asset URI and archived releases at version IRIs, which are immutable. A breaking change to a glossary, such as removing or changing the meaning of an entry, is a MAJOR version, and consumers move when they choose by pinning a version (A21). The catalog record names the current version and records its checksum and load time, and so is the registry the proposal calls for.
5. **Reserved segments.** Add label to draft, sim, changes and catalog; the Section 3.8 example already uses it. Add the graph family in A21 for derived index graphs.

A15 (Section 3.8): add Glossaries and Glossary Entries

Add a subsection after Lexicons: Labels by Tier. An entry is a concept; its names are labels; its wording belongs to the glossary owner.

- **Entry.** One skos:Concept in the glossary's own skos:ConceptScheme (skos:inScheme). Required: skos:inScheme, skosxl:prefLabel, skos:definition, a source citation (dcterms:source) and core:hasLifecycleStatus.
- **Names.** The preferred label is a SKOS-XL label whose literal form is the full form (core:FullForm). Every other name, including the owner's verbatim wording when it differs, is a skosxl:altLabel with core:hasTermType. At publish, skos:prefLabel and skos:altLabel are also written for SKOS-only consumers, as Section 3.8 already requires.
- **Definition.** skos:definition is the owner's text, as published. The Section 3.7 genus-and-differentia check is not run on a glossary, because the owner holds the wording. A missing definition is an error (A23). A meaning Insperity must govern is written in a vocabulary, and the glossary entry is mapped to it.
- **Status.** An entry or label uses the lifecycle values of Section 3.11. The proposal's Approved is Released.
- **Not a primitive, not a parent.** An entry never carries core:hasPrimaryTerm and is never the parent in a derivation edge (A4). It is only ever the target of a correspondence edge, from a mapping record (A19).

- **Exempt from the derivation checks.** A5 and the concept-derivation check in A6 apply to concepts in vocabularies, taxonomies and ontologies. A glossary entry is a described source term, not a local concept of the design, so it needs no BFO path. An entry with no accepted mapping is reported as unmapped coverage (A24) and is not rejected.
- **Single ownership.** The glossary owner holds definitions and expansions; the vocabulary owner holds concepts; the mapping steward holds the relationship; the platform owner holds the pipeline, shapes, catalog and mapping terms (roles in A20).

```
@prefix benefitsgls:   <https://www.insperity.com/glossary/enterprise-
employee-benefits/> .
@prefix benefitslabel: <https://www.insperity.com/glossary/enterprise-
employee-benefits/label/> .
@prefix core:          <https://www.insperity.com/ontology/core/> .
@prefix skosxl:        <http://www.w3.org/2008/05/skos-xl#> .

benefitsgls:family-and-medical-leave-act a skos:Concept ;
    skos:inScheme            <https://www.insperity.com/glossary/enterprise-
employee-benefits/> ;
    skosxl:prefLabel         benefitslabel:family-and-medical-leave-act-full-
form ;
    skosxl:altLabel          benefitslabel:family-and-medical-leave-act-
acronym ;
    skos:definition          "Definition as published by the glossary
owner."@en ;
    dcterms:source           <https://www.insperity.com/resource/enterprise-
employee-benefits/source/employee-benefits-handbook> ;
    core:hasLifecycleStatus  core:Released .

benefitslabel:family-and-medical-leave-act-full-form a skosxl:Label ;
    skosxl:literalForm "Family and Medical Leave Act"@en ;
    core:hasTermType   core:FullForm .
```

The acronym label that completes this entry is in A16.

A16 to A17: Acronyms resolve in a scope, never globally

An acronym keeps its place as a label, never an identifier, but it now names the context in which it means what it says, and the approved list becomes a register keyed by acronym and scope.

A16 (Sections 3.2 Avoiding Acronyms and 3.8): replace the acronym rules

Keep the first and last bullets of Avoiding Acronyms (full words in identifiers and preferred labels; "&" is and). Replace the two bullets between them, and add the following to Section 3.8 under Use of Alternate Labels, in place of the Acronyms bullet.

1. **An acronym is a label of its expansion.** It is a SKOS-XL label with core:hasTermType core:Acronym, attached with skosxl:altLabel to the concept whose preferred label is the spelled-out form. The expansion is therefore structural: no property is added, and no tool parses strings to find it. At publish, skos:altLabel is also written.
2. **Every acronym carries a resolution scope.** core:hasResolutionScope names one or more concept schemes in which this acronym means this concept. There is no global value. An acronym label with no scope fails the acronym-scope check (A23).
3. **One meaning per scope.** Within one scope an acronym resolves to exactly one concept. The same letters on two concepts are allowed only when their scopes differ. This extends the no-collision rule of Section 3.8, and the label-resolution check (A6) now runs per scope.
4. **Lookups carry a scope.** A service resolves an acronym only as an acronym plus a scope, and returns a concept or nothing. An acronym given with no scope returns every candidate with its scope, never one answer. The outbound agent takes the scope from the caller's tenant and persona, and when it cannot, it asks a clarifying question naming the candidates, which is what Section 2.7 already has the outbound orchestration agent do when more than one holon or job fits.
5. **Placement follows A7.** An acronym that holds for every tenant and has been vetted stays on the core or domain term. Any other acronym lives in a lexicon or glossary at the narrowest tier that fits, and the scope names where it applies. A persona may be added to the same label (core:intendedForPersona).
6. **A preferred label is still a full form.** A glossary that publishes only a short form, with no expansion, is loaded with the short form as the label and reported as a warning for the glossary owner to resolve (A23).

The same letters can mean two things. The letters IP below are shown for illustration; the point is that each meaning is a different concept in a different scope, and neither is wrong.

Acronym label	Concept (preferred label)	Resolution scope
IP	Internet protocol	Domain Platform Services taxonomy

Acronym label	Concept (preferred label)	Resolution scope
IP	Intellectual property	Domain Legal taxonomy

```
benefitslabel:family-and-medical-leave-act-acronym a skosxl:Label ;
    skosxl:literalForm       "FMLA"@en ;
    core:hasTermType         core:Acronym ;
    core:hasResolutionScope  <https://www.insperity.com/glossary/enterprise-
employee-benefits/> ,
                             <https://www.insperity.com/taxonomy/domain-
payroll-operations/> ;
    dcterms:source           <https://www.insperity.com/resource/enterprise-
employee-benefits/source/employee-benefits-handbook> ;
    core:hasLifecycleStatus  core:Released .
```

A17 (Sections 3.2, Appendix F and the ingestion configuration): replace the flat approved list with a scoped acronym register

Section 3.2 says Appendix F lists the approved expansions and the ingestion configuration holds the same list (acronyms.approved and acronyms.expansions). Replace that with:

- **The register.** The approved acronyms are rows of acronym, scope, expansion, source and approver. The acronym labels in released assets are the source of truth, and the configuration the ingester reads is generated from them, so the two cannot drift. A new acronym is approved for a scope before any label in that scope uses it.
- **The check.** An acronym used in a label of an asset is checked against the register for that asset's scope. An acronym approved only for another scope is reported, not accepted.
- **Appendix F** is the register for this guide's own scope. Its column is headed Meaning (scope: this guide), and each row's acronym is scoped to the Semantic Governance guide.
- **Approval.** In Conformance Review, approving an acronym or ticking Remember the expansion records the scope, which defaults to the scheme of the asset under review. The decision passes the same gate as any other disposition (A20).
- **Migration.** The current flat list holds terms from different fields, for example AI, API, DSL, EBITDA, HVAC, IP and IRI, each treated as if it held everywhere. On the first run after adoption, each configured acronym is assigned the scope of the asset where the

ingester finds it used, and a new Conformance Review category, Acronyms without scope, lists any that no asset uses. Nothing in that list counts as approved until a steward gives it a scope.

```
"acronyms": {
  "scopes": {
    "https://www.insperity.com/taxonomy/domain-platform-services/": { "IP":
"internet protocol" },
    "https://www.insperity.com/taxonomy/domain-legal/":             { "IP":
"intellectual property" }
  }
}
```

The configuration shape above is illustrative and is fixed when the ingester is changed (A24).

A18 to A20: Mappings that explain themselves

A link between a concept and a glossary entry becomes a record that says who made it, why, when and in what context, and that moves through a review before anyone consumes it.

A18 (Sections 3.5 and 3.9): add the weakest true predicate

Add to Section 3.9, under the concept mapping row, and to Section 3.5 beside the rule that mapping changes need Architecture:

Predicate	Use when	Caution
skos:exactMatch	The two are interchangeable in any context	Transitive, so one wrong link spreads through a chain. Limited by rule 3 below
skos:closeMatch	Interchangeable in some contexts	The default for a cross-domain link
skos:broadMatch, skos:narrowMatch	One is more general than the other	Check the direction before accepting
skos:relatedMatch	An associative link	Never used to carry a definition across

1. **Weakest true predicate.** A mapping uses the weakest predicate that is true. When two predicates fit, the weaker is chosen.
2. **No owl:sameAs across sources.** owl:sameAs MUST NOT link assets that come from different sources.
3. **Limits on exactMatch.** A chain of exactMatch statements is capped at a length [to be set at the Gate 1 baseline], a cycle is an error, and each exactMatch is accepted by the mapping steward and Architecture together, because Section 3.5 already routes mapping changes through Architecture.
4. **Lateral only.** A match relation is a correspondence edge (A4). It never gives the concept a parent, and it never replaces derivation.
5. **A definition crosses only on a strong link.** A glossary definition is shown for a concept only through an Accepted exactMatch or closeMatch (A21).
6. **Plain triples are derived.** At publish, the plain triple (subject, predicate, object) is also written from each Accepted record, for SKOS-only consumers, as Section 3.8 does for skos:altLabel. The record stays the source of truth.

A19 (Sections 3.2 GN-D5 and 3.11): add mapping records and mapping sets

This amendment confirms the path pattern GN-D5 asks about: a mapping asset is held at https://www.insperity.com/mapping/{tier}-{name}/, as the URI Conventions proposal states, for example mapping-domain-payroll-operations-to-employee-benefits. It then adds the record.

- **Mapping set.** One mapping asset holds the records between the assets named in its catalog record as source and target (Section 3.11). A record is held in no other graph.
- **Where a match lives.** A match relation whose object is in a glossary, a third-party source, or another tenant's or tier's asset lives only in a mapping asset. Existing exactMatch and broadMatch statements from process kinds to the APQC reference registry stay where they are; moving them is an open item.
- **Mapping record.** An individual of core:mapping-record. Its IRI is {mapping asset URI} {subject-identifier}-to-{object-identifier}, minted once and never changed. A second record for the same pair adds -2.

Property	Card.	Value
core:mappingSubject	1	IRI of a concept in a vocabulary, taxonomy or ontology

Property	Card.	Value
core:mappingPredicate	1	One of the five SKOS match properties (A18)
core:mappingObject	1	IRI of the concept, glossary entry or class matched
core:mappingStatus	1	core:Proposed, core:Accepted or core:Deprecated (A20)
core:mappingJustification	1..*	core:LexicalMatch, core:ManualReview or core:EmbeddingSimilarity; the list grows as the mapping agent gains methods
core:mappingConfidence	0..1	Decimal from 0 to 1; required when a justification is automated
core:hasResolutionScope	1..*	The concept schemes in which the link holds; every record has one
prov:wasAttributedTo	1	The person, or the pipeline agent, that made the record
dcterms:created	1	xsd:date
core:approvedBy	1 for Accepted	The steward who accepted it (Section 3.3)

The names are proposed. They are new core terms, so they enter the core only in a core release (A1), with BFO lineage chosen there (open item). A record is data about a link, not a primitive, so A2 does not apply to it.

```
@prefix mapping: <https://www.insperity.com/mapping/domain-payroll-
operations-to-employee-benefits/> .
@prefix payroll: <https://www.insperity.com/vocabulary/domain-payroll-
operations/> .

mapping:leave-accrual-to-family-and-medical-leave-act a core:mapping-record ;
    core:mappingSubject        payroll:leave-accrual ;
    core:mappingPredicate      skos:closeMatch ;
    core:mappingObject         benefitsgls:family-and-medical-leave-act ;
    core:mappingStatus         core:Accepted ;
    core:mappingJustification  core:LexicalMatch ;
    core:mappingConfidence     "0.86"^^xsd:decimal ;
    core:hasResolutionScope    <https://www.insperity.com/taxonomy/domain-
payroll-operations/> ;
    prov:wasAttributedTo       <https://www.insperity.com/resource/domain-
payroll-operations/agent/mapping-agent> ;
    core:approvedBy            <https://www.insperity.com/resource/domain-
payroll-operations/person/data-steward> ;
    dcterms:created            "2026-11-06"^^xsd:date .
```

A20 (Sections 3.3 and 3.4): add the mapping lifecycle and roles

Record status and asset lifecycle are separate. The asset (the mapping set) moves Draft, Candidate, Released, Deprecated, Retired under Section 3.3. A record inside it has its own status:

Record status	Meaning	Who moves it	Where it is held
Proposed	Created by a person or by candidate generation	The author, or the mapping agent	In the mapping asset's draft graph (asset URI + draft/{change-id}); never in the current release
Accepted	Reviewed and approved for use	The mapping steward, through the decision gate	In the current release
Deprecated	No longer valid; names a replacement if one exists	The mapping steward	In the current release, with owl:deprecated true and dcterms:isReplacedBy; never deleted

1. **Agents propose, people accept.** The mapping agent (Section 1.5) writes Proposed records and never accepts one. Candidates below a confidence threshold [to be set] are not queued.
2. **Acceptance is a decision.** It passes the AI circuit breaker gateway like every other decision (Section 2.7), is recorded in the change log with core:approvedBy, and an exactMatch also needs Architecture (A18).
3. **One queue per change.** The review queue is the draft graph of one change-id, so a batch of candidates is reviewed, released or rejected as a unit and its draft is then deleted (GN-12).
4. **Stale links are migrated, not edited.** A record whose target is deprecated or missing is found by the dangling-reference report (A23) and replaced by a new release of the mapping set: the old record is deprecated and a new one added.
5. **Change control.** A change to a source graph publishes a new version and the report. Mapping stewards review the affected records. No consumer is forced to move to the new version (A21).

Role	Responsibility	Guide role
Glossary owner	Definitions and acronym expansions in the glossary	Named in the catalog record (GN-15)

Role	Responsibility	Guide role
Vocabulary owner	Concepts and schemes in the vocabulary	The owner of the asset (Section 3.1)
Mapping steward	Reviews and accepts mappings for one domain pair	The domain data steward, named in the mapping set's catalog record
Platform owner	Pipeline, shapes, catalog and the mapping terms in the core	Architecture (Section 3.5)

A21 to A23: Consuming, onboarding and checking

Consumers read only reviewed links, a new source arrives by one procedure that edits nothing existing, and every load reports what it left dangling.

A21 (Sections 2.7, 3.2 GN-8 and 3.8): replace the consumption rules

Add to Section 2.7 (outbound services) and Section 3.8 (the search and selection rules):

1. **Accepted links only.** A consumer reads mapping records whose core:mappingStatus is core:Accepted. Proposed records are for stewards. They are held in draft graphs (A20), so the filter is a second safeguard rather than the only one.
2. **Acronyms with a scope.** An acronym lookup always carries its scope (A16).
3. **The facade chooses graphs.** GN-8 stands: a service MUST NOT accept a graph IRI from a caller. The facade derives the reachable graphs from the caller's tenant and persona and from the catalog. A caller may pin a version of an asset by SemVer, for example the employee benefits glossary at 2.0.0, and the facade resolves the version IRI from the catalog. With no pin, the current release is used. This replaces the proposal's hand-written FROM lists for callers.
4. **Compose at query time.** The facade queries the graphs it selected. It never serves a merged copy, and the only stored derived copy is the index graph below.
5. **Governed definition first.** When a concept has its own vocabulary definition and a mapped glossary definition, the answer shows the governed definition. The glossary definition is added only through an Accepted exactMatch or closeMatch (A18), labelled with its source and version.
6. **Tenant isolation.** A tenant's lookups reach the core, domain and enterprise assets and that tenant's own graphs, never another tenant's (A9).

7. **Facade contract.** The search facade of Section 2.6 exposes lookup by concept, by term, and by acronym with scope. Each returns the matched concept, its Accepted mappings with predicate, scope and provenance, the glossary definition where rule 5 allows it, and the source and version. The exact operations are [to be defined with the service team].

The query below is for stewards and internal services only. It shows the shape of a composed read, not what a caller writes.

```
SELECT ?concept ?entry ?definition
FROM <https://www.insperity.com/vocabulary/domain-payroll-operations/>
FROM <https://www.insperity.com/glossary/enterprise-employee-benefits/2.0.0/>
FROM <https://www.insperity.com/mapping/domain-payroll-operations-to-
employee-benefits/>
WHERE {
  ?m core:mappingSubject ?concept ; core:mappingObject ?entry ;
     core:mappingPredicate ?p ; core:mappingStatus core:Accepted .
  FILTER (?p IN (skos:exactMatch, skos:closeMatch))
  OPTIONAL { ?entry skos:definition ?definition }
}
```

Derived index graph. For fast lookup the pipeline may build a concept-to-term-to-acronym index. Add it to the Named Graphs table as a reserved family:

Graph family	Pattern	Holds
Derived index	https://www.insperity.com/graph/index/{tier}-{name}	A disposable lookup from concept to term to acronym, built from released assets and Accepted records

The index is rebuilt from its sources on every load, is never edited, and is never a source of truth. It holds nothing that is not Accepted and is never mapped to. For the customer tier there is one index per tenant, named with the tenant ID, so no index joins two tenants (GN-14).

A22 (Sections 1.4, 2.7, 3.10 and Appendix E): add one onboarding procedure for every source

Adding a source always means the same three artifacts: a graph, a catalog record and a mapping set. Nothing existing is edited.

You are adding	You create	You touch
A glossary or acronym set	Glossary graph, catalog record, mapping set to core or domain terms	Nothing existing
A domain vocabulary	Vocabulary graph, catalog record, mapping to the core, and to glossaries where the core has no home	Nothing existing
A third-party ontology or vocabulary	Reference graph, catalog record, mapping set	Nothing existing
Customer-supplied terms	Customer glossary or lexicon in the tenant's graphs, catalog record, tenant mapping set	Nothing existing; onboarding adds no triples to a core or domain graph (GN-3)
A new version of a source	New version graph, the catalog's current version, the dangling-reference report	The catalog record only
Mappings between two existing assets	A mapping set	Nothing existing

Third-party ontologies and vocabularies. Section 3.10 says BFO 2020, RO Core and the RO extract keep their own IRIs and are never ingested. Extend that rule to every third-party ontology or vocabulary:

- Its term IRIs stay the owner's and are never renamed or rewritten into Part III form.
- It is loaded into its own named graph. When a tenant supplies it, the graph is a tenant graph (A9) and the term IRIs still stay the owner's.
- No core, domain or enterprise asset imports it, and none of its classes is a derivation parent of a core term. Core lineage goes to BFO (A1).
- It is reached only through a mapping set, as the target of a correspondence edge (A4).
- Its source, licence and edition are in its catalog record.

The procedure. Steps map onto the guide's existing pipeline; the inbound pipe is the only way in, and a load replaces one graph.

1. **Propose.** Complete the onboarding proposal (Section E.5): owner, scope, licence, expected volume, refresh cadence.
2. **Register.** Create the catalog record and reserve the scope and namespace.
3. **Transform.** Convert the source to SKOS or SKOS-XL with identifiers minted under A14. Identifiers are minted once and kept on every reload.
4. **Validate.** Run the shapes for the graph type (A23). A failure stops the load.
5. **Load.** Run the inbound ingestion pipe into a new version graph. There are no side-channel writes, and loading again replaces the same graph (GN-6).
6. **Map.** Link to the core first. Candidates land as Proposed (A20). A link from one source to another is allowed only where the core has no concept; it is recorded as an interim, a core change request is opened in the same step (A8, disposition 3), and the interim record is deprecated when the core term exists.
7. **Review.** The mapping steward accepts, rejects or rescopes each candidate (A20). A term or acronym that cannot be resolved enters the pending state (A8), which is allowed in DEV and STG only.
8. **Publish.** Release the graphs, and make the catalog's current version point at the new release. Announce the version to consumers.

Mapping to the core first keeps the number of mappings roughly proportional to the number of sources, not to the number of pairs of sources. Add Section E.5 to Appendix E with the templates in the last section of this set, and refer to it from E.2.

A23 (Sections 3.4 and 3.11): add the glossary and mapping gates

Add these rules to the Part III checks. The rules marked blocking are added to loadBlockingRules, so a load stops while one fails, and, as Conformance Review already does for the existing blocking rules, waiving one is evaluated as a HALT decision under Section 2.7.

Rule	Checks	Applies to	Severity
glossary-shape	Every entry and label has the properties its shape requires (A15)	Glossary	Error, blocking
glossary-definition-present	skos:definition is present and the source is cited	Glossary	Error, blocking

Rule	Checks	Applies to	Severity
acronym-scope	Every acronym label has at least one resolution scope	All assets	Error, blocking
acronym-scope-unique	Within one scope an acronym resolves to one concept	All assets	Error, blocking
mapping-record-shape	A record has the properties of A19	Mapping	Error, blocking
mapping-resolves	Subject and object resolve in a graph registered in the catalog	Mapping	Error, blocking
exact-match-limit	No exactMatch cycle and no chain over the limit (A18)	Mapping	Error, blocking
exact-match-approval	An Accepted exactMatch records Architecture approval	Mapping	Error
match-in-source-graph	No match to a glossary, third-party or other-tenant asset outside a mapping asset (GN-17)	All but mapping	Error, blocking
catalog-complete	The catalog record has source, version, checksum and load time	All assets	Error, blocking
acronym-expansion-missing	A glossary entry published with a short form and no expansion	Glossary	Warning
glossary-unmapped	A glossary entry with no Accepted mapping	Glossary	Information

Dangling-reference report. Every load produces one. It lists records whose subject or object is missing or deprecated in the version now current, acronym scopes that name a scheme that no longer exists, and deprecated entries whose replacement is absent. It is attached to the change record, sent to the affected mapping stewards, and emitted as telemetry (A12).

Shapes. Each new form has one SHACL shape, named as in Section 3.2: the glossary entry, the label, and the mapping record. Rules SHACL core cannot state, namely scope uniqueness, resolution in the catalog, and the exactMatch chain limit, are SPARQL constraints. The platform's graph count and size limits, the SHACL engine, and graph-level versioning are [to be confirmed with the platform team].

A24: Measures, telemetry and KE Workbench impact

The design succeeds when a new glossary is added without editing anything that exists and every link can explain itself, so the measures below test exactly those two claims.

A24 (Section 3.6, with A11 and A12): add the glossary and mapping measures

Add these to the measures of Section 3.6. Following A12, each is computed by a check that emits a telemetry event, and the Operations Dashboard reads the events. A measure with no emitter yet is listed as not yet measured. Targets not stated here are set at the Gate 1 baseline, or after the pilot where noted.

Measure	What it shows	Target	Emitting check
Glossary reuse	Share of glossary entries with two or more Accepted inbound mappings	Set at baseline	glossary-unmapped and a reuse count
Link completeness	Share of Accepted records that carry status, justification, scope and provenance	100%	mapping-record-shape
Dangling references	Records, scopes and replacements flagged on a load	0 in a released graph	dangling-reference report
Cross-graph write dependencies	Match relations found outside a mapping asset; releases that needed a coordinated change	0	match-in-source-graph
Unscoped acronyms	Acronym labels with no resolution scope	0	acronym-scope
Acronym collisions	Acronyms that resolve to more than one concept across scopes; each must be scoped	Reported, all scoped	acronym-scope-unique
Unmapped glossary entries	Entries with no Accepted mapping	Set at baseline	glossary-unmapped

Measure	What it shows	Target	Emitting check
Proposed-mapping backlog age	Age of the oldest Proposed record; extends the promotion-backlog age of A11	Set at baseline	Draft graph query
Mapping acceptance rate	Share of agent-proposed records accepted on review; the Section 3.6 mapping accuracy measure, now read from records	80% or higher	Mapping records
Onboarding effort	Median days from Propose to Publish, per source	Set after the pilot	Change log timestamps

KE Workbench impact

What changes in the workbench when v2.4 is adopted. These are the tools to be changed, not changes made by this set.

Area	Change	Amendment
Ingestion	Glossary as a source kind; the scoped acronym configuration and its first-run migration; loadBlockingRules extended	A13, A17, A23
Standards Conformance and Conformance Review	The rules in A23; a category Acronyms without scope; waiving a blocking rule is a HALT disposition	A17, A23
Pending terms	Glossary entries and acronyms that cannot be resolved use the existing pending state	A22
Model Manager and editors	List glossary assets; a steward queue that shows the Proposed records of one change-id	A19, A20

Area	Change	Amendment
Operations Dashboard	The measures above on the Measures tab; RESOLUTION for 2.4 in ops_spec.py	A24
Core	The mapping-record class, its properties and the status and justification values are added in a core release	A1, A19
Edition in force	Saving this set in the workbench docs folder makes v2.4 the edition in force. Do that when the changes above are ready, since policy P07 then reports every asset that still declares an earlier edition	A24

Open items, Appendix F additions and how to apply

Ten items need a decision before these amendments are final. Five come from the design proposal and five are new. The proposal asks for approval of its architecture and funding for phase 1 (one core vocabulary, one domain vocabulary, one glossary); that approval applies to the design as amended here, because A14 replaces its URI strategy with the guide's.

Item	Question	Affects	Source
Platform limits	What are the named-graph count and size limits, the SHACL engine, and support for graph-level versioning?	A14, A23	Proposal
First mapping target	Which core vocabulary is mapped first, and who owns it?	A19, A22	Proposal
Pilot scope	Which domain vocabulary and which glossary go first?	A22	Proposal

Item	Question	Affects	Source
exactMatch policy	What is the maximum chain length, and does Architecture plus the mapping steward approve every exactMatch, as A18 proposes?	A18, A23	Proposal
Facade operations	Which operations does the facade expose for lookup by concept, term and scoped acronym?	A21	Proposal
Acronym scope grain	Is a scope always a concept scheme, or may it be a domain or an asset? How does a tenant's scope relate to the enterprise's?	A16	New
Core lineage	What is the BFO parent of core:mapping-record, as A1 requires?	A19	New
APQC statements	Do the exactMatch and broadMatch statements from process kinds to the APQC registry move into a mapping asset?	A19	New
Candidate threshold	What confidence is the minimum for queueing a Proposed record?	A20	New
Licensed customer content	When a tenant supplies a licensed third-party glossary or ontology, who holds and records the licence?	A22	New

The proposal's first open question, the host name and identifier format, is closed by A14: the base URL and identifier rule of Section 3.2 apply, and identifiers are minted by the builders and the ingester. GN-D5 is answered by A19 and awaits confirmation. The open items of v2.3 (area-container minting, persona search ranking, simulation sequencing, council approver, and GN-D1 and GN-D3 to GN-D7) are untouched by this set.

Appendix F additions

Add these entries. Rewrite Lexicon to end "definitions belong to a glossary or a vocabulary", and Mapping to "an asset that holds mapping records between assets". Head the Meaning column of Terms & Acronyms "Meaning (scope: this guide)".

Term	Meaning
Glossary	An asset that holds entries with the definition their owner publishes, as published, at the domain, enterprise or customer tier
Glossary entry	A skos:Concept in a glossary's scheme with SKOS-XL labels, an owner's definition and a source
Glossary owner	The party who alone changes a glossary's definitions and acronym expansions
Resolution scope	The concept schemes in which an acronym or a mapping holds; there is no global scope
Scoped acronym register	The approved acronyms, each with its scope and expansion, derived from the acronym labels in released assets
Mapping record	An individual that states one match: subject, predicate, object, status, justification, scope and provenance
Mapping set	A mapping asset and the records it holds between its source and target assets
Mapping steward	The domain data steward who accepts, rejects or rescopes mappings for one domain pair
Weakest true predicate	The rule that a mapping uses the weakest SKOS match property that is true
Dangling reference	A mapping, scope or replacement that points at a term that is missing or deprecated in the current version
Derived index graph	A disposable lookup graph rebuilt from released assets on every load, never a source of truth
Third-party source	An ontology or vocabulary kept at its owner's IRIs, loaded unchanged and reached only through a mapping set

Revision history row and how to apply

Add this row to Document Control:

Version	Date	Status	Changes
2.4	November 6, 2026	Draft	Glossaries and acronyms. Section 3.2: glossary as the sixth asset type (rules GN-15 to GN-19), glossary identifiers and graph IRIs, the reserved segment label, derived index graphs; acronyms as scoped labels and a scoped acronym register in place of the flat approved list. Sections 3.5 and 3.9: weakest true predicate. Sections 3.2 and 3.11: mapping records and mapping sets, GN-D5 confirmed. Sections 3.3 and 3.4: mapping lifecycle, roles, glossary and mapping gates, dangling-reference report. Sections 2.7 and 3.8: consumption rules. Sections 1.4, 3.10 and Appendix E: one onboarding procedure, including third-party ontologies and customer terms (new Section E.5). Section 3.6: ten measures. Appendix F: new terms.

1. Merge the v2.3 amendments (A1 to A12) into the v2.2 source first, then edit the sections named in A13 to A24.
2. Add the document control row above, Section E.5 from the templates below, and the Appendix F entries.
3. Rerun the build checks, including the rules in A23, and the dangling-reference report on every glossary and mapping set loaded.
4. Release the new core terms (A19) in a core release before any mapping set uses them.
5. Change the workbench as listed under KE Workbench impact, then save the PDF in the workbench docs folder.

Templates for new Section E.5: Onboarding a Glossary or Other Source

Copy these for each new source or mapping set and replace every value in braces. They are the proposal's templates, rewritten to the guide's names: the catalog record replaces the proposal's manifest entry, and the core: namespace replaces its ex: namespace.

E.5.1 Source onboarding proposal (one page per source)

```
# Onboarding: {source name}

- Type: {glossary | acronym set | domain vocabulary | third-party source |
customer terms | mapping set}
- Tier: {domain | enterprise | customer, with tenant ID}
- Owner and steward: {name, team}
- Purpose and consumers: {who uses it, for what}
- Scope, licence and sensitivity: {coverage, licence terms, data
classification}
- Expected volume: {entries, acronyms, mappings}
- Refresh cadence: {event-driven | weekly | quarterly}
- Depends on: {core assets, or none}
- Asset name and URI: {type-tier-name;
https://www.insperity.com/{type}/{tier}-{name}/}
- Mapping targets: {core concepts first; other sources only where the core
has no concept}
- Acronym scopes needed: {concept schemes}
- Risks and exceptions to the design principles: {none | list}
- Approvals: {owner, mapping steward, platform owner}
```

E.5.2 Catalog record

```
<https://www.insperity.com/glossary/{tier}-{name}/{version}/> a dcat:Dataset
;
    dcterms:title        "{source name}" ;
    dcterms:publisher    <{owner}> ;
    dcterms:source       <{source record}> ;
    dcterms:license      <{licence}> ;
    owl:versionInfo      "{SemVer}" ;
    dcterms:issued       "{date}"^^xsd:date ;
    core:hasLifecycleStatus core:{Draft | Candidate | Released} ;
    core:hasTier         core:{domain | enterprise | customer} ;
    core:dependsOn       <{asset URI}> ;
    core:hasChecksum     "{sha256}" ;
    core:hasLoadTime     "{date-time}"^^xsd:dateTime .
```

The property names are chosen when the catalog headers are written (Section 3.11). The record carries the version the catalog calls current, so flipping it is the publish step.

E.5.3 SHACL shape for a mapping record (starting point)

```
core:mapping-record-shape a sh:NodeShape ;
    sh:targetClass core:mapping-record ;
    sh:property [ sh:path core:mappingSubject ; sh:minCount 1 ; sh:maxCount 1
; sh:nodeKind sh:IRI ] ;
    sh:property [ sh:path core:mappingObject  ; sh:minCount 1 ; sh:maxCount 1
; sh:nodeKind sh:IRI ] ;
    sh:property [ sh:path core:mappingPredicate ; sh:minCount 1 ; sh:maxCount
1 ;
                  sh:in ( skos:exactMatch skos:closeMatch skos:broadMatch
skos:narrowMatch skos:relatedMatch ) ] ;
    sh:property [ sh:path core:mappingStatus ; sh:minCount 1 ; sh:maxCount 1
;
                  sh:in ( core:Proposed core:Accepted core:Deprecated ) ] ;
    sh:property [ sh:path core:mappingJustification ; sh:minCount 1 ] ;
    sh:property [ sh:path core:hasResolutionScope ; sh:minCount 1 ;
sh:nodeKind sh:IRI ] ;
    sh:property [ sh:path prov:wasAttributedTo ; sh:minCount 1 ] ;
    sh:property [ sh:path dcterms:created ; sh:minCount 1 ; sh:datatype
xsd:date ] .
```

Add as SPARQL constraints: subject and object resolve in a graph registered in the catalog (mapping-resolves); an Accepted record carries core:approvedBy; no acronym label lacks a core:hasResolutionScope, and no scope holds one acronym for two concepts (acronym-scope, acronym-scope-unique); no exactMatch chain exceeds the limit (exact-match-limit).

E.5.4 Pre-load and post-load checklist

- [ ] Onboarding proposal approved and catalog record created; scope and namespace reserved
- [ ] Source converted with identifiers minted under A14, and no acronym in any identifier
- [ ] Shapes pass for the graph type (A23)
- [ ] Loaded into a new version graph, never over an archived one
- [ ] Dangling-reference report reviewed
- [ ] Candidate mappings created as Proposed only, in the change's draft graph
- [ ] Mapping steward review complete; each exactMatch approved by Architecture
- [ ] Core change request opened for every interim source-to-source link
- [ ] Catalog's current version flipped and consumers notified