

How North Star search works

1 Admit

Each item is classified, tagged with its client tenant and PII class, and SHACL-validated before it can be found.

2 Anchor

Each admitted item gets a canonical URI, linked to its rules, plans and jurisdictions.

3 Resolve

The question becomes five coordinates: WHO, WHAT, WHERE, WHEN, WHY.

4 Retrieve

Hybrid retrieval: SPARQL over the graph plus vector search, both keyed on URIs.

5 Filter

The policy enforcement point removes anything outside the asker's tenant or role.

6 Score and cite

MTBH scores the answer, uncertain ones go to a person, and every answer cites its sources.

FOR TECHNICAL LEADERS

Stack independent by contract

Port	Canonical contract	Microsoft adapter	Alternates
Meaning	OWL 2 · SKOS · LKIF	Fabric IQ ontology (generated)	Neptune · GraphDB
Rules	SHACL · SWRL · KGCL	Fabric/dbt tests · Power Automate	Workday validations · dbt
Policy	OPA/Rego · JSON Schema	API Management + OPA · Purview DLP	Cedar · Envoy
Identity	OIDC · SCIM · URI registry	Entra ID · Entra Agent ID	Okta · Keycloak
Grounding	SPARQL · URI-anchored RAG	Foundry IQ · Azure AI Search	Bedrock KB · pgvector
Agents	MCP · A2A · OpenAPI	Copilot Studio · Foundry Agents	LangGraph · Claude · Workday
Telemetry	PROV-O · OpenTelemetry	Monitor · Sentinel · Purview Audit	Datadog · OpenLineage
Analytics	W3C DPROD	OneLake · Power BI	dbt Semantic Layer · Superset