Documentation

The Java™ Tutorials

Trail: Learning the Java Language **Lesson:** Numbers and Strings

Section: Strings

The Java Tutorials have been written for JDK 8. Examples and practices described in this page don't take advantage of improvements introduced in later releases and might use technology no longer available.

See Java Language Changes for a summary of updated language features in Java SE 9 and subsequent releases.

See JDK Release Notes for information about new features, enhancements, and removed or deprecated options for all JDK releases.

Converting Between Numbers and Strings

Converting Strings to Numbers

Frequently, a program ends up with numeric data in a string object—a value entered by the user, for example.

The Number subclasses that wrap primitive numeric types (Byte, Integer, Double, Float, Long, and Short) each provide a class method named valueOf that converts a string to an object of that type. Here is an example, ValueOfDemo, that gets two strings from the command line, converts them to numbers, and performs arithmetic operations on the values:

```
public class ValueOfDemo {
   public static void main(String[] args) {
        // this program requires two
        // arguments on the command line
        if (args.length == 2) {
            // convert strings to numbers
            float a = (Float.valueOf(args[0])).floatValue();
            float b = (Float.valueOf(args[1])).floatValue();
            // do some arithmetic
            System.out.println("a + b = " +
                               (a + b));
            System.out.println("a - b = " +
                               (a - b));
            System.out.println("a * b = " +
                               (a * b));
            System.out.println("a / b = " +
                               (a / b));
            System.out.println("a % b = " +
                               (a % b));
        } else {
            System.out.println("This program " +
                "requires two command-line arguments.");
       }
   }
```

The following is the output from the program when you use 4.5 and 87.2 for the command-line arguments:

```
a + b = 91.7

a - b = -82.7

a * b = 392.4

a / b = 0.0516055

a % b = 4.5
```

Note: Each of the Number subclasses that wrap primitive numeric types also provides a parseXXXX() method (for example, parseFloat()) that can be used to convert strings to primitive numbers. Since a primitive type is returned instead of an object, the parseFloat() method is more direct than the valueOf() method. For example, in the ValueOfDemo program, we could use:

```
float a = Float.parseFloat(args[0]);
float b = Float.parseFloat(args[1]);
```

Converting Numbers to Strings

Sometimes you need to convert a number to a string because you need to operate on the value in its string form. There are several easy ways to convert a number to a string:

```
int i;
// Concatenate "i" with an empty string; conversion is handled for you.
String s1 = "" + i;
or
// The valueOf class method.
String s2 = String.valueOf(i);
```

Each of the Number subclasses includes a class method, toString(), that will convert its primitive type to a string. For example:

```
int i;
double d;
String s3 = Integer.toString(i);
String s4 = Double.toString(d);
```

The ToStringDemo example uses the toString method to convert a number to a string. The program then uses some string methods to compute the number of digits before and after the decimal point:

The output of this program is:

```
3 digits before decimal point.
2 digits after decimal point.
```

About Oracle I Contact Us I Legal Notices I Terms of Use I Your Privacy Rights

Copyright © 1995, 2022 Oracle and/or its affiliates. All rights reserved.

Previous page: Strings

Next page: Manipulating Characters in a String