



Passivation quality control in poly-Si/SiO_x/c-Si passivated contact solar cells with 734 mV implied open circuit voltage

HyunJung Park^a, Hyomin Park^a, Se Jin Park^a, Soohyun Bae^a, Hyunho Kim^a, Jee Woong Yang^a, Ji Yeon Hyun^a, Chang Hyun Lee^a, Seung Hyun Shin^a, Yoonmook Kang^b, Hae-Seok Lee^{b,*}, Donghwan Kim^a

^a Department of Material science and Engineering, Korea University, 145, Anam-ro, Seongbuk-gu, Seoul 02841, Korea

^b KU-KIST Green School Graduate School of Energy and Environment, Korea University, 145, Anam-ro, Seongbuk-gu, Seoul 02841, Korea

ARTICLE INFO

Keywords:

Polysilicon
Tunnel oxide
Passivated contact
N-type silicon
High efficiency
Solar cell

ABSTRACT

Passivation quality of poly-Si contacts with different phosphorus doping concentration were investigated in this study. Intrinsic poly-Si layers were deposited by LPCVD on a tunnel oxide surface, followed by n + poly-Si doping and hydrogenation. For lightly doped poly-Si contacts with phosphorus concentration of $2.1 \times 10^{19} \text{ cm}^{-3}$, higher temperatures and longer times increased iV_{OC} achieving maximum value of 734 mV, as poly-Si grain size increases from 13 nm to 40 nm. However, for heavily doped poly-Si contacts with phosphorus concentration of $1.1 \times 10^{20} \text{ cm}^{-3}$, iV_{OC} decreased from 731 mV to 696 mV as annealing time increased from 10 to 60 min because Auger recombination rate increased from 9.3 fA/cm² to 21.6 fA/cm² as phosphorus in-diffusion occurs. The contact resistance of poly-Si contacts was also investigated to achieve a high fill factor. Finally, a poly-Si/SiO_x/c-Si passivated contact solar cell using a poly-Si contact on the back and boron diffused emitter on the front was fabricated. As a result, high efficiency of 21.1% solar cell was achieved with V_{OC} of 665 mV, J_{SC} of 40.6 mA/cm², and fill factor of 78.3%.

1. Introduction

Recombination losses at the interface between the metal contact and doped-semiconductor region is a major efficiency-limiting factor in solar cells. To reduce losses from metal-semiconductor contact recombination, the concept of passivated contact was introduced. A tunnel oxide passivated contact (TOPCon) solar cell [1] is composed of a n + poly-Si/SiO_x/c-Si contact on the rear side and boron doped emitter on the front side, and has a reported highest efficiency of 25.8% [2,3]. One major method to form poly-Si/SiO_x/c-Si passivated contacts is to deposit an amorphous silicon layer (a-Si) and crystallized a-Si onto poly-Si with subsequent annealing. Another way is to use the low-pressure chemical vapor deposition method (LPCVD) for poly-Si deposition, which provides better crystallinity. Using LPCVD-deposited poly-Si/SiO_x/c-Si passivated contact (hereafter, poly-Si contact), some groups reported poly-Si contact solar cells using POCl₃ diffusion method and the highest efficiency was 21.5% [4,5]. Also, some groups reported poly-Si contact solar cells formed by ion implantation method to form n + doping on i-poly-Si layer which achieved the highest

efficiency of 21.2% [6–10]. About iV_{OC} values, about 730 mV was obtained using crystallized a-Si passivated contact [9,11] and LPCVD deposited poly-Si passivated contact [12]. The highest iV_{OC} of 749 mV was reported by ISFH [13] for the latter with phosphorus implantation. Although many groups involved poly-Si contact, the relation between the poly-Si layer and passivation is still unclear because researchers focused on the tunnel oxide quality. However, characteristics of the poly-Si layer also affect on passivation quality of poly-Si contacts according to its annealing condition and doping concentration. Thus, we focused our study, to better understand the effect of the poly-Si layer on passivation quality, on the grain-size growth and phosphorus in-diffusion. High efficiency was achieved with a tunnel-oxide-passivated contact solar cell with a homogeneous boron emitter on the front and poly-Si contact on the rear.

For the experiments, the poly-Si contacts were annealed at different temperatures and times, and with different phosphorus doping concentrations, in the poly-Si layer. Passivation quality was determined using iV_{OC} and J_0 measured by the quasi-steady-state photoconductance (QSSPC) method [14]. The J_0 values are determined under the high

* Corresponding author.

E-mail addresses: jung1029@korea.ac.kr (H. Park), solar@korea.ac.kr (H.-S. Lee).

URL: <http://solar.korea.ac.kr> (D. Kim).

<https://doi.org/10.1016/j.solmat.2018.09.013>

Received 25 October 2017; Received in revised form 25 June 2018; Accepted 10 September 2018

Available online 25 September 2018

0927-0248/ © 2018 Elsevier B.V. All rights reserved.