



Contents lists available at ScienceDirect

## Electrochemistry Communications

journal homepage: [www.elsevier.com/locate/elecom](http://www.elsevier.com/locate/elecom)

# Proof-of-concept experiments of an acid-base junction flow battery by reverse bipolar electro dialysis for an energy conversion system



Jae-Hun Kim, Jin-Hyun Lee, Sandip Maurya, Sung-Hee Shin, Jae-Young Lee, In Seop Chang, Seung-Hyeon Moon \*

School of Environmental Science and Engineering, Gwangju Institute of Science and Technology (GIST), 123 Cheomdan-Gwagiro (Oryong-dong), Buk-gu, Gwangju 61005, Republic of Korea

## ARTICLE INFO

## Article history:

Received 15 September 2016

Received in revised form 28 September 2016

Accepted 29 September 2016

Available online 30 September 2016

## Keywords:

Bipolar membrane

Water splitting

Reverse electro dialysis

Energy storage system

Acid-base generation

Ion exchange membrane

## ABSTRACT

The acid-base junction potential can be used to generate electricity instead of the reduction-oxidation potential, which is often used for energy conversion between chemical energy and electricity. In this study, reverse bipolar electro dialysis was designed for energy conversion between acid-base solutions and electricity. Operating a flow battery with various HCl/NaOH concentrations, or an ABJFB, the current-voltage relationships showed typical polarization curves that were similar to those obtained in power generation from a fuel cell. We further demonstrated that the cell can be operated in a charge/discharge cyclic mode in a single cell. To the best of our knowledge, this study is the first report on a proof-of-concept experiment demonstrating the cyclic operation of an ABJFB.

© 2016 Elsevier B.V. All rights reserved.

## 1. Introduction

Most often, energy conversion between chemical energy and electricity occurs through redox reactions at the electrodes. For example, a fuel cell generates electricity by oxidizing fuel and reducing oxidants at the anodes and cathodes, respectively [1,2]. Lithium ions in a lithium battery move between electrodes with redox reactions [3,4]. A redox flow battery employs a redox couple for energy conversion [5–7].

Similar to the electric potential occurring at electrodes due to redox reactions, a difference in the concentrations of ionic species across an ion exchange membrane can create a membrane potential. That can be used to generate electricity when the potential is appropriately combined with electrode reactions. RED is a representative application of the concentration potential, in which sea water and river water are put into contact across ion exchange membranes [8,9]. In RED, cationic concentration differences across a CEM and anionic concentration differences across an AEM result in a membrane potential [10,11]. The

diffusion of corresponding ions through ion exchange membranes leads to the flow of electric current.

An ABJFB system is a form of the modified RED or RBED by introducing a BPM, which consists of a CEL and an AEL having opposite charges (Fig. 1 (a)) [12,13]. Due to the bias property of a BPM, protons and hydroxyl ions permeate through the CEL and the AEL respectively. The BPM is used to split water molecules into protons and hydroxyl ions under an electric field; accordingly, salt is converted to an acid and a base, as shown in Fig. 1 (a).

In this case, the membrane process is called bipolar membrane electro dialysis, or water splitting electro dialysis. As RED generates electricity from the membrane potential between high and low salt concentrations, the RBED may generate electricity from the membrane potential between acid and base solutions since the JP occurs with acid and base solutions through a CEL and an AEL of a BPM, respectively (Fig. 1 (b)). In addition, the ABJFB can be connected to multi-cells, which may generate electric power for practical application at a higher voltage (Fig. 1 (c)) [16].

Previously, an acid-base electrochemical cell was reported as a secondary battery powered by forced ionization [14]. However, it was suggested that palladium foil may be used as a depolarizing electrode instead of a BPM. Later, an acid-base concentration cell for electric power generation was patented using depolarizing electrodes [15]. It was found that the energy efficiency of this cell was significantly lower than the theoretical value because of the low permselectivity of the membranes. Other drawbacks of the systems previously studied are their use of hydrogen gas for electrode reactions and their

**Abbreviations:** Acid-base junction flow battery, ABJFB; Anion exchange membrane, AEM; Anion exchange layer, AEL; Bipolar membrane, BPM; Cation exchange layer, CEL; Cation exchange membrane, CEM; Junction potential, JP; Reduction oxidation, Redox; Reverse electro dialysis, RED; Reverse bipolar electro dialysis, RBED; Coulombic efficiency, CE; Voltage efficiency, VE; Energy efficiency, EE; Activity coefficient,  $\gamma$ ; Equilibrium constant of water,  $K_w$ ; Gas constant,  $R$ ; Absolute temperature,  $T$ ; Faraday constant,  $F$ ; Number of electrons,  $n$ ; Charging time,  $t_c$ ; Charging voltage,  $V_c$ ; Discharging time,  $t_d$ ; Discharging voltage,  $V_d$ .

\* Corresponding author.

E-mail address: [shmoon@gist.ac.kr](mailto:shmoon@gist.ac.kr) (S.-H. Moon).