



# Effect of type and stoichiometry of fuels on performance of polybenzimidazole-based proton exchange membrane fuel cells operating at the temperature range of 120–160 °C

Sung Kwan Ryu <sup>a,1</sup>, Mohanraj Vinothkannan <sup>b,c,1</sup>, Ae Rhan Kim <sup>a,d,\*</sup>, Dong Jin Yoo <sup>a,b,d,\*\*</sup>

<sup>a</sup> Department of Energy Storage/Conversion Engineering of Graduate School (BK21 FOUR), Hydrogen and Fuel Cell Research Center, Jeonbuk National University, Jeonju, Jeollabuk-do, 54896, Republic of Korea

<sup>b</sup> R&D Education Center for Whole Life Cycle R&D of Fuel Cell Systems, Jeonbuk National University, Jeonju, Jeollabuk-do, 54896, Republic of Korea

<sup>c</sup> Department of Energy Science and Engineering Research Center, Daegu Gyeongbuk Institute of Science & Technology (DGIST), Dalseong-Gun, Daegu, 42988, Republic of Korea

<sup>d</sup> Department of Life Science, Jeonbuk National University, Jeonju, Jeollabuk-do, 54896, Republic of Korea



## ARTICLE INFO

### Article history:

Received 3 July 2020

Received in revised form

8 August 2021

Accepted 12 August 2021

Available online 16 August 2021

### Keywords:

PEMFC

PA-PBI membrane

High temperature

Feed gas

Durability test

## ABSTRACT

Herein, a proton exchange membrane fuel cell (PEMFC) equipped with phosphoric acid-doped polybenzimidazole (PA-PBI) membrane was exploited to determine the effects of changing type and stoichiometry of feed gas at operating temperature from 120 to 160 °C. Results show that maximum power density of proposed system increases as increasing temperature, and varying the type and stoichiometry of feed gas. For example, a typical power density of 0.254, 0.299 and 0.389 W/cm<sup>2</sup> was obtained when operating PEMFC at 120, 140 and 160 °C respectively with pure hydrogen (H<sub>2</sub>) as feed gas. By contrast, power density of only 0.128, 0.194 and 0.243 W/cm<sup>2</sup> was achieved when operating the PEMFC under identical condition with reformed H<sub>2</sub> as feed gas. On the other hand, when varying oxygen (O<sub>2</sub>) stoichiometry from 2 to 6, power density of PEMFC vary from 0.330 to 0.472 W/cm<sup>2</sup> at 160 °C. At high temperature and high O<sub>2</sub> diffusion rate, reaction kinetics of electrodes and membrane were boosted, resulting lower mass-transfer resistance and higher PEMFC performance. In addition, we conducted long-term operation of PEMFC at 160 °C for 500 h to examine durability of PA-PBI. PA-PBI membrane was not lose open circuit voltage (OCV) significantly, indicating its good PEMFC durability.

© 2021 Elsevier Ltd. All rights reserved.

## 1. Introduction

In recent years, depletion of fossil fuels (oil, coal and natural gas) and increment of environmental pollution are being urged the humankind to seek alternative renewable energy sources with no or zero emission of pollutant gases (CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O). Proton

exchange membrane fuel cell (PEMFC) is a renewable energy device that can be widely used to convert chemical energy of fuels to electricity without emitting pollutant gases. These fuel cells have a wide range of applications in power plants, automobiles and various consumer electronics, owing to their fast startup and blackout times, high conversion efficiency, high power density, compact design and environmental friendliness. Hydrogen (H<sub>2</sub>), methanol, ethanol or formic acid is used as fuel for anode, while oxygen (O<sub>2</sub>) or air is exploited as fuel for cathode during PEMFC operation [1–6]. Generally, PEMFC which operate at low temperatures (30–90 °C) use a perfluorosulfonic acid (PFSA) membrane, such as Nafion, as a proton-transport medium [7–9], because it has high proton conductivity, and mechanical and chemical stabilities. However, the water level must be continuously maintained for sulfonic acid (SO<sub>3</sub>H) groups of Nafion membranes to enable efficient proton transport. Hence, an external humidifier must be installed to fully utilize Nafion membrane in PEMFC operating at

\* Corresponding author. Department of Life Science, Department of Energy Storage/Conversion Engineering of Graduate School (BK21 FOUR), and Hydrogen and Fuel Cell Research Center, Jeonbuk National University, Jeonju, Jeollabuk-do 54896, Republic of Korea.

\*\* Corresponding author. Department of Life Science, Department of Energy Storage/Conversion Engineering of Graduate School (BK21 FOUR), R&D Education Center for Whole Life Cycle R&D of Fuel Cell Systems, and Hydrogen and Fuel Cell Research Center, Jeonbuk National University, Jeonju, Jeollabuk-do 54896, Republic of Korea.

E-mail addresses: [kimaerhan@jbnu.ac.kr](mailto:kimaerhan@jbnu.ac.kr) (A.R. Kim), [djyoo@jbnu.ac.kr](mailto:djyoo@jbnu.ac.kr) (D.J. Yoo).

<sup>1</sup> The authors are contributed equally.