



ELSEVIER

Contents lists available at ScienceDirect

Catalysis Today

journal homepage: [www.elsevier.com/locate/cattod](http://www.elsevier.com/locate/cattod)

# Rapid photocatalytic degradation of nitrobenzene under the simultaneous illumination of UV and microwave radiation fields with a TiO<sub>2</sub> ball catalyst

Sangmin Jeong<sup>a</sup>, Heon Lee<sup>a</sup>, Hyunwoong Park<sup>b</sup>, Ki-Joon Jeon<sup>c</sup>, Young-Kwon Park<sup>d</sup>, Sang-Chul Jung<sup>a,\*</sup>

<sup>a</sup> Department of Environmental Engineering, Sunchon National University, 255 Jungang-ro, Sunchon, Jeonnam 57922, Republic of Korea

<sup>b</sup> School of Energy Engineering, Kyungpook National University, 80 Daehakro, Bukgu, Daegu 41566, Republic of Korea

<sup>c</sup> Department of Environmental Engineering, Inha University, 100 Inharo, Nam-gu, Incheon 22212, Republic of Korea

<sup>d</sup> School of Environmental Engineering, University of Seoul, 163 Seoulsiripdaero, Dongdaemun-gu, Seoul 02504, Republic of Korea

## ARTICLE INFO

### Article history:

Received 23 September 2016

Received in revised form 1 February 2017

Accepted 24 February 2017

Available online 3 March 2017

### Keywords:

TiO<sub>2</sub> photocatalyst

Microwave

Nitrobenzene

Reaction rate constant

Mechanism

## ABSTRACT

To use the microwave/ML/TiO<sub>2</sub> hybrid system as an advanced treatment of nitrobenzene (NB), a series of experiments were performed to examine the effects of microwave irradiation and auxiliary oxidants. The degradation of NB was carried out using different combinations of five-unit treatment techniques. The NB degradation rate increased with increasing microwave intensity. The circulation fluid velocity, concentration of H<sub>2</sub>O<sub>2</sub>, and the rate of O<sub>2</sub> gas injection showed the highest rate of degradation under optimal conditions. A significant synergistic effect was observed when H<sub>2</sub>O<sub>2</sub> addition was combined with the microwave/ML/TiO<sub>2</sub> hybrid process.

© 2017 Elsevier B.V. All rights reserved.

## 1. Introduction

Owing to the advances in industry, many organic compounds have been produced as organic solvents, which are contaminating soil and underground water [1,2]. A large portion of these organic compounds are volatile organic solvents and hydrophobic materials, whose specific gravity is larger than water. In addition, they are poisonous and mutagenic derivative materials, and are very difficult to decompose chemically and biologically, giving them significantly long half-life [3]. Nitrobenzene (NB) is used widely in areas, such as aniline synthesis, dyes, rubber making, textile, synthetic resins, pesticide, explosives, cosmetic, and drugs [4,5]. NB, which exists in the environment, is emitted mainly from the manufacturing process of chemical products or the use of products that contain these materials [6,7]. Even at low concentrations, NB can damage the reproductive cells of rodents, and the World Health Organization (WHO) defined NB as an animal carcinogenesis chemical compound [8–10]. For these reasons, this study assessed the decomposition of NB as a model pollutant.

Conventionally, NB in aqueous media is processed using physical, chemical, and biological techniques. The general treatments is composed of adsorption [11,12] and biodegradation [13,14]. These techniques can be effective but it occurs secondary pollution, resulting in high processing cost. Advanced oxidation processes (AOPs) have been shown to be effective in the destruction of aromatic wastewater pollutants [15,16]. Basically, the AOP process uses oxidizing hydroxyl radicals to oxidize pollutants using O<sub>3</sub>, H<sub>2</sub>O<sub>2</sub>, UV, and photocatalysts [17–21]. Among these methods, photocatalysis has been applied frequently for the advanced degradation of aromatic wastewater pollutants [22,23]. In particular, the TiO<sub>2</sub> photocatalytic process has significant advantages, such as available at room temperature, applicable under atmospheric pressure, complete mineralization, and low cost compared to the conventional treatments [24–26].

On the other hand, the use of TiO<sub>2</sub> as a photocatalyst has been limited by its high band gap (3.2 eV), meaning that it can be only activated by ultraviolet (UV) light. In addition, it has a low photo quantum efficiency and a high rate of electron–hole pair recombination [27,28]. Therefore, a method to enhance the processing efficiency is needed to decompose aromatic wastewater pollutants at high speed. Recently the effects of the microwave irradiation on the treatment of non-biodegradable materials in water using TiO<sub>2</sub>

\* Corresponding author.

E-mail address: [jsc@sunchon.ac.kr](mailto:jsc@sunchon.ac.kr) (S.-C. Jung).