


Available online at www.sciencedirect.com

ScienceDirect

journal homepage: www.elsevier.com/locate/hydro

The analysis of adhesion force at the interface of gas diffusion layer and channel in polymer electrolyte membrane fuel cell

Donggun Ko ^a, Seungwoo Doh ^b, Hyun Sun Park ^b, Moo Hwan Kim ^{a,b,*}

^a Department of Mechanical Engineering, Pohang University of Science and Technology (POSTECH), 77, Cheongam-ro, Nam-gu, Pohang-si, Gyeongsangbuk-do, Republic of Korea

^b Division of Advance Nuclear Engineering, Pohang University of Science and Technology (POSTECH), 77, Cheongam-ro, Nam-gu, Pohang-si, Gyeongsangbuk-do, Republic of Korea

ARTICLE INFO

Article history:

Received 10 April 2018

Received in revised form

14 June 2018

Accepted 28 June 2018

Available online 26 July 2018

Keywords:

Polymer electrolyte membrane fuel cell

Droplet deformation

Adhesion force

Pore gradient

X-ray visualization

ABSTRACT

The adhesion force of water droplet on the gas diffusion layer (GDL) is modeled based on the droplet deformation. The deformed droplet is represented as an ovoid shape. The adhesion force is calculated based on it and verified by the surface tilting experiment. The model predicts the shape of deformed droplet and adhesion force within 30% error, whereas previous models predict adhesion force with error larger than 30%. The modified model is used to compare the adhesion force among 3 types of GDL having pore gradient. The comparison result is well matched with the water distribution in polymer electrolyte membrane fuel cell (PEMFC) and water detachment phenomena at the GDL. High adhesion force makes more water accumulation at the interface of GDL and gas supplying channel. This makes different boundary condition and changes the water distribution in PEMFC.

© 2018 Hydrogen Energy Publications LLC. Published by Elsevier Ltd. All rights reserved.

Introduction

Polymer electrolyte membrane fuel cell (PEMFC) requires adequate water management because water distribution affects the efficiency of PEMFC directly. Reactant should be supplied properly to the catalyst layer through gas diffusion layer (GDL) to generate electricity. The diffusivity and permeability of reactant are inversely proportional to the water content in the GDL, so the amount of water must be as low as possible in the GDL. On the other hand, proton should

be transported through the membrane to generate the electricity. The proton conductivity of the membrane is directly proportional to the water content, so the amount of water must be controlled as high level in membrane. Therefore the transport of water and its distribution in PEMFC should be comprehended to maximize the performance of PEMFC.

Two crucial factors determine the water distribution in PEMFC. First is structure of porous media. The transport of water is governed by capillary pressure [1], so the structure of the porous media strongly affects the water distribution in the

* Corresponding author. 77 Cheongam-Ro, Nam-gu, Pohang, Gyeongbuk, Republic of Korea.

E-mail addresses: kdg_0306@postech.ac.kr (D. Ko), consider@postech.ac.kr (S. Doh), hejsunny@postech.ac.kr (H.S. Park), mhkim@postech.ac.kr (M.H. Kim).

<https://doi.org/10.1016/j.ijhydene.2018.06.180>

0360-3199/© 2018 Hydrogen Energy Publications LLC. Published by Elsevier Ltd. All rights reserved.