

# Hybrid electrochemical microfiltration treatment of reverse osmosis concentrate: A mechanistic study on the effects of electrode materials


Naresh Mameda<sup>a</sup>, Hyeona Park<sup>b</sup>, Kwang-Ho Choo<sup>a,b,\*</sup>

<sup>a</sup> Advanced Institute of Water Industry, Kyungpook National University, 80 Daehak-ro, Buk-gu, Daegu 41566, Republic of Korea

<sup>b</sup> Department of Environmental Engineering, Kyungpook National University, 80 Daehak-ro, Buk-gu, Daegu 41566, Republic of Korea



## GRAPHICAL ABSTRACT



## ARTICLE INFO

### Keywords:

Active anode  
Electrocatalysis  
Membrane filtration  
Non-active anode  
Reverse osmosis brine

## ABSTRACT

The reverse osmosis (RO) technology is promising as a key process for water reuse, but the RO brine (concentrate) needs proper treatments for minimal liquid disposals. This study investigated the potential of hybrid electrochemical microfiltration for the treatment of the RO concentrate from a municipal wastewater reuse plant. Two anodes (active Ir-RuO<sub>x</sub> and non-active Sb-SnO<sub>2</sub>) and two cathodes (stainless steel and carbon felt) were employed and compared in terms of the contaminants removal. The electrochemical microfiltration treatment achieved a substantial removal of color, turbidity, chemical oxygen demand, and fluorophores. However, the removal of the total nitrogen and organic carbon was limited. Then, mechanistic studies on the used electrode materials for the electrocatalysis of the RO concentrate were further conducted. The electrocatalysis that used a non-active anode improved the mineralization of the organics, whereas the active anode enhanced the denitrification. The combined use of the two anodes enabled the enhancement of the overall removal efficiencies. In addition, the oxidants (reactive chlorine/oxygen species) responsible for the organics and the nitrogen removals were elucidated. Overall, it was revealed that the electrochemical microfiltration that utilizes proper electrode combinations is a promising option for enhancing the treatment of RO concentrates with minimal disposals.

\* Corresponding author at: Department of Environmental Engineering, Kyungpook National University, 80 Daehak-ro, Buk-gu, Daegu 41566, Republic of Korea.  
E-mail address: [chookh@knu.ac.kr](mailto:chookh@knu.ac.kr) (K.-H. Choo).

<https://doi.org/10.1016/j.desal.2020.114617>

Received 11 May 2020; Received in revised form 13 June 2020; Accepted 15 June 2020

Available online 11 August 2020

0011-9164/ © 2020 Elsevier B.V. All rights reserved.