

Contents lists available at ScienceDirect

## Journal of Catalysis

journal homepage: www.elsevier.com/locate/jcat



# Base-free CO<sub>2</sub> hydrogenation to formic acid over Pd supported on defective carbon nitride modified by microwave and acid treatments



Eun Hyup Kim<sup>a,1</sup>, Yo Han Choi<sup>b,1</sup>, Min Hee Lee<sup>a</sup>, Jeehye Kim<sup>a</sup>, Hyung Bin Kim<sup>a</sup>, Kwang Young Kim<sup>a</sup>, Eun Cheol Ra<sup>a</sup>, Ju Hyeong Lee<sup>a</sup>, Jae Sung Lee<sup>a,\*</sup>

#### ARTICLE INFO

Article history: Received 7 November 2020 Revised 7 March 2021 Accepted 9 March 2021 Available online 18 March 2021

Keywords:
Base-free CO<sub>2</sub> hydrogenation to formic acid
Pd/g-C<sub>3</sub>N<sub>4</sub>
Hybrid microwave annealing
Acid treatments
Defects

#### ABSTRACT

Graphitic carbon nitride  $(g-C_3N_4)$  is synthesized via pyrolyzing urea by hybrid microwave annealing (HMA) to support Pd catalyst for direct  $CO_2$  hydrogenation to formic acid under a base-free condition. The HMA produces fragmented  $C_3N_4$  sheets with abundant defects along their edges, because of the high annealing temperature (>900 °C) in an extremely short time (<5 min). The acid treatment of  $C_3N_4$  further reduces its grain sizes forming additional defect sites to anchor small Pd nanoparticles. The modified  $C_3N_4$  provides ample  $CO_2$  adsorption sites relative to  $C_3N_4$  pyrolyzed by the conventional furnace annealing at 550 °C for 4 h. The Pd catalyst supported on the defective  $C_3N_4$  exhibits the benchmark performance ever reported for base-free  $CO_2$ -to-HCOOH conversion in terms of both palladium time yield based on total Pd, and turnover frequency based on exposed surface Pd atoms. The enhanced performance is explained by interplay between small Pd nanoparticles and the abundant  $CO_2$  supply from nearby defect sites along the edges of the modified  $C_3N_4$  sheets.

© 2021 Elsevier Inc. All rights reserved.

### 1. Introduction

Mitigation of carbon dioxide ( $CO_2$ ) emission has become an urgent issue to slow down the global climate change [1,2]. Carbon capture and storage (CCS) in underground geological formation has been pursued aggressively as an effective strategy for  $CO_2$  mitigation [3–5], but recently carbon capture and utilization (CCU) is considered a more desirable option in practice, which convert  $CO_2$  to valuable chemicals and fuels [6–10]. Formic acid (CCU) is one of those promising chemicals with diverse applications, which can be synthesized from catalytic hydrogenation of  $CO_2$  [7,11]. Recently, it is also receiving attention as an effective liquid CCU1 describes that a high volumetric capacity (CCU3 gH2/L), low toxicity, and low flammability [7,11–15], and decomposition of CCU3 and CU4 occurs readily on CU6 catalysts under mild conditions. It can also serve as a liquid fuel for formic acid fuel cells [16].

Formic acid is industrially synthesized by a two-step process of methanol carbonylation to methyl formate in the presence of a strong base catalyst, followed by hydrolysis [17]. Synthesis by

E-mail address: jlee1234@unist.ac.kr (J.S. Lee).

<sup>1</sup> These authors contributed equally to this work.

hydrogenation of  $CO_2$  is thermodynamically unfavourable  $(\Delta G^{\circ} = +32.9 \text{ kJ mol}^{-1})$ . The equilibrium limitation could be somewhat mitigated by carrying out the reaction in an aqueous system  $(\Delta G^{\circ} = -4 \text{ kJ mol}^{-1})$  [18], yet more favourable thermodynamics could be realized by performing the reaction in a basic solvent  $(\Delta G^{\circ} = -9.5 \text{ kJ mol}^{-1})$  [19,20]. For example, Filonenko *et al.* applied triethyl amine (NEt<sub>3</sub>) as the most effective base for this reaction [21]. However, the reaction forms an adduct of amine and formate (HCOO<sup>-</sup>), and the recovery of HCOOH from the adduct requires several additional processes [18]. To make the separation easier, Upadhyay and Srivastava introduced ionic liquids with a basic amino group [22]. But, the recycling of the expensive ionic liquid is essential, and the separation of this ionic liquid also requires additional processing.

The base-free  $CO_2$  hydrogenation directly to HCOOH can make the product recovery process much simpler without such formate-base adduct formation. Instead, one needs to overcome the kinetic and thermodynamic barriers of the hydrogenation of the stable  $CO_2$  molecule. In the present work, we employ graphitic carbon nitride  $(g-C_3N_4)$  as a basic catalyst support for Pd metal to promote adsorption of acidic  $CO_2$  molecules. Carbon materials containing nitrogen are well-known  $CO_2$  adsorbents with the nitrogen acting as a basic site [23–26]. Carbon nitride contains such a high N content, making it well-suited for the purpose [27–29]. In our

<sup>&</sup>lt;sup>a</sup> School of Energy and Chemical Engineering, Ulsan National Institute of Science and Technology (UNIST), Ulsan 44919, South Korea <sup>b</sup> Division of Advanced Nuclear Engineering, Pohang University of Science and Technology (POSTECH), Pohang 790-784, South Korea

<sup>\*</sup> Corresponding author.