


AUTO SHEET FEEDING FLATBED CUTTER

FC-100D1

- Multiple cutter sets for diverse materials; Equipped with oscillating, bevel, rotary, drag, roller, pen and creasing cutters;
- Self-developed OS, software, plugins and box library simplify operation;
- Forklift feeding supports full pallet loading to save time; Feeding while cutting greatly boosts productivity;
- Automatic tool alignment ensures precise cutting height; Smart light positioning avoids material deviation and improves accuracy;
- Built-in roll feeder processes sheet and roll materials;
- Reverse cutting achieves standard carton manufacturing process;
- Safety protection system monitors real-time operation; Timely alarm safeguards operator safety.



10 Inch Full
Touch Screen



Eight Knife Head Design



Intelligent
operation



Performance
improvement



Real-time
monitoring



Eight kinds
of tool



HEFEI SAGA COMPUTER NUMERICAL CONTROL Co.,Ltd.

Tel: +86-551-63444544

Address: Block7 Liando U-valley, Jilin Crossing of
Fanhua Avenue, Baohe District, Hefei, Anhui Province, PRC



Website



WeChat

PRODUCT PARAMETERS:

Model name		FC-100D1
Cutting control system		X-AC Servo Motor Y-AC Servo Motor
Positioning sensor type	Webcam	
Control panel		10 inch capacitive touch screen
Number of tool holders	Five tool holders(2 carving knives, 1 indentation, 1 V cutter, 1 vibrating knife) Oscillating Knife Assembly(1 creasing knife, 1 bevel knife, 1 oscillating knife)	
Blade types		Graver/pen/indentation/V cutter/vibrating knife
Machine performance		
Machine Working Mode	Support front & back dot cutting, multiple cutters optional	
Media hold method	Vacuum suction	
Scanning code type	Mark/QR code	
Maximum width	1165mmX1610mm	
Maximum cutting size	1000mmX1290mm	
Scanning speed	5-10s	
Cutting speed	10-700	
Cutting Force		No Pressure No Pressure
Maximum Paper Weight	7mm	
Minimum character cutting size	About 10mm² (Varies from contour paterns and medias)	
Maximum paper feeding size	L:1200mm W:900mm	
Mechanical resolution	0.02mm	
Programmable resolution	HPGL 0.025mm	
Repeat precision	≤0.05mm	
Cutting Media Types	Cardboard, corrugated paper, PVC, gray cardboard, etc.	
Software and compatibility		
Connectivity		USB , WiFi, U disk
Software and compatibility	CutArtist software,Corel Draw/ Illustrator Plug-in	
Power and working environment requirements		
Working voltage and current		200VAC-240VAC,50/60Hz
Working power	Maximum 8.4KW(Including 2 sets of 2.2KW suction air pumps)	
Operation environment	Temperature +5℃ to +35 ℃ (Fahrenheit 41-95),Humidity 30% -75% (Non-condensing)	
Dimensions and Weight		
Actual dimensions	1650mmX1700mmX1550mm(Feeding platform) 2465mmX1955mmX1320mm(Flatbed cutter)	
Package dimensions	1800mmX1845mm X1795mm(Feeding platform) 2700mm X 2080mm X 1520mm(Flatbed cutter)	

This parameter is subject to change without prior notice. The company reserves the right of final interpretation

APPLICABLE MATERIALS:

Cardboard

Corrugated Board

PVC

Gray Cardboard

APPLICATION DISPLAY :



Packaging box



Paper bag & Envelope bag



Table tag



Corrugated board



Packaging bag



Gray Cardboard