

SAGA FLATBED CUTTER

SG-FCT6698

- Intelligent control system and panel;
- The running pressure and speed are greatly increased;
- Real-time monitoring;
- Four tools in four combination;
- Convenient offline output;
- Linear guides make job more accurate.



Intelligent
operation



Performance
improvement



Real-time
monitoring



Four kinds
of tool



Multiple
Connection
Methods



7 Inch Full
Touch Screen



Four Knife Head Design
Die-cutting + Indentation



HEFEI SAGA COMPUTER NUMERICAL CONTROL Co.,Ltd.

☎ Tel: +86-551-63444544

📍 Address: Block7 Liando U-valley, Jilin Crossing of
Fanhua Avenue, Baohe District, Hefei, Anhui Province, PRC



Website



WeChat

PRODUCT PARAMETERS:

Model name		SG-FCT6698
Cutting control system		X- High-power brushless servo motor Y- High-power brushless servo motor
Positioning sensor type		Digital camera (CCD)
Control panel		7 inch capacitive touch screen
Number of tool holders		Double tool holders
Blade types		Blade, creasing tool and pen
Number of tangential blade		Double tool holders
Tangential blade types		Blade, creasing tool
Machine performance		
Media hold method		Vacuum suction
Scanning code type		Mark/QR code
Maximum width		730mmX1065mm
Maximum cutting size		650mmX1020mm
Scanning speed		5-10s
Maximum actual cutting speed		100mm/s-700mm/s 10mm/s Step
Maximum Cutting Force		Creasing: 0-1900gf (10gf 1Step) Blade: 0-1900gf (10gf 1Step)
Maximum Paper Weight		600g (Varies from different cutting materials)
Minimum character cutting size		About 10mm² (Varies from contour patterns and medias)
Mechanical resolution		0.02mm
Programmable resolution		HPGL 0.025mm
Repeat precision		≤0.05mm
Cutting Media Types		Self-adhesive sticker, cardboard, corrugated paper, etc.
Software and compatibility		
Connectivity		USB , TCP , WiFi, U disk , Interface
Software and compatibility		Corel Draw/ Illustrator Plug-in (U disk Interface)
Power and working environment requirements		
Working voltage and current		100VAC-120VAC,50/60Hz, Maximum current 6.8A 200VAC-240VAC,50/60Hz, Maximum current 3.4A
Power		Maximum 350W
Vacuum Pump voltage and current	110VAC, 50Hz, Rated current 15.2A, 60Hz, Rated current 16.5A 220VAC, 50Hz, Rated current 6.2A, 60Hz, Rated current 8.6A	
Power(Vacuum Pump)		50Hz, 1.1KW; 60Hz, 1.3KW
Stand		Included
Operation environment		Temperature +5℃ to +35 ℃ (Fahrenheit 41-95), Humidity 30% -75% (Non-condensing)
Dimensions and Weight		
Actual dimensions		L1360mm×W1350mm×H1015mm
Package dimensions		L1860mm×W1480mm×H615mm
Gross/Net weight		219ka/139ka

This parameter is subject to change without prior notice. The company reserves the right of final interpretation

APPLICABLE MATERIALS:

Jam Paper

Coated Paper

Sticker

Corrugated Board

Magnetic Sticker

PVC

APPLICATION DISPLAY :

