## ∢ 单衬型/双衬型

m


									2.45
代码	类型	材	质	轴套	表面处理	滚珠	保持架	密封圈	使用环境温度
1 (1)=	天至	国标	相当	硬度	农田处理	材质	材质	材质	使用外現画及
E-LMC02	单衬型				_				77
E-LMC03	平的主	GCr15	SUJ2	56HRC~	无电解镀镍	GCr15	树脂	丁腈橡胶	-15~80°C
E-LMC12	双衬型	GCI15	3032	SOURC ~	_	GCITS	1次) 月日	J胴像版	-15~60 C
E-LMC13	双利至				无电解镀镍			1X	


- 轴套、滚珠材质SUJ2相当于GCr15。
- 保持架材质树脂相当于DURACON M90。

! 如对防锈有要求,请优先选用镀镍产品!

双衬型







m 미리





## 🧿 单衬型

型号									偏心	滚珠	基本额	定负载	T = ( )			
代码		t			L		L1		m	D <sub>1</sub>	r	(最大)	列数	C(动)N	Co(静)N	重量(g)
	4	+0.003	8	+0.006	12	+0.1	_	_		_	0.3	0.016	(2)	85	125	1.9
	5	-0.011	10	-0.011	15	-0.2	8			9.6		0.016	37	165	205	3.9
	6		12	+0.006	19		11.3		1.1	11.5	0.4		4	205	260	8.3
	8		15	-0.013	24		15.3			14.3	0.4		4	260	375	15
	10	+0.003	19		29	+0.2	19.4	0 -0.4	1.3	18		0.024		370	545	30
	12		21	+0.006	30	-0.4	20.4		1.3	20			20	410	595	40
E-LMC02	16		28	0.0.0	37		23.3		1.6	27	0.8		5	770	1175	70
E-LMC03	20		32		42		27.3		1.0	30.5		100	5	880	1365	95
	25	+0.003	40	+0.006 -0.018	59		37.3		1.85	38		0.030		975	1565	235
	30	0.013	45		64		40.8		1.00	43	1X			1565	2735	260
	35		52		70	+0.2	45.3	-0.5	2.1	49	1.5		6	1665	3135	420
	40	+0.003	60	+0.006	80		56.3	- 4	2.1	57	D.	0.040		2155	4015	650
	50		80		100		68.8		2.6	76.5				3815	7935	1695

## 🖸 双衬型

1Kgf=9.81N

型号		р				1 1	18	m	D <sub>1</sub> r	r	偏心	滚珠	基本额	定负载	静态允许	重量(g)	
代码	d				_		_	JEL .		""   D1	'	(最大)	列数	C(动)N	Co(静)N	力矩(N/m)	里里(9)
	4		8	+0.006	23		1 = 1	),.—			0.3	0.016		175	250	0.6	4.5
	5		10	-0.013	28		18.2			9.6		0.010		260	410	1.35	10
	6		12	+0.006	35	15	24.8		1.1	11.5			4	320	525	2.15	15
	8	+0.003	15	-0.015	45	+0.3	32.8	0		14.3	0.4		4	430	780	4.3	30
	10		19		55	-0.6	41.4	-0.5	1.3	18		0.024		585	1095	7.2	60
E-LMC12	12		21	+0.006	57		43.4		1.5	20		0.024		655	1195	10.5	75
E-LMC12	16		28		70		49.8		1.6	27	0.8		5	1225	2345	19.5	140
L-LWC13	20		32	+0.006	80		57.8		1.0	30.5			J	1395	2735	26.5	175
	25	+0.003 -0.015	40	-0.021	112		78.3		1.85	38		0.030		1555	3135	43	435
	30		45		123		85.3	0	1.00	43				2485	5485	82.5	475
	35		52	+0.006	135	+0.3	94.8	-0.6	2.1	49	1.5		6	2645	6265	105	790
	40	+0.003	60	-0.024	151		116.8		2.1	57		0.040		3425	8035	145	1165
	50		80		192		142.8		2.6	76.5				6075	15895	395	2095

**!** 1Kgf=9.81N




$\circ$					
	D				
1	代码		d		
	MC02	4	+0.003	8	
E-L	MC03	5	-0.011	10	

🖸 双衬型

型	D			
代码		d	U	
ECIMC)2	6	+0.003	12	
E-LMC13	8	-0.013	15	

未税价(元)





E-LMC02-d4 E-LMC12-d6

AUTOMATIONEXPERT