

betaSandwich: Staging

Ivan Jacob Agaloos Pesigan

Staging...

References

R Core Team. (2022). *R: A language and environment for statistical computing*. R Foundation for Statistical Computing. Vienna, Austria. <https://www.R-project.org/>

1 Standardized Slopes

```
df <- nas1982
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = df)
mvn <- BetaN(object)
adf <- BetaADF(object)
hc3 <- BetaHC(object, type = "hc3")
summary(mvn)

#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t      p    0.05%   0.5%   2.5%  97.5%  99.5% 99.95%
#> NARTIC  0.4951 0.0759 6.5272 0.000   0.2268 0.2905 0.3421 0.6482 0.6998 0.7635
#> PCTGRT  0.3915 0.0770 5.0824 0.000   0.1190 0.1837 0.2360 0.5469 0.5993 0.6640
#> PCTSUPP 0.2632 0.0747 3.5224 0.001  -0.0011 0.0616 0.1124 0.4141 0.4649 0.5276

summary(adf)

#> Call:
#> BetaADF(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t      p    0.05%   0.5%   2.5%  97.5%  99.5% 99.95%
#> NARTIC  0.4951 0.0674 7.3490 0.0000   0.2568 0.3134 0.3592 0.6311 0.6769 0.7335
#> PCTGRT  0.3915 0.0710 5.5164 0.0000   0.1404 0.2000 0.2483 0.5347 0.5830 0.6426
#> PCTSUPP 0.2632 0.0769 3.4231 0.0014  -0.0088 0.0558 0.1081 0.4184 0.4707 0.5353
```

```

summary(hc3)

#> Call:
#> BetaHC(object = object, type = "hc3")
#>
#> Standardized regression slopes with HC3 standard errors:
#>      est      se      t      p  0.05%  0.5%  2.5% 97.5% 99.5% 99.95%
#> NARTIC  0.4951 0.0786 6.3025 0.0000  0.2172 0.2832 0.3366 0.6537 0.7071 0.7731
#> PCTGRT  0.3915 0.0818 4.7831 0.0000  0.1019 0.1707 0.2263 0.5567 0.6123 0.6810
#> PCTSUPP 0.2632 0.0855 3.0786 0.0037 -0.0393 0.0325 0.0907 0.4358 0.4940 0.5658

coef(mvn)

#>      NARTIC      PCTGRT      PCTSUPP
#> 0.4951451 0.3914887 0.2632477

coef(adf)

#>      NARTIC      PCTGRT      PCTSUPP
#> 0.4951451 0.3914887 0.2632477

coef(hc3)

#>      NARTIC      PCTGRT      PCTSUPP
#> 0.4951451 0.3914887 0.2632477

vcov(mvn)

#>      NARTIC      PCTGRT      PCTSUPP
#> NARTIC  0.005754524 -0.003360334 -0.002166127
#> PCTGRT -0.003360334  0.005933462 -0.001769723
#> PCTSUPP -0.002166127 -0.001769723  0.005585256

vcov(adf)

#>      NARTIC      PCTGRT      PCTSUPP
#> NARTIC  0.004539472 -0.002552698 -0.001742698
#> PCTGRT -0.002552698  0.005036538 -0.001906216
#> PCTSUPP -0.001742698 -0.001906216  0.005914088

vcov(hc3)

#>      NARTIC      PCTGRT      PCTSUPP
#> NARTIC  0.006172168 -0.003602529 -0.001943469
#> PCTGRT -0.003602529  0.006699155 -0.002443584
#> PCTSUPP -0.001943469 -0.002443584  0.007311625

confint(mvn)

```

```

#>           2.5%      97.5%
#> NARTIC  0.3420563 0.6482339
#> PCTGRT  0.2360380 0.5469395
#> PCTSUPP 0.1124272 0.4140682

confinf(adf)

#>           2.5%      97.5%
#> NARTIC  0.3591757 0.6311146
#> PCTGRT  0.2482683 0.5347091
#> PCTSUPP 0.1080509 0.4184444

confinf(hc3)

#>           2.5%      97.5%
#> NARTIC  0.33659828 0.6536920
#> PCTGRT  0.22631203 0.5566654
#> PCTSUPP 0.09068548 0.4358099

```

2 Multiple Correlation

```

df <- nas1982
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = df)
std_mvn <- BetaN(object)
std_adf <- BetaADF(object)
std_hc3 <- BetaHC(object, type = "hc3")
mvn <- RSqBetaSandwich(std_mvn)
adf <- RSqBetaSandwich(std_adf)
hc3 <- RSqBetaSandwich(std_hc3)
summary(mvn)

#> Call:
#> RSqBetaSandwich(object = std_mvn)
#>
#> Multiple correlation with MVN standard errors:
#>      est      se      t p 0.05%  0.5%  2.5% 97.5% 99.5% 99.95%
#> rsq 0.8045 0.0328 24.5344 0 0.6885 0.7161 0.7383 0.8707 0.8930 0.9205
#> adj 0.7906 0.0351 22.5014 0 0.6663 0.6958 0.7197 0.8615 0.8854 0.9149

summary(adf)

#> Call:
#> RSqBetaSandwich(object = std_adf)
#>
#> Multiple correlation with MVN standard errors:

```

```

#>      est      se      t p 0.05% 0.5% 2.5% 97.5% 99.5% 99.95%
#> rsq 0.8045 0.0287 28.0431 0 0.7030 0.7271 0.7466 0.8624 0.8819 0.9060
#> adj 0.7906 0.0307 25.7193 0 0.6818 0.7076 0.7285 0.8526 0.8735 0.8993

summary(hc3)

#> Call:
#> RSqBetaSandwich(object = std_hc3)
#>
#> Multiple correlation with HC3 standard errors:
#>      est      se      t p 0.05% 0.5% 2.5% 97.5% 99.5% 99.95%
#> rsq 0.8045 0.0313 25.6916 0 0.6937 0.72 0.7413 0.8677 0.8890 0.9153
#> adj 0.7906 0.0336 23.5627 0 0.6719 0.70 0.7229 0.8583 0.8811 0.9093

coef(mvn)

#>      rsq      adj
#> 0.8045263 0.7905638

coef(adf)

#>      rsq      adj
#> 0.8045263 0.7905638

coef(hc3)

#>      rsq      adj
#> 0.8045263 0.7905638

vcov(mvn)

#>      rsq      adj
#> rsq 0.001075300 0.001152107
#> adj 0.001152107 0.001234400

vcov(adf)

#>      rsq      adj
#> rsq 0.0008230557 0.0008818454
#> adj 0.0008818454 0.0009448343

vcov(hc3)

#>      rsq      adj
#> rsq 0.0009806163 0.001050660
#> adj 0.0010506603 0.001125707

confint(mvn)

```

```

#>           2.5%      97.5%
#> rsq 0.7383498 0.8707027
#> adj 0.7196605 0.8614672

confint(adf)

#>           2.5%      97.5%
#> rsq 0.7466296 0.8624229
#> adj 0.7285317 0.8525960

confint(hc3)

#>           2.5%      97.5%
#> rsq 0.7413304 0.8677221
#> adj 0.7228540 0.8582736

```

3 Differences of Standardized Slopes

```

df <- nas1982
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = df)
std_mvn <- BetaN(object)
std_adf <- BetaADF(object)
std_hc3 <- BetaHC(object, type = "hc3")
mvn <- DiffBetaSandwich(std_mvn)
adf <- DiffBetaSandwich(std_adf)
hc3 <- DiffBetaSandwich(std_hc3)
summary(mvn)

#> Call:
#> DiffBetaSandwich(object = std_mvn)
#>
#> Difference between standardized regression coefficients with MVN standard errors:
#>           est      se      z      p  0.05%   0.5%   2.5%  97.5%
#> NARTIC-PCTGRT  0.1037 0.1357 0.7640 0.4449 -0.3428 -0.2458 -0.1623 0.3696
#> NARTIC-PCTSUPP 0.2319 0.1252 1.8524 0.0640 -0.1800 -0.0906 -0.0135 0.4773
#> PCTGRT-PCTSUPP 0.1282 0.1227 1.0451 0.2960 -0.2755 -0.1878 -0.1123 0.3688
#>           99.5% 99.95%
#> NARTIC-PCTGRT  0.4531 0.5501
#> NARTIC-PCTSUPP 0.5544 0.6438
#> PCTGRT-PCTSUPP 0.4443 0.5320

summary(adf)

#> Call:
#> DiffBetaSandwich(object = std_adf)

```

```

#>
#> Difference between standardized regression coefficients with MVN standard errors:
#>           est      se      z      p    0.05%    0.5%    2.5%  97.5%
#> NARTIC-PCTGRT  0.1037 0.1212 0.8555 0.3923 -0.2950 -0.2084 -0.1338 0.3411
#> NARTIC-PCTSUPP 0.2319 0.1181 1.9642 0.0495 -0.1566 -0.0722  0.0005 0.4633
#> PCTGRT-PCTSUPP 0.1282 0.1215 1.0555 0.2912 -0.2716 -0.1847 -0.1099 0.3664
#>           99.5% 99.95%
#> NARTIC-PCTGRT  0.4158 0.5024
#> NARTIC-PCTSUPP 0.5360 0.6204
#> PCTGRT-PCTSUPP 0.4412 0.5281

summary(hc3)

#> Call:
#> DiffBetaSandwich(object = std_hc3)
#>
#> Difference between standardized regression coefficients with HC3 standard errors:
#>           est      se      z      p    0.05%    0.5%    2.5%  97.5%
#> NARTIC-PCTGRT  0.1037 0.1417 0.7316 0.4644 -0.3626 -0.2613 -0.1741 0.3814
#> NARTIC-PCTSUPP 0.2319 0.1318 1.7595 0.0785 -0.2018 -0.1076 -0.0264 0.4902
#> PCTGRT-PCTSUPP 0.1282 0.1375 0.9329 0.3509 -0.3241 -0.2259 -0.1412 0.3977
#>           99.5% 99.95%
#> NARTIC-PCTGRT  0.4686 0.5699
#> NARTIC-PCTSUPP 0.5714 0.6656
#> PCTGRT-PCTSUPP 0.4823 0.5806

coef(mvn)

#> NARTIC-PCTGRT NARTIC-PCTSUPP PCTGRT-PCTSUPP
#>      0.1036564      0.2318974      0.1282410

coef(adf)

#> NARTIC-PCTGRT NARTIC-PCTSUPP PCTGRT-PCTSUPP
#>      0.1036564      0.2318974      0.1282410

coef(hc3)

#> NARTIC-PCTGRT NARTIC-PCTSUPP PCTGRT-PCTSUPP
#>      0.1036564      0.2318974      0.1282410

vcov(mvn)

#>           NARTIC-PCTGRT NARTIC-PCTSUPP PCTGRT-PCTSUPP
#> NARTIC-PCTGRT  0.018408653  0.009511262 -0.008897391
#> NARTIC-PCTSUPP 0.009511262  0.015672035  0.006160773
#> PCTGRT-PCTSUPP -0.008897391  0.006160773  0.015058164

vcov(adf)

```

```
#>          NARTIC-PCTGRT NARTIC-PCTSUPP PCTGRT-PCTSUPP
#> NARTIC-PCTGRT      0.014681407      0.006928651     -0.007752755
#> NARTIC-PCTSUPP      0.006928651      0.013938955      0.007010303
#> PCTGRT-PCTSUPP     -0.007752755      0.007010303      0.014763058
```

`vcov(hc3)`

```
#>          NARTIC-PCTGRT NARTIC-PCTSUPP PCTGRT-PCTSUPP
#> NARTIC-PCTGRT      0.020076382      0.009274583     -0.010801799
#> NARTIC-PCTSUPP      0.009274583      0.017370731      0.008096148
#> PCTGRT-PCTSUPP     -0.010801799      0.008096148      0.018897947
```

`confint(mvn)`

```
#>          2.5%      97.5%
#> NARTIC-PCTGRT -0.16226855 0.3695814
#> NARTIC-PCTSUPP -0.01346652 0.4772614
#> PCTGRT-PCTSUPP -0.11226950 0.3687516
```

`confint(adf)`

```
#>          2.5%      97.5%
#> NARTIC-PCTGRT -0.1338262589 0.3411391
#> NARTIC-PCTSUPP 0.0004975295 0.4632974
#> PCTGRT-PCTSUPP -0.1099011119 0.3663832
```

`confint(hc3)`

```
#>          2.5%      97.5%
#> NARTIC-PCTGRT -0.17405314 0.3813660
#> NARTIC-PCTSUPP -0.02642203 0.4902169
#> PCTGRT-PCTSUPP -0.14119483 0.3976769
```